

各種アルミ丸パイプ(1)

A = A 1070 T D C = A 6063 T E
 B = A 5052 T D D = A 6063 T D
 長さ⇒4000

外径	肉 厚						
	1.0	1.4	1.5	2.0	3.0	4.0	5.0
6	A・D						
8	A・D	B					
9	D						
10	A・C・D	B	A				
11	C						
12	A・B・C・D			A・B・C			
12.7	A						
13	C						
14	A・C			A			
15	A・C・D	B					
16	A・C・D		A・C・D	A・B	B		
17	A						
18	A・C・D		A・D				
19	A・B・C・D		A・C・D	A・B・D	A		
20	A・C・D	B	A・C・D	A・B・C・D	B		
22	A・C・D		A・C・D	A・B・C・D	B・D		
25	A・C・D		A・C・D	A・B・C・D	A・B・C・D		
28	C・D		C・D	A・B・C・D	B・C		
30	A・C・D	B	C・D	A・B・C・D	A・B・C・D		
32	D		C・D	A・B・C・D	A・B・C・D		
35	D		C・D	A・B・C・D	A・B・C・D		
38			C・D	A・B・C・D	A・B・C・D	B	B
40	A・D		C・D	A・B・C・D	A・B・C・D	A・B	B
42				A			
43			A				
45	D		C	A・B・C・D	A・B・C・D		A・B
50	D		A・C・D	A・B・C・D	A・B・C・D	A・B	A・B・C・D

各種アルミ丸パイプ(2)

A = A1070 T D C = A6063 T E
 B = A5052 T D D = A6063 T D
 長さ⇒4000

外径	肉 厚						
	1.0	1.4	1.5	2.0	3.0	4.0	5.0
55				C・D	C・D		B
60				B・C・D	A・B・C・D	A・B	A・B・C・D
65				C	A・B・C・D		A・B
70					A・B・C・D		A・B・D
75					A・B・C・D		A・B
80					A・B・C・D	B	A・B・D
85							A
90					A・C・D	B	A・B・C・D
100					A・B・C・D	A	A・B・C・D
110					A・C・D		A・B・C・D
120					A・C・D	B	A・B・C・D
130					A・B・D		A・B・C
140							B
150					A		A・B・C・D
165							A

A5056丸パイプ(A)

長さ⇒2005

外径 × 肉厚	kg/m	外径 × 肉厚	kg/m
50 × 10	3.34	190 × 30	39.97
60 × 10	4.17	200 × 15	23.11
70 × 10	5.00	20	29.98
80 × 10	5.83	30	42.46
90 × 10	6.67	220 × 20	33.31
100 × 10	7.50		
15	10.62		
20	13.33		
30	17.49		
110 × 10	8.33		
20	14.99		
120 × 10	9.16		
15	13.12		
20	16.66		
130 × 10	10.00		
20	18.32		
140 × 10	10.83		
20	19.99		
150 × 10	11.66		
15	16.86		
20	21.65		
160 × 20	23.32		
30	32.47		
170 × 20	24.98		
30	34.97		
180 × 15	20.61		
20	26.65		
30	37.47		
190 × 20	28.31		

A5056丸パイプ(B)(1)

長さ⇨乱尺

外径 × 肉厚	外径 × 肉厚	外径 × 肉厚	外径 × 肉厚
14 × 3.5	45 × 10	75 × 20	120 × 30
16 × 3.5	15	80 × 5	130 × 10
18 × 5	48 × 10.5	10	15
20 × 5	50 × 5	15	20
21 × 3.5	7.5	20	30
22 × 5	10	85 × 5	140 × 10
24 × 4	15	10	15
× 4.5	20	15	20
25 × 7	55 × 5	20	150 × 10
26 × 5.5	10	90 × 5	15
28 × 4.5	15	10	20
8	60 × 5	15	30
30 × 3	7.5	20	160 × 10
5	10	95 × 5	15
7.5	15	10	20
10	20	15	30
31 × 3.5	65 × 5	20	170 × 10
33 × 7.5	10	100 × 5	15
35 × 5	15	10	20
10	17.5	15	30
36 × 9.25	20	20	180 × 10
37.5 × 5	70 × 5	30	15
38 × 7.5	10	110 × 10	20
40 × 3	12.5	15	30
5	15	20	190 × 10
7.5	20	30	15
10	75 × 5	120 × 10	20
15	10	15	200 × 10
45 × 5	15	20	15

A5056丸パイプ(B)(2)

長さ⇒乱尺

外径 × 肉厚	外径 × 肉厚	外径 × 肉厚	外径 × 肉厚
200 × 20			
30			
210 × 20			
220 × 20			
230 × 20			
240 × 20			
250 × 20			
260 × 20			
280 × 20			
300 × 20			
320 × 25			

63S平角パイプ

長さ⇒5000

縦 × 横 × 肉厚	kg/P	縦 × 横 × 肉厚	kg/P
10 × 15 × 1.2	0.750	30 × 70 × 3.0	7.615
10 × 20 × 1.2	0.895	30 × 100 × 2.0	6.850
12 × 25 × 1.2	1.150	× 2.5	8.440
15 × 20 × 1.5	1.295	40 × 60 × 2.0	5.185
15 × 25 × 1.5	1.505	× 2.5	6.415
× 2.0	1.945	× 3.0	7.615
15 × 30 × 1.5	1.705	× 4.0	10.00
× 2.0	2.225	40 × 70 × 3.0	8.500
20 × 30 × 1.5	1.905	40 × 80 × 2.0	6.265
× 2.0	2.485	× 2.5	7.765
× 2.5	3.040	× 3.0	9.235
20 × 40 × 1.5	2.310	40 × 110 × 2.0	7.915
× 2.0	3.035	50 × 70 × 2.0	6.265
× 2.5	3.715	50 × 100 × 1.8	7.140
× 3.0	4.375	× 2.0	7.885
25 × 30 × 3.0	3,970	× 2.5	9.790
25 × 40 × 3.0	4.800	× 3.0	11.67
25 × 50 × 1.5	2.925	50 × 150 × 2.5	13.17
× 3.0	3.835	× 3.0	15.72
25 × 60 × 2.0	4.375	60 × 120 × 2.5	11.90
30 × 40 × 1.5	2.780	× 2.8	13.19
× 2.0	3.565	80 × 100 × 2.7	12.76
× 3.0	5.185		
30 × 50 × 2.0	4.105		
30 × 60 × 1.5	3.535		
× 2.0	4.650		
× 2.5	5.740		
30 × 70 × 2.0	5.185		
× 2.4	6.200		

63S四角パイプ

長さ⇒5000

縦 × 横 × 肉厚	kg/P	縦 × 横 × 肉厚	kg/P
9 × 1.2	0.510		
10 × 1.0	0.485		
12 × 1.2	0.705		
15 × 1.2	0.900		
1.5	1.095		
19 × 1.5	1.420		
20 × 1.5	1.500		
2.0	1.945		
2.5	2.365		
25 × 1.5	1.905		
2.0	2.495		
2.5	3.040		
25.4 × 1.4	1.815		
30 × 1.5	2.310		
2.0	3.025		
3.0	4.375		
40 × 2.0	4.105		
2.5	5.065		
3.0	5.995		
50 × 2.0	5.185		
2.5	6.415		
3.0	7.615		
60 × 2.0	6.265		
2.5	7.760		
70 × 2.0	7.345		
80 × 2.0	8.425		
2.5	10.55		
100 × 2.5	13.25		
3.0	15.72		