

# ステンレス目次

304 No. 1 板 …………… 1	304 不等辺アングル・コールドアングル …… 39
304 2 B ・片研板 …………… 3	304・430 フォーミングアングル …… 40
304 H L 板 …………… 4	304 スモールアングル・フォーミングチャンネル・C形鋼 … 41
316・316L No.1 ・ 2 B 板 …………… 5	304・316・316L チャンネル・ワイドチャンネル … 42
430 2 B 板 …………… 7	304 H形鋼 …………… 43
304 縞板 …………… 8	304・316・316L 配管用溶接パイプ …… 44
304 パンチング板 …………… 9	304・316・316L シームレスパイプ …… 48
304 エキスパンドメタル …………… 10	304・316・316L B Aパイプ …………… 67
304 ウロコ研磨板・301 バネ板 …………… 12	304 極細パイプ …………… 69
各種切板 …………… 13	304 ロール用パイプ …………… 70
304 化粧パイプ H L ・#400 4M …… 15	304・303 丸棒 …………… 71
〃 〃 5・6M …… 17	各種丸棒 316・310 S 他 …………… 73
304 角パイプ H L ・#400・未研磨 …… 19	〃 403・440 C 他 …………… 76
304 大型(肉厚)角パイプ …………… 23	304 みがき丸棒 …………… 78
304 フラット角パイプ …………… 24	各種みがき丸棒 …………… 80
304・316・316L フラットバー・角棒 …… 25	各種セントレス棒 …………… 82
303 フラットバー・角棒 …………… 34	各種六角棒 …………… 83
304・316・316L・430 アングル …………… 36	金網 …………… 84

# SUS304(No.1)板(1)

厚さ サイズ 重量	1000×2000	1219×2438	1524×3048	1524×4000
	1枚重量	1枚重量	1枚重量	1枚重量
3.0	47.6 kg	70.7 kg	111.0 kg	145.0 kg
3.5	55.5			
4.0	63.4	94.3	147.0	193.0
4.5	71.4	106.0	166.0	218.0
5.0	79.3	118.0	184.0	242.0
6.0	95.2	141.0	221.0	290.0
7.0	111.0	165.0	258.0	338.0
8.0	127.0	189.0	295.0	387.0
9.0	143.0	212.0	332.0	435.0
10.0	159.0	236.0	368.0	483.0
12.0	190.0	283.0	442.0	580.0
14.0	222.0		516.0	677.0
15.0	238.0		553.0	725.0
16.0	254.0		589.0	774.0
18.0	285.0		663.0	870.0
19.0	301.0		700.0	919.0
20.0	317.0		737.0	967.0
22.0	349.0		811.0	1064
25.0	396.0		921.0	1208
28.0			1031	1353
30.0			1105	
32.0			1179	
35.0			1289	
38.0			1400	
40.0			1473	
45.0			1657	
50.0			1842	
55.0			2026	

## SUS304 (No.1) 板(2)

<div style="display: inline-block; transform: rotate(-45deg); font-size: small;">                     サイズ 重量 厚さ                 </div>	1000×2000	1219×2438	1524×3048	1524×4000
1 枚 重 量	1 枚 重 量	1 枚 重 量	1 枚 重 量	1 枚 重 量
60.0			2210 kg	
65.0			2394	
その他サイズ			厚さ 4 ~ 100 : 2050×4100 ・ 2050×6100 4 ~ 45 : 2438×6100 6 ~ 45 : 3050×6100 6 ~ 16 : 2438×8050	

# SUS304 (2B) 板

○=片研も有

厚さ	サイズ	1000×2000	1219×2438	1524×3048	1524×4000
	重量	1 枚 重 量	1 枚 重 量	1 枚 重 量	1 枚 重 量
0.3		4.76 ○ kg	kg	kg	kg
0.4		6.34 ○			
0.5		7.93 ○	11.80		
0.6		9.52 ○	14.10 ○		
0.7		11.10			
0.8		12.70 ○	18.90 ○		
1.0		15.90 ○	23.60 ○		
1.2		19.00 ○	28.30 ○		
1.5		23.80 ○	35.40 ○	55.30 ○	
2.0		31.70 ○	47.10 ○	73.70 ○	96.70
2.5		39.60	58.90	92.10	121.0
3.0		47.60 ○	70.70 ○	111.0 ○	145.0
3.5		55.50			
4.0		63.40 ○	94.30	147.0	193.0
5.0		79.30	118.0	184.0	242.0
6.0		95.20	141.0	221.0	290.0

## SUS304 (HL) SPV 張板

厚さ \ サイズ 重量	1000×2000	1219×2438	1000×3000
	1 枚 重 量	1 枚 重 量	1 枚 重 量
0.4	6.34 kg	kg	kg
0.5	7.93		
0.6	9.52	14.10	14.30
0.8	12.70	18.90	19.00
1.0	15.90	23.60	23.80
1.2	19.00	28.30	28.50
1.5	23.80	35.40	35.70
2.0	31.70	47.10	47.60
3.0	47.60	70.70	

厚さ \ サイズ 重量	1219×3048	1219×4000	1524×3048
	1 枚 重 量	1 枚 重 量	1 枚 重 量
0.4	kg	kg	kg
0.5			
0.6			
0.8			
1.0	29.50		
1.2	35.40	46.40	
1.5	44.20	58.00	55.3
2.0	58.90	77.30	73.7
3.0			

# SUS316・316 L (No.1)板

サイズ 厚さ	1000×2000	1219×2438	1524×3048	1524×4000
	1枚重量	1枚重量	1枚重量	1枚重量
3.0	47.90 kg	71.10 kg	111.0 kg	146.0 kg
4.0	63.80	94.9	148.0	195.0
5.0	79.80	119.0	185.0	243.0
6.0	95.80	142.0	222.0	292.0
7.0				341.0
8.0	128.0	190.0	316Lのみ 297.0	389.0
9.0	144.0	213.0	334.0	438.0
10.0	160.0		371.0	486.0
12.0	192.0		445.0	584.0
14.0			316Lのみ 519.0	316Lのみ 681.0
15.0			316Lのみ 556.0	316Lのみ 730.0
16.0			593.0	316Lのみ 778.0
18.0			316Lのみ 667.0	316Lのみ 875.0
19.0			316Lのみ 704.0	316Lのみ 924.0
20.0			741.0	
22.0			816.0	
25.0			927.0	1216
28.0			316Lのみ 1038	
30.0			1112	
32.0			316Lのみ 1186	
35.0			316のみ 1297	
38.0				
40.0			316Lのみ 1483	
45.0				
50.0				
55.0				
60.0			316Lのみ 2224	
65.0~100.0				2000×4000で有

## SUS316・316L(2B)板

厚さ	サイズ	1000×2000	1219×2438	1524×3048	1524×4000
	重量	1 枚 重 量	1 枚 重 量	1 枚 重 量	1 枚 重 量
0.3	316Lのみ	4.79 kg	kg	kg	kg
0.4	316Lのみ	6.38			
0.5		7.98			
0.6		9.58	316のみ 14.20		
0.8		12.80	19.00		
1.0		16.00	23.70	37.10	
1.2		19.20	28.50	44.50	
1.5		23.90	35.60	55.60	
2.0		31.90	47.40	74.10	97.30
2.5		39.90	59.30	92.70	122.0
3.0		47.90	71.10	111.0	146.0
4.0		63.80	94.90	148.0	195.0
5.0		79.80	119.0	185.0	243.0
6.0		95.80	142.0	222.0	292.0

## SUS430(2B)板

厚さ サイズ 重量	1000×2000	1219×2438	
	1 枚 重 量	1 枚 重 量	
0.3	4.62 kg	kg	
0.4	6.16		
0.5	7.70		
0.6	9.24		
0.8	12.3	18.3	
1.0	15.4	22.9	
1.2	18.5	27.5	
1.5	23.1	34.3	
2.0	30.8	45.8	
2.5	38.5	57.2	
3.0	46.2	68.7	
4.0	61.6		



## SUS304縞板(1)

NAS 製

サイズ 重量 厚さ	1020×2100	1020×4100	1240×2500	1240×4100
	1 枚 重量	1 枚 重量	1 枚 重量	1 枚 重量
2.5	46.5 kg	90.8 kg	kg	kg
3.0	55.0	107.4	79.6	131.0
3.5	63.5	124.0	91.9	151.0
4.0	72.0	141.0	104.0	171.0
4.5	80.5	157.0	116.0	191.0
6.0	106.0	207.0	153.0	252.0

## SUS304縞板(2)

JFE 製

サイズ 重量 厚さ	1000×2000	1000×4000	1219×2438	1219×4000	1524×3048	1524×4000
	1 枚 重量	1 枚 重量	1 枚 重量	1 枚 重量	1 枚 重量	1 枚 重量
2.5	43.5 kg	87.0 kg	64.7 kg	106.0 kg		
3.0	51.4	103.0	76.4	125.0		
3.5	59.4	119.0	88.2	145.0	138.0	181.0
4.0	67.3	135.0	100.0	164.0	156.0	205.0
4.5	75.2	150.0	112.0	183.0	175.0	229.0
6.0	99.0	198.0	147.0	241.0	230.0	302.0

# SUS304パンチング板

1000×2000

厚さ×孔径×ピッチ	厚さ×孔径×ピッチ	厚さ×孔径×ピッチ	厚さ×孔径×ピッチ
0.3 × 0.5 × 1.09	0.8 × 5 × 8	1.2 × 3 × 5	2.0 × 10 × 15
0.4 × 0.5 × 1.09	6 × 8	4 × 7	12 × 18
3 × 5	6 × 9	5 × 8	15 × 20
0.5 × 1 × 2	8 × 10	6 × 9	20 × 30
1.5 × 3	10 × 15	8 × 10	3.0 × 3 × 5
3 × 4	1.0 × 1 × 2	8 × 12	5 × 8
3 × 5	1.5 × 3	10 × 15	8 × 12
5 × 8	2 × 3	1.5 × 2 × 3.5	10 × 15
0.6 × 0.8 × 1.55	2 × 3.5	3 × 5	0.3 × ○ × +
1 × 2	2.5 × 4	4 × 7	0.4 × ○ × +
2 × 3.5	3 × 4	5 × 8	0.5 × ○ × +
3 × 5	3 × 5	6 × 8	0.6 × ○ × +
4 × 7	4 × 5	6 × 9	0.8 × ○ × +
5 × 8	4 × 7	8 × 12	1.0 × ○ × +
6 × 9	5 × 7	10 × 15	1.2 × ○ × +
8 × 10	5 × 8	12 × 18	1.5 × ○ × +
0.8 × 1 × 2	6 × 8	15 × 20	0.8 × 長孔3 × 12
1.5 × 3	6 × 9	20 × 30	0.8 × 長孔3 × 20
2 × 3.5	8 × 10	2.0 × 3 × 5	1.0 × 3角 × 5並列
3 × 4	8 × 12	4 × 7	1.0 × 8角 × 10並列
3 × 5	10 × 15	5 × 8	1.5 × HL10 × 15SPV
4 × 7	12 × 18	6 × 9	
5 × 7	1.2 × 2 × 3.5	8 × 12	

1219×2438



厚さ×孔径×ピッチ	厚さ×孔径×ピッチ	厚さ×孔径×ピッチ	厚さ×孔径×ピッチ
0.8 × 3 × 5	1.0 × 5 × 8	1.2 × 10 × 15	1.5 × 10 × 15
5 × 8	10 × 15	1.5 × 3 × 5	2.0 × 5 × 8
10 × 15	1.2 × 3 × 5	5 × 8	10 × 15
1.0 × 3 × 5	5 × 8	6 × 9	1.5 × HL10 × 15SPV

# SUS304エキスパンドメタル(1)

品番	メッシュ寸法(mm)		ストランド寸法(mm)		1枚重量(kg)	
	SW	LW	T	W	1m×2m	4'×8'
31	12	30.5	1.2	1.5	4.76	7.07
32	〃	〃	1.5	2.0	7.94	11.8
33B	〃	〃	2.0	2.5	13.2	19.6
33	〃	〃	2.0	3.0	15.9	23.6
41	22	50.8	1.5	2.0	4.32	6.42
42B	〃	〃	2.0	2.0	5.76	8.56
42	〃	〃	2.0	2.5	7.20	10.7
43B	〃	〃	3.0	3.0	13.0	19.3
43	〃	〃	3.0	3.5	15.2	22.5
61B	34	76.2	2.0	2.0	3.74	
C-20	〃	〃	2.0	2.5	4.66	6.92
61	〃	〃	2.0	3.0	5.60	
62C	〃	〃	3.0	3.0	8.40	12.5
62B	〃	〃	3.0	3.5	9.80	14.6
62	〃	〃	3.0	4.0	11.2	16.6
63D	〃	〃	4.0	4.5	16.8	24.9
63B	〃	〃	4.5	4.5	18.9	28.1
63	〃	〃	4.5	5.0	21.0	31.2
20C	36	101.6	4.0	4.5	15.9	23.6
20B	〃	〃	4.0	5.0	17.6	26.2
20	〃	〃	4.5	5.0	19.8	29.5
21	〃	〃	4.5	7.0	27.8	41.3
D-50	〃	〃	5.0	6.0	26.6	39.5
22B	〃	〃	6.0	6.0	31.8	47.3
22	〃	〃	6.0	7.0	37.0	55.0
E-40	34	135.4	4.0	5.0	18.7	27.7
E-45	〃	〃	4.5	5.0	21.0	31.2
E-50	〃	〃	5.0	6.0	28.0	41.6

# SUS304エキスパンドメタル(2)

品番	メッシュ寸法(mm)		ストランド寸法(mm)		1枚重量(kg)	
	SW	LW	T	W	1m×2m	4'×8'
E-60	34	135.4	6.0	7.0	39.2	58.2
383	38	100.0	3.0	3.5	8.76	
714	7	14.0	0.8	0.8	1m×1m	
820	8	20.0	0.8	0.8	1m×1m	



SW:メッシュ短目方向の中心間距離  
 LW:メッシュ長目方向の中心間距離  
 T:板 厚  
 W:割み巾

タタミ目

## SUS304ウロコ研磨板

サイズ 重量 厚さ	1000×2000	1219×2438
	1枚重量	1枚重量
0.4	6.34 kg	kg
0.5	7.93	
0.6	9.52	14.10
0.8	12.70	18.90
1.0	15.90	23.60
1.2	19.00	28.30
1.5	23.80	35.40
2.0	31.70	47.10
2.5	39.60	58.90
3.0	47.60	70.70

## SUS301バネ板

3/4H 400×1000	
1枚重量	
0.1×300×1000	0.24 kg
0.2	0.63
0.3	0.95
0.4	1.27
0.5	1.59
0.6	1.90
0.8	2.54
1.0	3.17
1.2	3.81
1.5	4.76
2.0×320×1000	5.08

## 各種ステンレス切板(1)

鋼種 厚さ	SUS410	SUS420J2	SUS440C	SUS303	SUS304L	SUS309S	SUS310S	SUS329J4L	SUS630
1.5					○				
2.0					○	○	○		
2.5					○				
3.0					○	○	○	○	
3.3			○						
4.0	○		○	○	○	○	○	○	
5.0	○			○	○	○	○	○	
6.0	○		○	○	○	○	○	○	
8.0	○		○	○	○	○	○	○	
9.0	○			○	○	○	○	○	
10.0	○	○	○	○	○	○	○	○	○
12.0	○			○	○	○	○	○	○
13.0		○	○						
14.0	○			○	○		○		
15.0			○	○	○	○	○		○
16.0	○	○	○	○	○	○	○		
18.0	○		○	○	○	○	○		○
19.0	○			○	○	○	○		
20.0	○	○	○	○	○	○	○		○
22.0	○			○	○	○	○		○
23.0			○						
25.0	○		○	○	○	○	○		○
26.0		○	○						
28.0			○	○	○		○		○
30.0	○		○	○	○	○	○		○
32.0		○	○	○	○		○		
33.0			○						
35.0	○			○	○	○	○		○

## 各種ステンレス切板(2)

銅種 厚さ	SUS410	SUS420J2	SUS440C	SUS303	SUS304L	SUS309S	SUS310S	SUS329J4L	SUS630
38.0			○		○				
40.0	○		○	○	○	○	○		○
43.0			○						
45.0	○			○	○	○	○		○
48.0			○						
50.0	○		○	○	○	○	○		○
53.0			○						
55.0				○			○		
60.0				○	○		○		
63.0			○						
65.0				○					
70.0				○	○				
73.0			○						
80.0				○					
83.0			○						
85.0				○					
90.0				○					
93.0			○						
100.0				○					
135.0			○						
205.0	○		○						

# SUS304化粧管(HL,#400) (1)

H = H L 4 = # 400

<div style="display: inline-block; border-right: 1px solid black; border-bottom: 1px solid black; padding: 2px;">長さ</div> <div style="display: inline-block; border-bottom: 1px solid black; padding: 2px;">肉厚</div>	4M						
	0.8	1.0	1.2	1.5	2.0	3.0	4.0
5	4	4					
6	4	4					
7	4	4					
8	4	H・4					
9	4	4					
10	4	H・4					
12	4	H・4					
13	4	H・4	H・4	H・4			
13.8			H・4	H・4			
14	4	4					
15	4	4					
16	4	H・4	H・4	H・4	H・4		
17.3				H・4	H・4		
19	4	H・4	H・4	H・4	H・4		
21.7		4	H・4	H・4	H・4	H・4	
22	4	H・4	H・4	H・4	H・4		
25	4	H・4	H・4	H・4	H・4	H・4	
25.4		4	H・4	H・4	H・4		
27.2		H・4	H・4	H・4	H・4	H・4	
30				4	4		
32		H・4	H・4	H・4	H・4	H・4	
34		H・4	H・4	H・4	H・4	H・4	
38		H・4	H・4	H・4	H・4	H・4	
42.7			H・4	H・4	H・4	H・4	
45				H・4	H・4		
48.6			H・4	H・4	H・4	H・4	
50		4	H・4	H・4	H・4	H・4	
50.8				4			





# SUS304化粧管(HL,#400) (3)

H = H L 4 = # 400

外径 ↙ 長さ ↘ 肉厚	5M			6M			
	1.5	2.0	3.0	1.5	2.0	3.0	4.0
5							
6							
7							
8							
9							
10							
12							
13	H・4			H・4			
13.8	H						
14							
15							
16	H・4			H・4			
17.3	H・4	H・4		H・4	H・4		
19	H・4	H・4		H・4	H・4		
21.7	H・4	H・4	4	H・4	H・4	H・4	
22	H・4	H・4		H・4	H・4		
25	H・4	H・4		H・4	H・4		
25.4							
27.2	H・4	H・4	H・4	H・4	H・4	H・4	
32	H・4	H・4	H・4	H・4	H・4	H・4	
34	H・4	H・4	H・4	H・4	H・4	H・4	
38	H・4	H・4	H・4	H・4	H・4	H・4	
42.7	H・4	H・4	H・4	H・4	H・4	H・4	
45							
48.6	H・4	H・4	H・4	H・4	H・4	H・4	
50	H・4	H・4	H・4	H・4	H・4	H・4	
60.5	H・4	H・4	H・4	H・4	H・4	H・4	
76.3	H・4	H・4	H・4	H・4	H・4	H・4	



# SUS304角パイプ(HL, #400, 未研磨) (1)

正方形

H = HL 4 = #400 0 = 未研磨

サイズ	肉厚		1.0	1.2	1.5	2.0	3.0
	長さ						
7 × 7	4,000		H・4・0				
9 × 9	3,000		H・4・0				
	4,000		H・4・0				
10 × 10	〃		H・4・0	H・4・0			
12 × 12	〃		H・4・0	H・4・0			
13 × 13	〃		H・4・0	H・4・0			
14 × 14	4,000		H・4・0	H・4・0	H・4・0		
16 × 16	5,000		H・4・0	H・4・0	H・4・0		
	6,000				H・4・0		
19 × 19	5,000		H・4・0	H・4・0	H・4・0	H・4・0	
	6,000				H・4・0		
20 × 20	5,000			H・4・0	H・4・0		
	6,000				H・0		
21 × 21	5,000		H・4・0	H・4・0	H・4・0		
22 × 22	〃		H・4・0	H・4・0	H・4・0		
24 × 24	〃		H・4・0	H・4・0	H・4・0		
25 × 25	〃			H・4・0	H・4・0		
	6,000			H・0	H・4・0		
25.4×25.4	5,000			H・4・0	H・4・0		
28.6×28.6	〃		H・4・0	H・4・0	H・4・0		
30 × 30	〃			H・4・0	H・4・0	H・4・0	
	6,000			H・0	H・4・0		
32 × 32	5,000			H・4・0	H・4・0	H・4・0	
	6,000				H・4・0		
35 × 35	5,000			H・4・0	H・4・0		
38.5×38.5	〃			H・4・0	H・4・0	H・4・0	
40 × 40	〃				H・4・0	H・4・0	
	6,000				H・4・0	H・4・0	



# SUS304角パイプ(HL, #400, 未研磨) (3)

長方形

H = HL    4 = #400    0 = 未研磨

サイズ	肉厚		1.0	1.2	1.5	2.0	3.0
	長さ						
19 × 10	4,000		H・4・0	H・4・0			
22 × 12	5,000		H・4・0	H・4・0	H・4・0		
24 × 14	5,000		H・4・0	H・4・0	H・4・0	H・4・0	
25 × 12	5,000			H・4・0	H・4・0		
30 × 20	5,000			H・4・0	H・4・0		
	6,000				H・4・0		
30 × 25	5,000			H・4・0	H・4・0		
32 × 16	5,000		H・4・0	H・4・0	H・4・0		
	6,000				H・4・0		
40 × 18	5,000		H・4・0	H・4・0	H・4・0		
40 × 20	5,000			H・4・0	H・4・0	H・4・0	
	6,000				H・4・0		
40 × 25	5,000			H・4・0	H・4・0	H・4・0	
	6,000				H・4・0		
50 × 20	5,000			H・0	H・4・0	H・4・0	
	6,000				H・0		
50 × 25	5,000				H・4・0	H・4・0	
	6,000				H・4・0		
50 × 30	5,000				H・4・0	H・4・0	
	6,000				H・4・0		
51 × 26	5,000			H・4・0	H・4・0	H・4・0	
	6,000				H・4・0		
60 × 25	5,000				H・4・0	H・4・0	
60 × 30	5,000				H・4・0	H・4・0	
	6,000				H・4・0	H・4・0	
60 × 40	5,000				H・4・0	H・4・0	H・4・0
61 × 32	5,000				H・4・0	H・4・0	
	6,000				H・4・0		







# SUS304 HLフラット角パイプ

長さ⇒4000

肉厚 サイズ	1.0	1.2	1.5	肉厚 サイズ	1.0	1.2	1.5
6 × 12	○	○					
25		○	○				
30		○	○				
40		○	○				
50		○	○				
65			○				
75			○				
100			○				
9 × 25			○				
30			○				
40			○				
50		○	○				
65		○	○				
75			○				
100			○				
10 × 40			○				
12 × 50		○	○				
65			○				
75			○				
100			○				

# SUS304・316・316Lフラットバー・四角棒(1)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
				304			304	316 316L	304					304	316 316L					
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延	
2×6	2000	0.19		○						3×15	4000	1.43		○	○	○	○	○		
	8	〃	0.254		○						16	〃	1.52		○	○			○	
9	〃	0.286		○						19	〃	1.81		○	○			○	○	
10	3000	0.477		○					○	20	〃	1.90	1.92	○	○	○	○	○	○	○
	4000	0.636		○	○				○		22	〃	2.09		○	○			○	
12	〃	0.76		○						25	〃	2.38	2.39	○	○	○	○	○	○	○
15	〃	0.952		○	○				○	30	〃	2.86	2.87	○	○	○	○	○	○	○
20	〃	1.27		○	○				○	32	〃	3.04	3.06	○	○	○	○	○	○	○
25	〃	1.58		○	○				○	35	〃	3.33		○	○			○	○	
30	〃	1.90		○	○				○	38	〃	3.62	3.64	○	○	○	○	○	○	○
32	〃	2.03		○	○				○	40	〃	3.81	3.83	○	○	○	○	○	○	○
35	〃	2.22							○	42	〃	4.00		○	○					
38	〃	2.41		○					○	45	〃	4.28		○	○			○	○	
40	〃	2.54		○	○				○	48	〃	4.56		○	○					
45	〃	2.86		○	○				○	50	〃	4.76	4.80	○	○	○	○	○	○	○
50	〃	3.17		○	○				○	60	〃	5.72		○	○	○	○	○	○	
										65	〃	6.20		○	○			○	○	
3×3	2000	0.142		○						75	〃	7.12		○	○	○		○		
	5	3000	0.357		○					90	〃	8.56		○						
6	〃	〃	0.429		○					100	〃	9.52		○	○	○		○		
	4000	0.572		○						110	〃	10.5		○						
7	〃	0.668		○						120	〃	11.4		○						
8	〃	0.76		○						125	〃	11.9		○						
9	〃	0.856		○						130	〃	12.4		○						
10	〃	0.952		○	○				○	140	〃	13.3		○						
12	〃	1.14		○	○				○	150	〃	14.3		○						
13	〃	1.24		○	○				○											

# SUS304・316・316Lフラットバー・四角棒(2)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	H L	#400	圧延	HOT	圧延			304	316 316L	コールド	H L	#400	圧延	HOT	圧延
4× 4	4000	0.508		○						5× 8	4000	1.27		○					
	9	1.14		○							9	1.43		○					
	10	1.27		○	○						10	1.58		○	○				
	11	1.40		○	○			○			12	1.90		○	○				
	12	1.52		○							13	2.06		○	○				
	13	1.65		○	○			○			15	2.38		○	○	○	○	○	
	15	1.90		○	○	○	○	○			16	2.54		○	○				
	16	2.03		○	○		○	○			19	3.01		○	○		○	○	
	17	2.16		○							20	3.17	3.19	○	○	○	○	○	○
	19	2.41		○	○		○	○			22	3.49		○	○		○	○	
	20	2.54		○	○	○	○	○			25	3.96	3.99	○	○	○	○	○	○
	22	2.79		○	○		○	○			30	4.76	4.80	○	○	○	○	○	○
	25	3.17	3.19	○	○	○	○	○	○		32	5.08	5.12	○	○	○	○	○	○
	30	3.81	3.83	○	○	○	○	○	○		34	5.40		○	○				
	32	4.08		○	○	○	○	○			35	5.56		○	○		○	○	
	35	4.44		○	○		○	○			38	6.04	6.08	○	○	○	○	○	○
	38	4.84		○	○	○	○	○			40	6.36	6.40	○	○	○	○	○	○
	40	5.08	5.12	○	○	○	○	○	○		45	7.12					○	○	
	45	5.72		○	○		○	○			50	7.92	8.00	○	○	○	○	○	○
	50	6.36	6.40	○	○	○	○	○	○		60	9.52		○	○	○	○	○	
	60	7.60		○	○	○	○	○			65	10.3		○	○	○	○	○	
	65	8.24		○	○		○	○			75	11.9		○	○	○	○	○	
	75	9.52		○	○	○	○	○			90	14.3		○	○		○	○	
	90	11.4		○	○						100	15.8		○	○	○	○	○	
	100	12.7		○	○	○		○			130	20.6		○					
											150	23.8		○	○				
5× 5	4000	0.792		○	○														

# SUS304・316・316Lフラットバー・四角棒(3)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延
6× 6	4000	1.14		○	○					6× 42	4000	8.00		○	○				
	9	ノ	1.71		○						45	ノ	8.56		○	○	○	○	○
	10	ノ	1.90		○	○					48	ノ	9.12		○	○		○	○
	12	ノ	2.28		○	○				50	ノ	9.52	9.56	○	○	○	○	○	○
	13	ノ	2.48		○	○					5000	11.9					○		
	15	ノ	2.86		○	○	○	○	○		6000	14.3			○	○		○	○
	16	ノ	3.04		○	○				60	4000	11.4		○	○	○	○	○	
	18	ノ	3.42		○	○				65	ノ	12.4	12.40	○	○	○	○	○	○
	19	ノ	3.62		○	○		○	○		5000	15.4					○		
	20	ノ	3.81	3.83	○	○	○	○	○		6000	18.5			○	○		○	○
	22	ノ	4.20		○	○		○	○	70	4000	13.3		○	○		○	○	
25	ノ	4.76	4.80	○	○	○	○	○	○	75	ノ	14.3	14.40	○	○	○	○	○	○
	5000	5.95					○				5000	17.8					○		
	6000	7.14					○				6000	21.4			○	○		○	○
30	4000	5.72	5.76	○	○	○	○	○	○	90	4000	17.1		○	○		○	○	
	5000	7.15					○			100	ノ	19.0	19.20	○	○	○	○	○	○
	6000	8.58			○		○				5000	23.8					○		
32	4000	6.08	6.12	○	○	○	○	○	○	110	6000	28.6		○	○		○	○	
	5000	7.60					○				4000	20.9			○	○		○	
	6000	9.12					○				120	ノ	22.8		○	○		○	
35	4000	6.68		○	○		○	○	125	ノ	23.8		○	○		○			
38	ノ	7.24	7.28	○	○	○	○	○	○	130	ノ	24.8		○	○		○		
	5000	9.05					○			140	ノ	26.6		○	○		○		
	6000	10.90			○		○	○	○	150	ノ	28.6		○	○		○		
40	4000	7.60	7.68	○	○	○	○	○	○	7× 7	4000	1.56		○	○				
	5000	9.50					○				20	ノ	4.44					○	
	6000	11.4			○		○	○											

# SUS304・316・316Lフラットバー・四角棒(4)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット					
				304			304	316 316L	304					304	316 316L							
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延			
8× 8	4000	2.03		○	○	○				9× 32	5000	11.4					○					
	10	ノ	2.54		○	○					6000	13.7			○	○		○				
	16	ノ	4.08		○	○		○			35	4000	10.0			○	○		○			
	25	ノ	6.36					○			38	ノ	10.8	10.9	○	○	○	○		○	○	
	30	ノ	7.60					○				5000	13.6						○			
	32	ノ	8.12		○	○	○	○			6000	16.3			○	○		○				
	35	ノ	8.88					○			40	4000	11.4			○	○	○	○			
	38	ノ	9.64		○	○		○				5000	14.2						○			
	40	ノ	10.2					○				6000	17.1			○	○		○			
	45	ノ	11.4					○				45	4000	12.8			○			○		
50	ノ	12.7		○	○		○		50	ノ	14.3	14.4	○	○	○	○		○	○			
	65	ノ	16.5				○			5000	17.8						○					
	75	ノ	19.0				○			6000	21.4			○	○		○					
	100	ノ	25.4					○			55	4000	15.7					○				
											60	ノ	17.1			○	○	○	○			
	9× 9	4000	2.57		○	○	○				90	ノ	18.6	18.7	○	○	○	○		○	○	
13		ノ	3.71		○	○		○		65		5000	23.2					○				
15		ノ	4.28		○	○	○	○		6000		27.8			○	○		○				
16		ノ	4.56		○	○		○		75		4000	21.4	21.6	○	○	○	○		○	○	
19		ノ	5.44		○	○		○				5000	26.8						○			
20		ノ	5.72		○	○	○	○				6000	32.1			○	○		○			
22		ノ	6.28		○	○		○				4000	25.7	25.8	○	○		○		○	○	
25		ノ	7.12	7.20	○	○	○	○		○		5000	32.1						○			
		6000	10.7		○	○						6000	38.5						○			
30		4000	8.56	8.60	○	○	○	○		○		100	4000	28.6	28.7	○	○	○	○		○	○
	6000	12.8		○	○					5000	35.7							○				
32	4000	9.12	9.20	○	○	○	○		○	6000	42.8				○	○		○				

# SUS304・316・316Lフラットバー・四角棒(5)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	H L	#400	圧延	HOT	圧延			304	316 316L	コールド	H L	#400	圧延	HOT	圧延
9×125	4000	35.7		○	○		○			75	4000	23.8		○	○	○	○		
	5000	44.6					○				6000	35.7		○					
	6000	53.5					○				4000	31.7	31.9	○	○	○	○		○
150	4000	42.8		○	○		○			100	5000	39.6					○		
	5000	53.5					○				6000	47.6		○			○		
	6000	64.2					○				125	4000	39.6		○	○		○	
200	4000	57.2		○	○		○			150	〃	47.6		○	○		○		
250	〃	71.2		○	○		○			200	〃	63.6		○	○		○		
300	〃	85.6		○			○			250	〃	79.2		○	○		○		
										300	〃	95.2		○			○		
10×10	4000	3.17		○	○	○	○												
	15	〃	4.76		○	○	○	○		12×12	4000	4.56		○	○	○	○		
	19	〃	6.04		○	○		○		14	〃	5.32		○					
	20	〃	6.36		○	○	○	○		15	〃	5.72					○		
	25	〃	7.92		○	○	○	○		16	〃	6.08		○	○				
	30	〃	9.52		○	○	○	○		19	〃	7.24		○	○		○		
	32	〃	10.2		○	○	○	○		20	〃	7.60		○	○	○	○		
	35	〃	11.1					○		25	〃	9.52	9.56	○	○	○	○		
	38	〃	12.0		○	○	○	○			6000	14.3		○					
	40	〃	12.7		○	○	○	○		28	4000	10.6					○		
	45	〃	14.3					○		30	4000	11.4		○	○	○	○		
	〃	15.8	16.0	○	○	○	○		〃		6000	17.1		○					
50	5000	19.8						○		32	4000	12.2	12.2	○	○	○	○		
	6000	23.8		○				○			6000	18.3		○	○				
60	4000	19.0						○		35	4000	13.3		○	○		○		
65	〃	20.6		○	○	○	○			38	〃	14.5	14.6	○	○	○	○		
	6000	30.9		○							5000	18.1					○		

# SUS304・316・316Lフラットバー・四角棒(6)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット					
				304			304	316 316L	304					304	316 316L							
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延			
38	6000	21.7		○	○		○			13×13	4000	5.36		○	○	○	○					
40	4000	15.2		○	○	○	○			14×14	4000	6.20		○	○	○	○					
	6000	22.9		○	○																	
45	4000	17.1					○															
50	4000	19.0	19.2	○	○	○	○		○○	15×15	4000	7.12		○	○	○	○					
	5000	23.8					○															
	6000	28.6		○	○		○			16×16	4000	8.12		○	○	○	○					
65	4000	24.8	24.9	○	○	○	○		○○	19	〃	9.64		○	○							
	5000	31.0					○			20	〃	10.2		○	○	○	○					
	6000	37.1		○	○		○			25	〃	12.7	12.8	○	○	○	○		○○			
70	4000	26.6				○			30	〃	15.2					○						
75	〃	28.6	28.7	○	○	○	○		○○	32	〃	16.2	16.4	○	○	○	○		○○			
	5000	35.7					○			35	〃	17.8					○					
	6000	42.8		○	○		○			38	〃	19.3	19.4	○	○	○	○		○○			
90	4000	34.2		○	○		○		40	〃	20.3		○	○	○	○						
100	〃	38.1	38.3	○	○	○	○		○○	45	〃	22.8					○					
	5000	47.6					○			50	5000	31.7					○					
	6000	57.1		○	○		○															
125	4000	47.6		○	○		○			65	4000	33.0	33.2	○	○		○		○○			
	5000	59.5				○								5000	41.2					○		
	6000	71.4				○											6000	49.5		○		
150	4000	57.2		○	○		○			75	4000	38.1	38.3	○	○		○		○○			
	5000	71.5				○								5000	47.6					○		
	6000	85.8				○											6000	57.1		○		
200	4000	76.0		○	○		○		90	4000	45.6					○						
250	〃	95.2		○	○		○		100	〃	50.8	51.2	○	○		○			○○			

# SUS304・316・316Lフラットバー・四角棒(7)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
				304			304	316 316L	304					304	316 316L					
		304	316 316L	コールド	H L	#400	圧延	HOT	圧延			304	316 316L	コールド	H L	#400	圧延	HOT	圧延	
16×100	5000	63.5					○			75	4000	45.2	45.6	○	○		○		○	
	6000	76.2		○			○			90	♪	54.4					○			
125	4000	63.6		○	○		○			100	♪	60.4	60.8	○	○		○		○	
	5000	79.5					○				5000	75.5						○		
	6000	95.4					○				6000	90.6						○		
150	4000	76.0		○	○		○			125	4000	75.2		○	○		○			
	5000	95.0					○			150	♪	90.4		○	○		○			
	6000	114					○			200	♪	120		○	○		○			
200	4000	102		○	○		○		250	♪	151		○	○		○				
250	♪	127		○	○		○		300	♪	181		○			○				
300	♪	152		○			○													
										20×20	4000	12.7	12.8	○	○	○	○		○	
19×19	4000	11.4	11.5	○	○	○	○		○○	70	♪	44.4					○			
25	♪	15.1		○	○	○	○													
30	♪	18.1					○			22×22	4000	15.4	15.4	○	○		○		○○	
32	4000	19.3		○	○	○	○			25	♪	17.4					○			
35	♪	21.1					○			30	♪	20.9					○			
38	♪	22.9		○	○	○	○			32	♪	22.3		○			○			
40	♪	24.1					○			35	♪	24.4					○			
45	♪	27.1					○			38	♪	26.5		○			○			
50	♪	30.1	30.3	○	○	○	○		○○	40	♪	27.9					○			
	5000	37.6					○			45	♪	31.4					○			
	6000	45.2					○			50	♪	34.9		○			○			
55	4000	33.1				○			65	♪	45.2		○			○				
65	♪	39.2	39.4	○	○		○		○○	75	♪	52.4		○			○			
	5000	48.9					○			90	♪	62.8					○			
	6000	58.7					○			100	4000	69.6		○			○			



# SUS304・316・316Lフラットバー・四角棒(8)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
				304			304	316 316L	304					304	316 316L					
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延	
22×125	〃	87.2					○			30×50	〃	47.6			○			○		
150	〃	105					○			55	〃	52.4			○			○		
200	〃	140					○			65	〃	62.0			○			○		
250	〃	174					○			75	〃	71.2			○			○		
300	〃	209					○			100	〃	95.2			○			○		
										125	〃	119						○		
25×25	4000	19.8	20.0	○	○	○	○		○○	150	〃	143						○		
32	〃	25.4		○			○			200	〃	190						○		
38	〃	30.1		○			○			250	〃	238						○		
40	〃	31.7					○			300	〃	286						○		
45	〃	35.7					○													
50	〃	39.6		○			○			32×32	4000	32.5	32.7	○	○			○		○○
60	〃	47.6					○													
65	〃	51.6		○			○			35×50	4000	55.6		○				○		
75	〃	59.6		○			○			×55	〃	61.2						○		
100	〃	79.2		○			○			×65	〃	72.0		○				○		
125	〃	99.2		○			○			×75	〃	83.2		○				○		
150	〃	119		○			○			×100	〃	111		○				○		
200	〃	158		○			○			×125	〃	139						○		
250	〃	198		○			○			×150	〃	166						○		
300	〃	238		○			○													
										36×36	4000	41.2	41.4	○				○		○○
26×26	4000	21.4		○																
										38×38	4000	46.0	46.0	○	○			○		○○
28×28	4000	24.9		○	○		○													
										40×40	4000	50.8	51.2	○				○		○○
30×30	4000	28.6	28.7	○	○		○		○○	50	〃	63.6						○		

# SUS304・316・316Lフラットバー・四角棒(9)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延
40× 65	〃	82.4					○			65×100	〃	206					○		
75	〃	95.2					○												
100	〃	127					○			70× 70	4000	156					○		
125	〃	158					○			100	〃	222					○		
150	〃	190					○			125	〃	278					○		
										150	〃	333					○		
42× 42	4000	56.0	56.4				○	○○											
										75× 75	4000	178					○		
45× 45	4000	64.4	64.8	○			○	○○											
										80×100	4000	254					○		
50× 50	4000	79.2	79.8	○			○	○○		125	〃	317					○		
65	〃	103					○			150	〃	381					○		
75	〃	119					○												
100	〃	158					○			90× 90	4000	257					○		
125	〃	198					○			100	〃	286					○		
150	〃	238					○			125	〃	357					○		
										150	〃	428					○		
55× 55	4000	96.0		○			○												
										100×100	4000	317					○		
60× 60	4000	114		○			○			×125	〃	396					○		
75	〃	143					○			×150	〃	476					○		
100	〃	190					○												
125	〃	238					○												
150	〃	286					○												
65× 65	4000	134		○			○												
75	〃	155					○												

# SUS303 ホットフラットバー・四角棒(1)

長さ⇒4000

厚さ×幅	kg/P	厚さ×幅	kg/P	厚さ×幅	kg/P
6×25	4.76	16×50	25.4	75	59.6
30	5.72	65	33.0	100	79.2
40	7.60	75	38.1	150	119.0
50	9.52	100	50.8	200	158.0
65	12.4	150	76.0		
75	14.3	200	102.0	30×50	47.6
100	19.0			75	71.2
		19×25	15.1	100	95.2
9×25	7.12	30	18.1	150	143.0
30	8.56	40	24.1	200	190.0
40	11.4	50	30.1		
50	14.3	65	39.2	35×50	55.6
65	18.6	75	45.2	75	83.2
75	21.4	100	60.4		
100	28.6	150	90.4	35×100	111.0
		200	120.0		
12×25	9.52			40×50	63.6
30	11.4	22×25	17.4	75	95.2
40	15.2	30	20.9	100	127.0
50	19.0	40	27.9		
65	24.8	50	34.9	50×75	119.0
75	28.6	65	45.2	100	158.0
100	38.1	75	52.4		
150	57.2	100	69.6	四角棒	
200	76.0	150	105.0	16×16	8.12
		200	140.0	19×19	11.4
16×25	12.7			22×22	15.4
30	15.2	25×50	39.6	25×25	19.8
40	20.3	65	51.6	30×30	28.6



# SUS304・316・316L・430 アングル(1)

0 = 酸洗仕上品 H = 全面 HL 研磨品 4 = 外 2 面 # 400 研磨品

厚さ×幅	304						316・316L				430	
	4000		5000		6000		4000		6000		4000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨
2× 30											3.62	0・4
40											4.88	0・4
3× 20	3.58	0・H・4					3.60	0			3.47	0・4
25	4.52	0・H・4					4.56	0			4.40	0・4
30	5.48	0・H・4	6.85	0	8.22	0・H・4			8.28	0	5.32	0・4
35					9.66	0						
40	7.40	0・H・4	9.25	0	11.1	0・H・4			11.2	0	7.20	0・4
45					12.8	0						
50	9.48	0・H			14.2	0・H						
4× 30					10.6	0						
35	8.4	0			12.6	0						
40	9.64	0・H・4			14.5	0・H・4						
45					16.6	0						
50	12.4	0・H	15.4	0	18.5	0・H・4			18.7	0		
55					20.4	0						
5× 30					13.1	0						
35					15.5	0						
40	11.9	0・H	14.9	0	17.9	0・H・4			18.0	0		
45					20.5	0						
50	15.2	0・H	19.0	0	22.9	0・H・4			23.0	0		
60					27.6	0						
65					30.3	0						
70					32.7	0						
75					35.0	0						
6× 30					15.2	0						
35					18.2	0						
40	14.0	0			21.0	0・H						

# SUS304・316・316L・430 アングル(2)

0 = 酸洗仕上品 H = 全面 HL 研磨品 4 = 外 2 面 # 400 研磨品

厚さ×幅	304						316・316L				430	
	4000		5000		6000		4000		6000		4000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨
6× 45					24.1	0						
50	17.9	0・H	22.4	0	26.9	0・H・4			27.0	0		
55					29.8	0						
60					32.6	0・H・4						
65	23.9	0・H	29.8	0	35.8	0・H・4			36.1	0		
70					38.6	0						
75	27.7	0・H	34.6	0	41.5	0・H・4			41.8	0		
80					44.4	0						
90					50.2	0						
100	37.3	0	46.6	0	55.9	0・H・4						
7× 70					44.5	0						
8× 50					34.7	0						
60					42.3	0						
65					46.4	0						
70					50.2	0						
75					54.1	0						
80					57.8	0・H						
90					66.0	0						
100	48.8	0			73.2	0・H						
9× 50	25.8	0			38.6	0・H						
60					47.2	0						
65					51.8	0						
70					56.1	0						
75	40.4	0・H			60.6	0・H・4			60.6	0		
80					64.8	0						
90	49.2	0			73.8	0・H						
100					82.2	0						



# SUS304不等辺アングル SUS304 コールド(ピン角)アングル

0 = 酸洗仕上品

0 = 未研磨

厚さ×辺×辺	6,000	
	kg/P	研磨
● 4× 45×30	13.6	0
● 6× 50×30	21.4	0
● 65×50	31.7	0
75×50	34.4	0
● 75×65	38.8	0
100×75	48.8	0
125×75	55.9	0
7× 75×50	39.5	0
● 100×75	56.7	0
● 9× 75×50	50.0	0
● 90×75	67.2	0
100×75	71.4	0
125×75	82.2	0
150×90	99.0	0
12×150×90	130.0	0

厚さ×辺	4,000		6,000	
	kg/P	研磨	kg/P	研磨
3×20	3.54	0		
25	4.48	0		
30	5.44	0	8.16	0
40	7.36	0	11.0	0
50	9.24	0	13.9	0
4×30			10.7	0
40			14.5	0
50			18.3	0
5×30			13.1	0
40	11.9	0	17.9	0
50			22.6	0
6×30			15.5	0
40			21.2	0
50			26.9	0
60			32.6	0
65			35.5	0
75			41.2	0
9×50			39.0	0
75			60.6	0

● = 片辺切断品

※表面肌 = 熱間圧延品の引抜肌



# SUS304・430 フォーミングアングル

C = C G 肌 H = 酸洗肌 2 = 2 B 4 = 外 2 面 # 400 研磨品

鋼種 長さ 厚さ×幅	304				430	
	4,000		6,000		4,000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨
2× 20	2.37	C・2			2.30	C・2
25	3.01	C・2			2.92	C・2
30	3.64	C・2・4			3.54	C・2・4
40	4.92	C・H・2・4			4.76	C・2・4
3× 15	2.48	C・2				
20	3.44	C・H・2・4			3.24	C・4
25	4.40	C・2・4			4.24	C・4
30	5.32	C・H・2・4	7.98	C・H・2	5.20	C・4
40	7.24	C・H・2・4	10.9	C・H・2	7.04	C・4
50			13.6	C・H・2		
4× 50			17.8	C		
5× 40			17.1	C		
50			21.8	C・H		
65			29.0	H		
75			33.7	C・H		
6× 50			25.7	C・H		
60			31.4	C・H		
65			34.3	C・H		
70			37.1	H		
75			40.0	C・H		
80			42.8	H		

## SUS304スモールアングル


厚さ×辺	4.000
	kg/P
1.0 × 9	0.568
10	0.632
12	0.760
13	0.824
16	1.01
19	1.20
25	1.53
1.2 × 19	1.39
25	1.90
30	2.17
32	2.32
1.5 × 30	2.85
32	3.04
外面HL SPV	

## SUS304フォーミングチャンネル


厚さ×縦×横	6,000
	kg/P
3 × 40 × 10	8.1
40 × 20	11.0
50 × 12.5	10.3
50 × 25	13.8
60 × 15	12.4
60 × 30	16.7
75 × 35	20.3
80 × 20	16.7
80 × 40	22.4
100 × 25	21.0
100 × 50	28.1
120 × 60	33.8
150 × 50	34.5
4 × 100 × 50	36.3
5 × 80 × 40	36.9
100 × 50	46.4
150 × 50	58.7
6 × 60 × 30	32.5
80 × 40	44.0
100 × 50	55.4
125 × 65	71.1

## SUS304フォーミングC形鋼

厚さ×縦×横×A	6,000
	kg/P
2 × 40×20× 8	8.28
50×25×10	10.7
52×20× 8	9.48
60×20× 8	10.2
60×30×10	12.5
60×30×15	13.1
70×20× 8	11.2
75×40×15	16.4
75×45×15	17.8
80×40×14.5	17.2
100×50×19.5	22.0
100×50×20	21.6
120×60×19.5	25.8
125×50×20	24.0
2 B 外面HL SPV	




CG・外面HL SPV



## SUS304・316・316L チャンネル

鋼種 長さ 重量 厚さ×縦×横	304			316		316L	
	4,000	5,000	6,000	4,000	6,000	4,000	6,000
	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P
3×40×20			10.8				
50×25			13.7				
4×100×50	24.8		37.2		37.4		37.4
5×80×40	23.9	29.9	35.9		36.1		36.1
100×50	30.6	38.2	45.9		46.2		46.2
6×100×50	36.0	45.0	54.1		54.4		54.4
● 120×60			65.4				
130×65	48.0	60.0	72.0		72.6		72.6
150×75	55.6	69.5	83.4		84.0		84.0
※ 200×100	74.8		112.0				
※ 8×200×100	98.4		148.0				
9×150×75	81.2		122.0		122.0		122.0
● 10×200×100	121.2		182.0		183.0		183.0

※溶接品  
●圧延品と溶接品



## SUS304ワイドチャンネル

長さ 重量 厚さ×縦×横	6,000	長さ 重量 厚さ×縦×横	6,000
	kg/P		kg/P
6 × 220 × 65	96.6	9 × 300 × 90	198.0
230 × 65	99.6	300 × 100	206.0
250 × 75	111.0	10 × 250 × 100	205.0
9 × 250 × 75	164.0	300 × 90	219.0
250 × 90	176.0	300 × 100	229.0

※全て溶接品です  
※304L・316・316Lも製作できます

# SUS304 H形鋼

圧延品


高さ×幅×ウェブ×フランジ	6,000
	kg/P
100 × 100 × 6 × 8	103.0
125 × 125 × 6.5 × 9	143.0
148 × 100 × 6 × 9	125.0
150 × 150 × 7 × 10	188.0
200 × 100 × 5.5 × 8	127.0
200 × 200 × 8 × 12	302.0
250 × 250 × 9 × 14	435.0

※表面肌は酸洗仕上品

溶接品

高さ×幅×ウェブ×フランジ	6,000
	kg/P
75 × 75 × 5 × 8	71.40
100 × 100 × 6 × 8	100.0
125 × 125 × 7 × 9	143.0
148 × 100 × 6 × 9	123.0
150 × 150 × 8 × 10	192.0
200 × 100 × 6 × 8	128.0
200 × 200 × 8 × 12	295.0
250 × 125 × 6 × 9	173.0
250 × 9 × 14	428.0
300 × 300 × 10 × 16	584.0

※表面肌は酸洗仕上品



# SUS304・316・316L 配管用溶接管(1)

外径×肉厚	長さ 銅種			4000			6000			外径×肉厚	長さ 銅種			4000			6000		
	304	316	316L	304	316	316L	304	316	316L		304	316	316L	304	316	316L	304	316	316L
6 × 1.0	○									× 1.5	○								
6.35 × 〃	○									× 2.0	○								
7 × 〃	○									16 × 1.0	○								
8 × 〃	○									× 1.5	○								
× 1.5	○									× 2.0	○								
9 × 1.0	○									17.3 × 1.2	○								
9.53 × 〃	○									× 1.5	○	○			○				
10 × 〃	○									× 2.0	○	○	○		○				
× 1.5	○									× 2.5	○	○	○		○				
× 2.0	○									× 3.0	○	○	○						
10.5 × 1.0	○									18 × 1.0	○								
× 1.2	○									19 × 〃	○								
× 1.5	○									× 1.2	○								
× 2.0	○	○								× 1.5	○								
12 × 1.0	○									× 2.0	○								
× 1.5	○									20 × 1.0	○								
× 2.0	○									× 1.5	○								
12.7 × 1.0	○									× 2.0	○								
× 1.5	○									21.7 × 1.2	○								
× 2.0	○									× 1.5	○	○							
13 × 1.0	○									× 2.0	○	○	○		○	○	○		
13.8 × 1.2	○									× 2.5	○	○	○		○				
× 1.5	○	○								× 3.0	○	○	○		○	○	○		
× 2.0	○	○	○							22 × 1.0	○								
× 2.2	○									25 × 〃	○								
× 3.0	○	○								× 1.5	○								
14 × 1.0	○									× 2.0	○								
15 × 〃	○									25.4 × 1.2	○								

## SUS304・316・316L 配管用溶接管(2)

長さ 鋼種		4000			6000			長さ 鋼種		4000			6000		
		304	316	316L	304	316	316L			304	316	316L	304	316	316L
外径× 肉厚	鋼種														
25.4 × 1.5	○							42.7 × 2.0	○	○	○	○			
× 2.0	○	○						× 3.0	○	○	○	○	○	○	
× 3.0	○							× 3.5	○	○	○	○	○		
27.2 × 1.2	○							× 4.0	○	○	○	○			
× 1.5	○	○	○					45 × 2.0	○						
× 2.0	○	○	○	○	○			48.6 × 1.2	○						
× 2.5	○	○	○	○				× 1.5	○	○	○				
× 3.0	○	○	○	○	○	○		× 2.0	○	○	○	○			
30 × 1.5	○							× 3.0	○	○	○	○	○	○	
× 2.0	○							× 3.5	○	○	○	○			
× 3.0	○							× 4.0	○	○	○	○	○	○	
32 × 1.2	○							× 5.1	○	○	○	○			
× 1.5	○							50.8 × 1.5	○						
× 2.0	○							× 2.0	○	○					
× 3.0	○							× 3.0	○	○					
34 × 1.2	○							60.5 × 1.5	○	○	○				
× 1.5	○	○			○			× 2.0	○	○	○	○			
× 2.0	○	○	○	○	○	○		× 3.0	○	○	○	○	○	○	
× 2.5	○		○	○		○		× 3.5	○	○	○	○	○		
× 3.0	○	○	○	○	○	○		× 4.0	○	○	○	○	○	○	
× 3.5	○	○	○	○	○			× 5.0	○						
× 4.0	○	○	○	○				× 5.5	○	○	○	○			
38 × 1.5	○							63.5 × 2.0	○						
× 2.0	○							76.3 × 2.0	○	○	○	○			
× 3.0	○							× 3.0	○	○	○	○	○	○	
40 × 2.0	○							× 3.5	○	○	○	○	○		
42.7 × 1.2	○							× 4.0	○	○	○	○			
× 1.5	○				○			× 5.0	○	○	○	○			

# SUS304・316・316L 配管用溶接管 (3)

長さ 鋼種 外径×肉厚	4000			6000			長さ 鋼種 外径×肉厚	4000			6000		
	304	316	316L	304	316	316L		304	316	316L	304	316	316L
76.3 × 5.2	○	○	○	○			165.2 × 3.5	○	○	○	○	○	
× 7.0	○	○	○	○			× 4.0	○	○	○	○		
89.1 × 2.0	○	○	○	○			× 5.0	○	○	○	○	○	
× 3.0	○	○	○	○	○	○	× 7.1	○	○	○	○		
× 4.0	○	○	○	○	○	○	× 11	○	○	○	○		
× 5.0	○						190.7 × 3.0	○					
× 5.5	○	○	○	○		○	× 4.0	○					
× 7.6	○	○	○	○		○	× 6.0	○					
101.6 × 2.0	○	○	○	○			216.3 × 3.0	○	○	○	○		
× 3.0	○	○	○	○			× 4.0	○	○	○	○	○	
× 4.0	○	○	○	○			× 5.0	○			○		
× 5.7	○	○		○			× 6.0	○					
× 8.1	○			○			× 6.5	○	○	○	○		
114.3 × 2.0	○	○	○	○			× 8.2	○	○	○	○		
× 3.0	○	○	○	○	○	○	× 12.7	○	○	○	○		
× 4.0	○	○	○	○	○	○	267.4 × 3.0	○	○	○	○		
× 5.0	○	○	○	○			× 3.5	○			○		
× 6.0	○	○	○	○	○		× 4.0	○	○	○	○		
× 8.6	○	○	○	○			× 5.0	○			○		
139.8 × 2.0	○						× 6.5	○	○	○	○		
× 3.0	○	○	○	○	○		× 9.3	○	○	○	○		
× 3.5	○	○	○	○	○		× 15.1	○	○	○	○		
× 4.0	○	○	○	○			× 21.4				○		
139.8 × 5.0	○	○	○	○	○		× 28.6				○		
× 6.6	○	○	○	○			318.5 × 3.0	○	○	○	○		
× 9.5	○	○	○	○			× 4.0	○	○	○	○		
165.2 × 2.0	○						× 4.5	○	○	○	○		
× 3.0	○	○	○	○	○		× 5.0	○					

# SUS304・316・316L 配管用溶接管(4)

外径×肉厚	長さ 銅種			4000			6000			外径×肉厚	長さ 銅種			4000			6000		
	304	316	316L	304	316	316L	304	316	316L		304	316	316L	304	316	316L	304	316	316L
318.5 × 6.5	○	○	○	○						558.8 × 5.5	○	○			○				
× 10.3	○	○	○	○						× 6.0			○						
× 17.4	○	○		○						× 9.5	○								
355.6 × 4.0	○	○	○	○						609.6 × 6.0	○	○	○	○					
× 5.0	○	○	○	○						× 6.5	○								
× 6.0	○	○								× 9.5	○				○				
× 6.5	○									660.4 × 5.5	○								
× 8.0	○	○	○	○						× 8.0	○								
× 11.1	○	○	○	○						711.2 × 6.0	○								
× 19	○			○						× 8.0	○								
406.4 × 4.0	○	○	○	○															
× 4.5	○																		
× 5.0	○	○	○	○															
× 6.0	○	○	○	○															
× 6.5	○																		
× 8.0	○	○	○	○															
× 12.7	○	○	○	○															
457.2 × 4.0	○	○	○	○															
× 5.0	○	○	○	○															
× 6.0	○			○															
× 8.0	○	○	○	○															
× 14.3	○		○	○															
508 × 4.0	○			○															
× 5.0	○	○	○	○															
× 5.5	○		○																
× 6.0	○	○		○															
× 9.5	○	○	○	○															
× 15.1	○			○															



# SUS304・316・316L シームレスパイプ(1)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
2.0	0.5	2000	○			6.35	1.0	4000	○	○	○
2.5	〃	2000	○				1.2	4000	○	○	
3.0	0.5	2000	○	○			1.5	4000	○	○	
	〃	4000	○				1.65	4000		○	
	1.0	2000	○	○		2.0	4000	○			
	〃	4000	○			7.0	0.5	2000	○	○	
3.5	0.5	2000	○				〃	4000	○		
4.0	0.5	2000	○	○			0.8	4000	○		
	〃	4000	○				1.0	2000	○		
	1.0	2000	○	○		〃	4000	○	○		
	〃	4000	○	○		1.5	4000	○	○		
5.0	0.5	2000	○	○		2.0	4000	○			
	〃	4000	○	○		8.0	0.5	2000	○	○	
1.0	2000	○	○	○	〃		4000	○	○	○	
〃	4000	○	○	○	0.8		4000	○	○	○	
1.5	2000	○			1.0		2000	○	○		
	〃	4000	○			〃	4000	○	○	○	
	6.0	0.5	2000	○	○		1.2	4000	○		
〃		4000	○	○	○	1.5	2000			○	
	0.8	4000	○	○		〃	4000	○	○	○	
	1.0	2000	○	○		2.0	4000	○	○	○	
	〃	4000	○	○	○	2.5	4000	○			
	1.2	4000	○			9.0	0.5	2000	○	○	
1.5	4000	○	○	○	〃		4000	○			
2.0	4000	○	○		0.8		4000	○			
6.35	0.5	2000	○	○			1.0	2000	○		
	〃	4000	○	○		〃	4000	○	○	○	
	1.0	2000	○			1.2	4000	○			

# SUS304・316・316L シームレスパイプ(2)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
9.0	1.5	4000	○	○		10.5	1.7	4000	○	○	○
	2.0	4000	○				〃	5500	○	○	○
	2.5	4000	○				2.0	4000	○	○	○
	3.0	4000	○				2.4	2000		○	
9.53	0.5	2000	○			11.0	〃	4000	○	○	○
	〃	4000	○	○			〃	5500	○	○	○
	1.0	2000	○				0.5	2000		○	
	〃	4000	○	○	○		〃	4000	○	○	
	1.2	4000	○	○			0.8	4000	○		
	1.5	4000	○	○			1.0	4000	○	○	
	1.65	4000		○			1.5	4000	○		
	2.0	4000	○	○	○		2.0	4000	○		
10.0	0.5	2000	○	○		12.0	3.0	4000	○		
	〃	4000	○	○			0.5	2000	○	○	
	0.8	4000	○	○			〃	4000	○	○	
	1.0	2000	○	○			0.8	4000	○	○	
	〃	4000	○	○	○		1.0	2000	○	○	
	1.2	2000	○				〃	4000	○	○	○
	〃	4000	○	○			1.2	2000	○		
	1.5	2000	○				〃	4000	○		
	〃	4000	○	○	○		1.5	2000		○	
	2.0	4000	○	○	○		〃	4000	○	○	○
	2.5	4000	○				2.0	2000	○		
	3.0	4000	○				〃	4000	○	○	○
10.5	1.0	4000	○	○	○	12.7	2.5	4000	○		
	1.2	4000	○	○	○		3.0	4000	○	○	
	1.5	4000	○	○	○		4.0	4000	○		
	1.7	2000		○			0.5	2000	○		

# SUS304・316・316L シームレスパイプ(3)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
12.7	0.5	4000	○			13.8	3.0	5500	○	○	○
	0.8	2000	○				3.5	4000	○		
	∕	4000	○				4.0	4000	○		
	1.0	4000	○	○	○	14	0.5	4000	○		
	1.2	4000	○	○	○		0.8	4000	○		
	1.5	4000	○	○	○		1.0	4000	○	○	○
	1.65	4000	○	○	○		1.5	4000	○	○	
	2.0	4000	○	○	○		2.0	4000	○	○	
	3.0	4000	○				2.5	4000	○		
13	0.5	2000	○	○		15	3.0	4000	○		
	∕	4000	○				0.5	2000	○		
	0.8	4000	○				∕	4000	○		
	1.0	4000	○	○	○		0.8	4000	○		
	1.2	4000	○				1.0	2000	○		
	1.5	4000	○	○			∕	4000	○	○	○
	2.0	4000	○	○			1.2	4000	○		
	2.5	4000	○				1.5	4000	○	○	
	3.0	4000	○				2.0	4000	○	○	○
13.8	1.0	4000	○			15.9	2.5	4000	○	○	
	1.2	4000	○	○	○		3.0	4000	○		
	∕	5500	○				4.0	4000	○		
	1.65	4000	○	○	○	16	0.89	4000	○		
	∕	5500	○				1.0	4000	○		
	2.0	4000	○	○	○	16	0.5	2000	○	○	
	∕	5500	○	○	○		∕	4000	○	○	
	2.2	4000	○	○	○		0.8	4000	○		
	∕	5500	○	○	○		1.0	4000	○	○	○
	3.0	4000	○	○	○		1.2	4000	○	○	

# SUS304・316・316L シームレスパイプ(4)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質			
			304	316	316L				304	316	316L	
16	1.5	4000	○	○	○	18	1.5	4000	○	○		
	1.6	4000	○				2.0	4000	○	○		
	2.0	4000	○	○	○		2.5	4000	○			
	2.5	4000	○	○			3.0	4000	○			
	3.0	4000	○	○			4.0	4000	○			
	3.5	4000	○				19	0.5	2000	○		
	4.0	4000	○					φ	4000	○		
17	0.5	2000	○			0.8		4000	○			
	0.8	4000	○			1.0		4000	○	○	○	
	1.0	4000	○			1.2		4000	○	○		
	1.5	4000	○			1.5		4000	○	○	○	
17.3	1.0	4000	○			1.6		4000	○			
	1.2	4000	○	○	○	2.0	4000	○	○			
	φ	5500	○			2.5	4000	○				
	1.65	4000	○	○	○	3.0	4000	○				
	φ	5500	○	○	○	3.5	4000	○				
	2.0	4000	○	○	○	4.0	4000	○				
	φ	5500	○	○	○	20	0.5	4000	○			
	2.3	4000	○	○	○		0.8	4000	○			
	φ	5500	○	○	○		1.0	4000	○	○	○	
	3.2	4000	○	○	○		1.5	4000	○	○	○	
	φ	5500	○	○	○		2.0	4000	○	○		
	φ	6000	○				2.5	4000	○			
	4.0	4000	○				3.0	4000	○	○		
18	0.5	4000	○			4.0	4000	○				
	0.8	4000	○			5.0	4000	○				
	1.0	4000	○	○	○	21.7	1.2	4000	○	○		
	1.2	4000	○				1.65	4000	○	○	○	

# SUS304・316・316L シームレスパイプ(5)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
21.7	1.65	5500	○	○		23.0	1.5	4000	○		
	2.1	4000	○	○	○		2.0	4000	○		
	〃	5500	○	○	○		3.0	4000	○		
	〃	6000	○	○		24.0	1.0	4000	○		
	2.5	4000	○	○	○		2.0	4000	○		
	〃	5500	○	○	○		4.0	4000	○		
	〃	6000	○			25.0	0.5	2000	○		
	2.8	4000	○	○	○		1.0	4000	○	○	
	〃	5500	○	○	○		1.2	4000	○		
	〃	6000	○	○	○		1.5	4000	○	○	
	3.7	4000	○	○	○		2.0	4000	○	○	
	〃	5500	○	○	○		〃	6000	○		
	〃	6000	○	○			2.5	4000	○		
	4.7	4000	○	○	○		3.0	4000	○	○	
	〃	5500	○	○	○		3.5	4000	○		
	〃	6000	○	○			4.0	4000	○	○	
	7.5	4000	○				5.0	4000	○	○	
	〃	5500	○				5.5	4000	○		
22.0	0.5	2000	○			6.0	4000	○			
	0.8	4000	○			25.4	1.0	4000	○		
	1.0	4000	○	○	○		1.2	4000	○	○	
	1.5	4000	○	○	○		1.5	4000	○	○	
	2.0	4000	○				1.6	4000	○		
	2.5	4000	○				2.0	4000	○	○	○
	3.0	4000	○				2.5	4000	○		
	4.0	4000	○				3.0	4000	○	○	
	4.5	4000	○				3.5	4000	○		
23	1.0	4000	○				4.0	4000	○	○	

# SUS304・316・316L シームレスパイプ(6)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
25.4	4.5	4000	○			28	3.0	4000	○		
	5.0	4000	○				4.0	4000	○		
	6.0	4000	○				5.0	4000	○		
26	3.0	4000	○			6.5	4000	○			
27.2	1.2	4000	○	○		29	7.5	4000	○		
	1.65	4000	○	○	○		1.0	4000	○		
	∕	5500	○			30	1.0	4000	○		○
	2.1	4000	○	○	○		1.5	4000	○		
	∕	5500	○	○	○		2.0	4000	○	○	
	∕	6000	○	○	○		2.5	4000	○		
	2.5	4000	○	○	○		3.0	4000	○	○	○
	∕	5500	○	○	○		3.5	4000	○		
	∕	6000	○				4.0	4000	○		
	2.9	4000	○	○	○		5.0	4000	○	○	
	∕	5500	○	○	○		6.0	4000	○	○	
	∕	6000	○	○			8.0	4000	○		
	3.9	4000	○	○	○	32	1.0	4000	○		
	∕	5500	○	○	○		1.2	4000	○		
	∕	6000	○				1.5	4000	○	○	
	4.5	4000	○				2.0	4000	○	○	
	5.5	4000	○	○	○		3.0	4000	○	○	
	∕	5500	○	○	○		3.5	4000	○		
	∕	6000	○				4.0	4000	○	○	
	7.8	4000	○				5.0	4000	○		
∕	5500	○			6.0		ℓ	○	○		
∕	6000	○			7.0		4000	○			
28	1.0	4000	○			8.0	ℓ	○	○		
	1.5	4000	○			34	1.0	4000	○		
	2.0	4000	○								

# SUS304・316・316L シームレスパイプ(7)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質			
			304	316	316L				304	316	316L	
34	1.2	4000	○			35	5.0	4000	○			
	1.65	4000	○	○	○		36	3.0	4000	○		
	〃	5500	○		○			〃	6000	○		
	2.0	4000	○	○	○			4.0	4000	○		
	〃	5500	○					5.5	4000	○		
	2.5	4000	○					6.5	4000	○		
	〃	6000	○					8.0	4000	○	○	
	2.8	4000	○	○	○			9.0	4000	○		
	〃	5500	○	○	○			10.0	ℓ	○		
	〃	6000	○		○			38	1.0	4000	○	
	3.0	4000	○	○	○	1.2			4000	○		
	〃	5500	○	○	○	1.5	4000		○	○		
	〃	6000	○	○	○	2.0	4000		○	○		
	3.4	4000	○	○	○	3.0	4000		○	○		
	〃	5500	○	○	○	3.5	4000		○			
	〃	6000	○	○	○	4.0	4000		○	○		
	4.0	4000	○			4.5	4000		○			
	4.5	4000	○	○	○	5.0	4000		○	○		
	〃	5500	○	○	○	5.5	4000		○			
	〃	6000	○	○	○	6.0	4000	○	○			
5.0	4000	○			7.0	4000	○					
〃	6000	○			8.0	4000	○	○				
6.4	4000	○	○	○	9.0	4000	○					
〃	5500	○	○	○	40	1.0	4000	○				
〃	6000	○	○	○		1.5	4000	○				
9.1	4000	○	○	○		2.0	4000	○				
〃	5500	○	○	○		3.0	4000	○				
〃	6000	○	○			3.5	4000	○				

# SUS304・316・316L シームレスパイプ(8)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
40	4.0	4000	○			42.7	6.4	5500	○	○	○
	5.0	4000	○	○			〃	6000	○		○
	6.0	4000	○				7.0	ℓ	○	○	
	7.0	4000	○				8.0	ℓ	○		
	7.5	4000	○				9.1	4000	○		
	8.0	4000	○				〃	5500	○		
	9.0	4000	○				〃	6000	○		
	10.0	4000	○	○			9.5	4000	○	○	
42	10.0	4000	○			44	5.0	ℓ	○		
42.7	1.65	4000	○	○	○	45	2.0	4000	○		
	〃	5500	○	○			3.0	4000	○	○	
	2.0	4000	○				4.0	4000	○		
	2.8	4000	○	○	○		5.0	4000	○	○	
	〃	5500	○	○	○		5.5	ℓ	○		
	〃	6000	○				6.5	ℓ	○	○	
	3.0	4000	○	○	○		7.0	4000	○		
	〃	5500	○	○	○		8.0	ℓ	○	○	
	〃	6000	○	○			8.5	4000	○		
	3.6	4000	○	○	○		10.0	4000	○	○	
	〃	5500	○	○	○		〃	6000	○		
	〃	6000	○		○		11.5	ℓ	○		
	4.0	ℓ	○				12.5	6000	○		
	4.5	ℓ	○				48.6	1.65	4000	○	○
	4.9	4000	○	○	○	〃		5500	○		○
	〃	5500	○	○	○	2.0		4000	○	○	
	〃	6000	○			2.8		4000	○	○	○
	6.0	ℓ	○			〃		5500	○	○	○
	6.4	4000	○	○	○	〃		6000	○		



# SUS304・316・316L シームレスパイプ(9)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
48.6	3.0	4000	○	○	○	50.8	6.0	4000	○		
	〃	5500	○	○	○		6.5	4000	○		
	〃	6000	○	○			7.0	4000	○		
	3.5	4000	○				7.5	4000	○		
	3.7	4000	○	○	○		8.0	ℓ	○		
	〃	5500	○	○	○		10.0	ℓ	○	○	
	〃	6000	○	○	○		10.5	4000	○		
	4.0	4000	○				12.5	4000	○		
	5.1	4000	○	○	○		13.5	4000	○		
	〃	5500	○	○	○		52	3.5	4000	○	
	〃	6000	○	○	○	6.0		4000	○		
	6.0	4000	○			7.5		4000	○	○	
	7.1	4000	○	○	○	10.0		4000	○	○	
	〃	5500	○	○	○	14.0		4000	○	○	
	〃	6000	○	○		54		2.0	4000	○	
	8.0	ℓ	○				3.0	4000	○		
	10.2	4000	○				3.5	4000	○	○	
	〃	5500	○	○	○		4.0	4000	○		
50	7.0	ℓ	○				5.0	4000	○		
	9.0	ℓ	○				6.0	4000	○		
	12.5	ℓ	○	○			9.0	6000	○		
	14.0	ℓ	○			12.5	6000	○			
50.8	1.5	4000	○	○		15.0	5000	○			
	2.0	4000	○	○		55	2.0	4000	○		
	3.0	4000	○	○			5.0	4000	○		
	4.0	4000	○	○			5.5	4000	○		
	5.0	4000	○				8.0	4000	○		
	5.5	ℓ	○			56	3.0	4000	○		

# SUS304・316・316L シームレスパイプ(10)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
56	6.0	4000	○			60.5	3.5	6000	○		○
	8.0	4000	○	○			3.9	4000	○	○	○
	10.0	4000	○	○			〃	5500	○	○	○
	14.0	6000	○	○			〃	6000	○	○	○
	17.0	4000	○				4.9	4000	○	○	
57	2.0	4000	○				〃	6000	○		
	3.0	4000	○				5.5	4000	○	○	○
	4.0	ℓ	○				〃	5500	○	○	○
	6.0	ℓ	○				〃	6000	○	○	○
	7.5	ℓ	○				6.0	4000	○		
58	10.0	4000	○			〃	6000	○			
60	7.0	ℓ	○			〃	ℓ	○	○		
	12.5	ℓ	○	○		8.7	4000	○	○	○	
	14.0	ℓ		○		〃	5500	○	○	○	
	15.0	ℓ	○			〃	6000	○		○	
	17.5	4000	○			10.0	6000	○			
60.5	1.65	4000	○	○	○	11.1	4000	○	○		
	〃	5500	○			〃	5500	○	○		
	〃	6000	○			〃	6000	○			
	2.0	4000	○	○		13.0	6000	○			
	2.8	4000	○	○	○	15.0	6000	○	○		
	〃	5500	○	○	○	18.0	4000	○			
	〃	6000	○	○	○	62	7.0	4000	○		
	3.0	4000	○	○	○	63	8.0	ℓ	○	○	
	〃	5500	○	○			11.5	ℓ	○		
	〃	6000	○				15.5	ℓ	○		
	3.5	4000	○	○	○		17.5	ℓ	○		
	〃	5500	○	○	○	63.5	2.0	4000	○		

# SUS304・316・316L シームレスパイプ(11)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
63.5	3.0	4000	○			68	8.0	ℓ	○		
	4.0	4000	○			70	2.0	4000	○		
	5.0	6000	○				3.0	4000	○		
	6.0	6000	○				4.0	4000	○		
	6.5	6000	○	○	○		5.0	4000	○	○	
	7.0	4000	○				〃	6000	○		
	10.0	4000	○	○			6.5	ℓ	○	○	
	12.0	4000	○				7.0	6000	○		
	13.5	4000	○				8.0	4000	○		
	16.0	ℓ	○				〃	6000	○		
65	2.0	4000	○				10.0	4000	○		
	3.0	4000	○			〃	5000	○	○		
	3.5	ℓ	○			12.5	4000	○			
	4.0	ℓ	○			〃	5500	○	○		
	5.0	ℓ	○	○		15.0	ℓ	○	○		
	6.0	4000	○			18.0	4000	○			
	7.0	4000	○			20.0	6000	○			
	8.5	ℓ	○			71	4.0	4000	○		
	10.0	4000	○	○			5.5	5000		○	
	12.0	6000	○	○			〃	6000		○	
	13.5	6000	○				7.5	4000	○		
	15.0	6000	○	○			〃	6000	○		
	18.0	6000	○				10.5	6000			○
	20.0	6000	○				13.0	ℓ	○	○	
					15.0		ℓ	○			
67	7.0	6000	○			17.5	4000	○	○		
	8.0	6000	○			73	3.5	6000	○		
	10.0	4000	○				5.0	4000	○		
68	6.0	ℓ	○								

# SUS304・316・316L シームレスパイプ(12)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
73	5.0	5500	○			76.3	8.0	ℓ	○		
	7.0	4000	○				9.5	4000	○	○	○
	∕	6000	○	○			∕	5500	○	○	○
	10.0	4000	○				∕	6000	○		○
	12.5	6000	○				10.0	ℓ	○	○	
	15.0	4000	○				12.5	4000	○		
75	10.0	4000	○			∕	6000	○			
	12.5	ℓ	○			13.5	ℓ	○	○		
	15.0	4000	○			14.0	4000		○		
	17.5	ℓ	○			15.0	4000	○		○	
76.3	2.1	4000	○	○	○	∕	6000	○	○		
	∕	5500	○			18.0	ℓ	○	○		
	3.0	4000	○	○	○	20.0	ℓ	○			
	∕	5500	○	○	○	23.0	ℓ	○			
	∕	6000	○	○	○	80	2.0	4000	○		
	3.5	4000	○	○	○		3.0	4000	○		
	∕	5500	○	○			4.0	4000	○		
	∕	6000	○				5.0	ℓ	○		
	4.0	4000	○				6.0	ℓ	○		
	∕	5500	○				8.5	ℓ	○		
	5.2	4000	○	○	○		10.0	6000	○	○	
	∕	5500	○	○	○		12.5	4000	○		
	∕	6000	○		○		15.0	4000	○	○	○
	6.0	4000	○				16.0	ℓ	○		
	∕	ℓ	○	○		17.5	ℓ	○			
	7.0	4000	○	○	○	20.0	ℓ	○	○		
∕	5500	○	○	○	25.0	4000	○				
∕	6000	○		○	81	6.0	ℓ	○			

# SUS304・316・316L シームレスパイプ(13)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
82	13.0	6000	○			89.1	5.5	6000	○		○
82.6	3.0	4000	○				6.6	4000	○		
	5.0	ℓ	○				〃	ℓ	○	○	
83	8.5	ℓ	○				7.6	4000	○	○	○
	10.0	ℓ	○				〃	5500	○	○	○
85	8.0	6000	○				〃	6000	○	○	○
	8.5	ℓ	○				11.1	4000	○	○	○
	10.0	6000	○	○			〃	5500	○	○	○
	12.5	4000		○			〃	6000	○		○
	〃	6000	○	○			15.2	4000	○		
	15.0	4000	○	○		〃	6000	○	○		
	20.0	4000	○			90	10.0	ℓ	○	○	
	〃	6000	○	○			13.0	4000	○		
	22.5	ℓ	○				13.5	ℓ	○	○	
	25.0	4000	○				15.0	5000		○	
〃	6000	○			16.0		6000	○			
27.5	ℓ	○			17.5		6000	○			
89.1	2.1	4000	○	○	○		20.0	5000	○	○	
	〃	5500	○				22.5	5000	○		
	3.0	4000	○	○	○	25.0	6000	○			
	〃	5500	○	○	○	92	11.0	ℓ	○		
	〃	6000	○	○	○		15.0	5000		○	
	4.0	4000	○	○	○	95	5.0	6000	○		
	〃	5500	○	○	○		7.5	6000	○	○	
	〃	6000	○				10.0	6000	○	○	
	5.0	4000	○				12.5	6000	○	○	
	5.5	4000	○	○	○		14.5	6000	○		
〃	5500	○	○	○	15.0		4000	○			

# SUS304・316・316L シームレスパイプ(14)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質			
			304	316	316L				304	316	316L	
95	16.0	6000	○	○		101.6	12.7	4000	○	○	○	
	17.5	6000	○				〃	5500	○	○		
	20.0	5000	○				〃	6000	○		○	
	22.5	4000	○	○			15.0	4000	○	○		
	25.0	4000	○	○			20.0	6000	○			
100	10.0	6000	○	○		103	25.0	ℓ	○			
	14.5	5000	○	○			26.0	ℓ	○	○		
	15.0	4000	○			105	10.5	4000	○			
	17.5	5000	○			105	5.0	6000	○			
	18.5	ℓ	○				9.0	ℓ	○			
	20.0	6000	○				10.0	5000	○	○		
22.0	ℓ	○	○		106	〃	ℓ	○				
101.6	2.1	4000	○			○	13.0	4000	○	○		
	〃	5500	○				17.5	6000	○	○		
	〃	6000	○				20.0	ℓ	○			
	3.0	4000	○	○		○	25.0	ℓ	○	○		
	〃	5500	○	○	○	27.5	ℓ	○				
	〃	6000	○			108	13.0	4000	○			
	4.0	4000	○	○	○		110	10.0	4000	○	○	
	〃	5500	○	○				13.0	5000	○		
	〃	6000	○			15.0		6000	○			
	5.7	4000	○	○	○	20.0		4000	○	○		
	〃	5500	○	○	○	112	16.0	4000	○	○		
	〃	6000	○		○		21.0	ℓ	○			
	7.0	ℓ	○				24.5	4000	○			
8.1	4000	○	○	○	114.3	2.1	4000	○	○	○		
〃	5500	○		○		〃	5500	○		○		
〃	6000	○	○	○		〃	6000	○				

# SUS304・316・316L シームレスパイプ(15)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
114.3	3.0	4000	○	○	○	120	4.0	ℓ	○		
	〃	5500	○	○	○		5.0	6000	○		
	〃	6000	○	○	○		8.0	ℓ	○		
	4.0	4000	○	○	○		10.0	6000	○	○	
	〃	5500	○	○	○		13.0	6000	○		
	〃	6000	○				15.0	6000	○		
	5.0	4000	○				20.0	4000	○	○	
	6.0	4000	○	○	○		25.0	ℓ	○		
	〃	5500	○	○	○		26.0	ℓ		○	
	〃	6000	○	○	○		27.0	4000	○		
	7.1	ℓ	○	○			30.0	5000	○		
	8.6	4000	○	○	○		125	5.0	ℓ	○	
	〃	5500	○	○	○	10.0		5000	○	○	
	〃	6000	○	○	○	12.5		6000	○	○	
	11.1	4000	○	○	○	15.0		ℓ	○		
	〃	5500	○	○	○	17.5		ℓ	○	○	
	〃	6000	○		○	20.0		ℓ	○		
	13.5	4000	○	○	○	22.5		ℓ	○		
	〃	5500	○	○	○	25.0		ℓ	○		
	〃	6000	○		○	27.0		ℓ	○		
16.0	4000	○			127	5.0		5000	○		
17.1	4000	○				6.0	ℓ	○			
〃	6000	○		○		7.0	6000	○			
20.0	6000	○				8.0	6000	○	○		
25.0	ℓ	○				10.0	6000	○			
117	13.5	ℓ	○				20.0	ℓ	○		
118	14.0	ℓ	○			27.0	ℓ	○			
	23.5	ℓ	○		130	5.0	6000	○			

# SUS304・316・316L シームレスパイプ(16)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質			
			304	316	316L				304	316	316L	
130	7.0	6000	○			139.8	6.6	5500	○	○	○	
	10.0	ℓ	○				〃	6000	○		○	
	12.5	4000	○				9.5	4000	○	○	○	
	14.0	ℓ	○				〃	5500	○	○	○	
	15.0	ℓ	○				〃	6000	○	○	○	
	16.0	ℓ	○				12.7	4000	○	○		
	20.0	ℓ	○				〃	5500	○	○	○	
132	6.0	ℓ	○			140	〃	6000	○	○		
	10.0	5000	○				15.9	4000	○	○	○	
	13.0	ℓ	○	○			〃	5500	○	○	○	
	16.0	ℓ	○				〃	6000	○		○	
	21.0	ℓ	○	○			20.0	5500	○			
	23.5	ℓ	○				〃	6000	○			
	26.0	ℓ	○				21.0	6000	○			
	27.5	ℓ	○				25.0	ℓ	○	○		
	30.5	ℓ	○				145	14.0	4000	○		
	31.0	ℓ	○					20.0	ℓ	○	○	
135	10.0	ℓ	○			25.0		ℓ	○	○		
	15.0	ℓ	○			30.0	ℓ	○				
	20.0	ℓ	○			35.0	ℓ	○				
139.8	2.8	4000	○			150	10.0	6000	○			
	3.4	4000	○	○	○		12.5	6000	○			
	〃	5500		○	○		13.0	4000	○	○	○	
	〃	6000	○	○	○		15.0	ℓ	○			
	5.0	4000	○	○	○		20.0	ℓ	○	○		
	〃	5500	○	○	○		25.0	ℓ	○			
	〃	6000	○	○	○		30.0	ℓ	○			
	6.6	4000	○	○	○							



# SUS304・316・316L シームレスパイプ(17)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
150	12.5	ℓ	○			165.2	5.0	4000	○	○	○
	15.0	6000	○				〃	5500	○	○	○
	17.5	ℓ	○				〃	6000	○	○	○
	20.0	ℓ	○				7.1	4000	○	○	○
	22.0	ℓ	○	○			〃	5500	○	○	○
	25.0	ℓ	○				〃	6000	○	○	○
	30.0	ℓ	○				9.3	4000	○		
	35.0	ℓ	○				11.0	4000	○	○	
152	22.0	ℓ	○			〃	5500	○	○	○	
152.4	10.0	4000	○			〃	6000	○		○	
154	〃	ℓ	○			14.3	4000	○	○	○	
155	〃	4000	○			〃	5500	○	○	○	
	15.0	ℓ	○	○		〃	6000	○	○		
	20.0	ℓ	○	○		18.2	4000	○	○	○	
	26.0	ℓ	○			〃	5500	○		○	
160	5.0	6000	○			〃	6000	○	○	○	
	10.0	6000	○			21.9	ℓ	○			
	12.5	6000	○			24.0	ℓ	○			
	15.0	ℓ	○	○		25.0	ℓ	○			
	20.0	ℓ	○	○		27.0	ℓ	○			
	24.0	ℓ	○			30.0	ℓ	○			
	29.0	ℓ	○			170	10.0	ℓ	○		
	30.0	ℓ	○				15.0	ℓ	○	○	
	35.0	ℓ	○				20.0	ℓ	○		
							25.0	ℓ	○		
165.2	2.8	4000	○			26.0	ℓ	○			
	3.4	4000	○	○	○	〃	5500	○	○	○	
	〃	5500	○	○	○	32.0	ℓ	○			
	〃	6000	○	○		175	10.0	ℓ	○		

# SUS304・316・316L シームレスパイプ(18)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
175	15.0	ℓ	○			200	25.0	ℓ	○		
180	10.0	ℓ	○				28.0	ℓ	○		
	12.5	ℓ	○				30.0	ℓ	○		
	15.0	ℓ	○	○			40.0	ℓ	○		
	18.0	ℓ	○			206.0	20.0	ℓ	○		
	20.0	ℓ	○	○		212	21.0	ℓ	○	○	
	25.0	ℓ	○				27.0	ℓ	○		
	27.5	ℓ	○				41.0	ℓ	○		
	30.0	ℓ	○			216.3	2.8	4000	○		
	35.0	ℓ	○				4.0	4000	○	○	○
185	10.0	ℓ	○				≠	6000	○		
	15.0	ℓ	○			6.5	4000	○	○	○	
	20.0	ℓ	○			≠	5500	○	○	○	
190	10.0	ℓ	○			≠	6000	○	○	○	
	12.5	ℓ	○			8.2	4000	○	○	○	
	15.0	ℓ	○			≠	5500	○	○		
	17.5	ℓ	○			≠	6000	○	○	○	
	20.0	ℓ	○	○		10.3	ℓ	○			
	22.5	ℓ	○			12.7	4000	○	○		
	25.0	ℓ	○			≠	5500	○	○		
	28.0	ℓ	○			≠	6000	○	○	○	
	30.0	ℓ	○			18.2	4000	○			
190.7	7.0	6000	○			≠	5500	○			
	10.0	ℓ	○			≠	6000	○	○	○	
	11.0	4000			○	23.0	4000	○	○	○	
200	10.0	ℓ	○			≠	6000	○		○	
	15.0	ℓ	○			27.0	4000	○			
	20.0	ℓ	○	○		30.0	ℓ	○			

# SUS304・316・316L シームレスパイプ(19)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
216.3	33.0	ℓ	○			267.4	28.6	6000	○		○
220	25	ℓ	○			318.5	4.5	4000	○		
224	15.0	ℓ	○				6.5	4000	○		
	22.0	ℓ	○				∕	6000	○		
	32.0	ℓ	○				10.3	5500			○
	42.0	ℓ	○				∕	6000	○	○	○
232	9.0	6000	○				17.4	5500	○		○
	16.0	ℓ	○	○			∕	6000	○	○	○
	21.0	ℓ	○	○			21.4	ℓ	○		
236	16.0	ℓ	○				25.4	6000	○		
	23.0	ℓ	○				33.3	6000	○		○
	30.0	ℓ	○			355.6	11.1	6000	○	○	○
	43.0	ℓ	○				19.0	6000	○	○	○
250	15.0	ℓ	○			406.4	12.7	6000	○		○
	20.0	ℓ	○				21.4	6000	○		○
	25.0	ℓ	○	○							
	30.0	ℓ	○								
	35.0	ℓ	○								
255	24.0	ℓ	○								
267.4	4.0	4000	○								
	6.5	4000	○								
	∕	5500	○	○							
	∕	6000	○								
	9.3	5500	○	○							
	∕	6000	○	○	○						
	15.1	6000	○	○	○						
	18.2	6000	○	○							
	21.4	6000	○								

# SUS304・316・316L BAパイプ(1)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
1.58	0.4	2000		○		6.35	1.65	4000		○	
2	0.5	2000		○		7	0.5	2000	○		
3	0.5	2000	○	○		〃	〃	4000	○		
〃	1.0	2000	○	○		8	0.5	2000	○		
3.18	0.5	2000	○	○		〃	〃	4000	○		
〃	0.72	2000	○	○	○	〃	0.8	4000	○		
〃	1.0	2000	○	○		〃	1.0	2000	○	○	○
4	0.5	2000	○	○		〃	〃	4000	○	○	
〃	1.0	2000	○	○		〃	1.5	4000		○	
4.76	0.8	2000		○		9	0.5	2000	○		
5	0.5	2000	○			〃	〃	4000	○		
〃	0.8	2000	○			9.53	0.89	2000		○	
〃	〃	4000	○			〃	〃	4000	○	○	
〃	1.0	2000	○	○		〃	1.0	2000	○	○	○
6	0.5	2000	○			〃	〃	4000	○	○	○
〃	〃	4000	○			〃	1.24	4000	○	○	○
〃	0.8	4000	○			〃	1.65	4000		○	
〃	1.0	2000	○	○		10	0.5	2000	○		
〃	〃	4000	○	○	○	〃	〃	4000	○		
〃	1.2	4000		○		〃	0.8	4000	○		
〃	1.5	4000		○		〃	1.0	2000	○	○	○
6.35	0.5	2000	○			〃	〃	4000	○	○	
〃	〃	4000	○			〃	1.5	4000	○	○	
〃	0.89	2000	○	○	○	11	0.5	2000	○		
〃	〃	4000	○	○	○	〃	〃	4000	○		
〃	1.0	2000	○	○	○	12	0.5	2000	○		
〃	〃	4000	○	○	○	〃	〃	4000	○		
〃	1.24	4000		○		〃	1.0	2000	○	○	○

## SUS304・316・316L BAパイプ(2)

外径	肉厚	長さ	材質			外径	肉厚	長さ	材質		
			304	316	316L				304	316	316L
12	1.0	4000	○								
〃	1.2	4000		○							
〃	1.5	4000	○	○							
12.7	1.0	2000	○	○	○						
〃	〃	4000	○	○	○						
〃	1.24	2000	○	○	○						
〃	〃	4000	○	○	○						
〃	1.65	4000		○							
〃	2.11	4000		○							
13.8	1.2	4000	○								
14	1.0	4000	○								
15	1.0	4000	○								
15.88	1.0	4000	○	○	○						
〃	1.24	4000		○							
〃	1.65	4000		○							
17	1.0	4000	○								
17.3	1.2	4000	○								
18	1.0	4000	○								
19	1.5	4000	○								
19.05	1.24	4000	○	○	○						
〃	1.65	4000	○	○	○						
20	1.0	4000	○								
21.7	1.65	4000	○		○						
25.4	1.65	4000			○						
27.2	1.65	4000	○		○						
34	1.65	4000	○		○						
48.6	1.65	4000			○						
60.5	1.65	4000			○						

# SUS304極細パイプ(セミシームレス)

長さ⇒1000

規格サイズ	外 径	内 径	肉 厚	
7G	4.57	4.01	0.28	
8G	4.20	3.64	0.28	
9G	3.75	3.19	0.28	
10G	3.40	2.84	0.28	
11G	3.06	2.64	0.21	
12G	2.76	2.40	0.18	
13G	2.41	1.99	0.21	
14G	2.11	1.69	0.21	
15G	1.81	1.45	0.18	
16G	1.61	1.25	0.18	
17G	1.48	1.12	0.18	
18G	1.26	0.90	0.18	
19G	1.06	0.70	0.18	
20G	0.88	0.58	0.15	
21G	0.81	0.51	0.15	
22G	0.71	0.41	0.15	
23G	0.63	0.33	0.15	
24G	0.55	0.30	0.125	
25G	0.51	0.26	0.125	
26G	0.45	0.23	0.11	
27G	0.41	0.19	0.11	
28G	0.35	0.17	0.09	
29G	0.33	0.15	0.09	
30G	0.31	0.13	0.09	

## SUS304 ロール用パイプ

外径	肉厚	長さ	外径	肉厚	長さ
60	2.0	2000	100	2.0	1650
75	〃	1650		〃	1800
	〃	1800		〃	2000
	〃	2000		〃	2200
	〃	2200		〃	2300
	〃	2300		〃	2400
	〃	2400		〃	2500
	〃	2500		〃	2600
	〃	2600		〃	2800
	〃	2800	100	3.0	1650
	〃	3000		〃	1800
75	3.0	1650		〃	2000
	〃	1800		〃	2200
	〃	2000		〃	2300
	〃	2200		〃	2400
	〃	2300		〃	2500
	〃	2500		〃	2600
	〃	2600		〃	2800
	〃	2800		〃	3000
	〃	3000		〃	3300
			125	〃	2000

# SUS304・303丸棒(1)

6φ~25φ 長さ⇒4,000

26φ以上長さ⇒5,500乱尺

S D = 酸洗品, P M = ピーリング品

項目 径	表面仕上		1Mあたり重量	項目 径	表面仕上		1Mあたり重量
	SUS304	SUS303			SUS304	SUS303	
6	S D		0.224 kg	40	P M	P M	10.0 kg
7	〃		0.305	42	〃	〃	11.1
8	S D・P M		0.398	44	〃		12.1
9	〃		0.504	45	〃	〃	12.7
10	〃		0.623	46	〃	〃	13.3
11	P M		0.75	48	〃	〃	14.4
12	S D・P M	S D	0.90	50	〃	〃	15.6
13	〃	〃	1.05	55	〃	〃	18.9
14	〃	〃	1.22	60	〃	〃	22.5
15	〃		1.40	65	〃	〃	26.4
16	〃	P M	1.61	70	〃	〃	30.6
17	〃	〃	1.82	75	〃	〃	35.1
18	〃	〃	2.03	80	〃	〃	40.0
19	〃	〃	2.27	85	〃	〃	45.3
20	〃	〃	2.51	90	〃	〃	50.7
22	〃	〃	3.03	95	〃	〃	56.5
24	P M	〃	3.61	100	〃	〃	62.6
25	S D・P M	〃	3.92	105	〃	〃	69.0
26	P M	〃	4.25	110	〃	〃	75.7
28	〃	〃	4.93	115	〃	〃	82.7
30	〃	〃	5.65	120	〃	〃	90.1
32	〃	〃	6.43	125	〃	〃	97.7
34	〃	〃	7.25	130	〃	〃	106.0
35	〃	〃	7.68	135	〃	〃	114.0
36	〃	〃	8.13	140	〃	〃	123.0
38	〃	〃	9.05	145	〃	〃	132.0



## SUS304・303丸棒(2)

項目 径	表面仕上		1Mあたり重量	項目 径	表面仕上		1Mあたり重量
	SUS304	SUS303			SUS304	SUS303	
150	P M	P M	141.0 kg	380	P M	P M	899.0 kg
155	〃	〃	152.0	390	〃	〃	947.0
160	〃	〃	161.0	400	〃	〃	1001.0
165	〃	〃	172.0	420	〃	〃	1104.0
170	〃	〃	182.0	450	〃	〃	1267.0
175	〃	〃	193.0	480	〃	〃	1435.0
180	〃	〃	204.0	500	〃	〃	1563.0
185	〃	〃	215.0				
190	〃	〃	227.0				
195	〃	〃	239.0				
200	〃	〃	252.0				
210	〃	〃	277.0				
220	〃	〃	304.0				
230	〃	〃	332.0				
240	〃	〃	362.0				
250	〃	〃	392.0				
260	〃	〃	424.0				
270	〃	〃	457.0				
280	〃	〃	492.0				
290	〃	〃	527.0				
300	〃	〃	564.0				
310	〃	〃	602.0				
320	〃	〃	642.0				
330	〃	〃	682.0				
340	〃	〃	720.0				
350	〃	〃	767.0				
360	〃	〃	807.0				
370	〃	〃	857.0				

# 各種丸棒 SUS316・310S 他(1)

SD=酸洗品  
PM=ピーリング品

鋼種 径	1Mあたり 重量(304)	S U S 3 0 4 L	S U S 3 1 6	S U S 3 1 6 L	S U S 3 2 1	S U S 3 0 9 S	S U S 3 1 0 S	S U S 3 1 7 L	S U S 3 2 9 J 4 L	S U S 6 3 0
6	0.22 kg		SD	SD			SD			
8	0.40	SD	〃	〃		SD	〃			
9	0.50	〃	〃	〃		〃	〃			
10	0.62	〃	〃	〃		〃	〃	SD		SD
11	0.75		〃							
12	0.90		〃	〃		〃	〃			
13	1.05	〃	〃	〃		〃	〃	〃	PM	〃
14	1.22		〃				〃			
15	1.40									
16	1.61	PM	SD・PM	SD・PM		〃	SD・PM	PM	〃	〃
17	1.82		PM							
18	2.03		〃	PM			PM			
19	2.27	〃	〃	〃		PM	〃		〃	PM
20	2.51	〃	〃	〃	PM	〃	〃		〃	〃
22	3.03	〃	〃	〃		〃	〃	〃	〃	〃
24	3.61		〃							〃
25	3.92	〃	〃	〃	〃	〃	〃	〃	〃	〃
26	4.25		〃							
28	4.93		〃	〃			〃		〃	〃
30	5.65	〃	〃	〃	〃	〃	〃	〃	〃	〃
32	6.43	〃	〃	〃		〃	〃		〃	〃
34	7.25		〃							
35	7.68	〃	〃	〃		〃		〃		
36	8.13		〃	〃	〃		〃		〃	〃
38	9.05	〃	〃	〃		〃	〃		〃	〃
40	10.0	〃	〃	〃	〃	〃	〃	〃	〃	〃
42	11.1		〃	〃			〃		〃	〃

## 各種丸棒 SUS316・310S 他(2)

鋼種 径	1Mあたり 重量 (304)	S U S 3 0 4 L	S U S 3 1 6	S U S 3 1 6 L	S U S 3 2 1	S U S 3 0 9 S	S U S 3 1 0 S	S U S 3 1 7 L	S U S 3 2 9 J 4 L	S U S 6 3 0
45	12.7 kg	PM	PM	PM			PM	PM		
46	13.3		〃	〃	PM				PM	PM
48	14.4		〃	〃						
50	15.6	〃	〃	〃	〃	PM	〃	〃	〃	〃
55	18.9		〃	〃			〃			〃
60	22.5	〃	〃	〃		〃	〃	〃	〃	〃
65	26.4		〃	〃			〃			〃
70	30.6	〃	〃	〃		〃	〃	〃	〃	〃
75	35.1		〃	〃			〃			〃
80	40.0	〃	〃	〃		〃	〃	〃	〃	〃
85	45.3		〃	〃			〃			〃
90	50.7	〃	〃	〃		〃	〃	〃	〃	〃
95	56.5		〃	〃			〃			〃
100	62.6	〃	〃	〃		〃	〃	〃	〃	〃
105	69.0		〃							
110	75.7	〃	〃	〃		〃	〃		〃	〃
115	82.7		〃							
120	90.1	〃	〃	〃		〃	〃		〃	〃
125	97.7		〃							
130	106.0	〃	〃	〃		〃	〃		〃	〃
135	114.0		〃							
140	123.0	〃	〃	〃		〃	〃		〃	〃
145	132.0		〃							
150	141.0	〃	〃	〃		〃	〃		〃	〃
155	152.0		〃							
160	161.0	〃	〃	〃			〃			〃
165	172.0		〃							
170	182.0	〃	〃	〃			〃			〃

## 各種丸棒 SUS316・310S 他(3)

鋼種 径	1Mあたり 重量 (304)	S U S 3 0 4 L	S U S 3 1 6	S U S 3 1 6 L	S U S 3 2 1	S U S 3 0 9 S	S U S 3 1 0 S	S U S 3 1 7 L	S U S 3 2 9 J 4 L	S U S 6 3 0
175	193.0 kg									
180	204.0	PM	PM	PM			PM			PM
185	215.0		〃							
190	227.0	〃	〃	〃			〃			〃
195	239.0									
200	252.0	〃	〃	〃			〃			〃
210	277.0		〃	〃						
220	304.0		〃	〃						
230	332.0		〃	〃						
240	362.0		〃	〃						
250	392.0	〃	〃	〃			〃			〃
260	424.0		〃	〃						
270	457.0		〃	〃						
280	492.0		〃	〃						
290	527.0		〃	〃						
300	564.0		〃	〃						
310	602.0		〃	〃						
320	642.0		〃	〃						
330	682.0		〃	〃						
340	720.0		〃	〃						
350	767.0		〃	〃						
360	807.0		〃	〃						
370	857.0		〃	〃						
400	1001.0		〃	〃						
420	1104.0		〃	〃						
450	1267.0		〃	〃						
500	1563.0		〃	〃						

# 各種丸棒 SUS403他(1)

S D=酸 洗 品  
P M=ピ ー リ ン グ 品

鋼種 径	S U S 4 0 3	S U S 4 2 0 J 2	S U S 4 3 0	S U S 4 4 0 C	鋼種 径	S U S 4 0 3	S U S 4 2 0 J 2	S U S 4 3 0	S U S 4 4 0 C
10.0	S D				65.0	P M	P M	P M	P M
12.0		S D			70.0	〃	〃	〃	〃
13.0	〃	〃		S D	75.0	〃	〃	〃	〃
14.0	〃				80.0	〃	〃	〃	〃
16.0	P M	P M	P M	P M	85.0	〃	〃	〃	〃
18.0	〃	〃			90.0	〃	〃	〃	〃
19.0	〃	〃	〃	〃	95.0	〃	〃	〃	〃
20.0	〃	〃	〃	〃	100.0	〃	〃	〃	〃
22.0	〃	〃	〃	〃	110.0	〃	〃	〃	〃
24.0	〃	〃			120.0	〃	〃	〃	〃
25.0	〃	〃	〃	〃	130.0	〃	〃	〃	〃
26.0	〃	〃			140.0	〃	〃	〃	〃
28.0	〃	〃	〃	〃	150.0	〃	〃	〃	〃
30.0	〃	〃	〃	〃	160.0	〃	〃	〃	〃
32.0	〃	〃	〃	〃	170.0	〃	〃	〃	〃
34.0	〃	〃		〃	180.0	〃	〃	〃	〃
35.0	〃	〃	〃		190.0	〃	〃	〃	〃
36.0	〃	〃		〃	200.0	〃	〃	〃	〃
38.0	〃	〃	〃	〃	210.0	〃	〃		
40.0	〃	〃	〃	〃	220.0	〃	〃		
42.0	〃	〃	〃	〃	230.0	〃	〃		
45.0	〃	〃	〃		240.0	〃	〃		
46.0	〃	〃		〃	250.0	〃	〃		〃
48.0		〃			260.0	〃	〃		
55.0	〃	〃	〃	〃	270.0	〃	〃		
55.0	〃	〃	〃	〃	280.0	〃	〃		
60.0	〃	〃	〃	〃	290.0	〃	〃		



# SUS304みがき丸棒(1)

外径	kg/m	長さ			外径	kg/m	長さ		
		2000	4000	6000			2000	4000	6000
0.9	0.005	1000 ○			12.7	1.00		○	
1.0	0.006	1000 ○			13	1.05		○	
1.2	0.008	1000 ○			14	1.22		○	
1.4	0.012	○			15	1.40		○	
1.5	0.014	○			15.87	1.55		○	
1.6	0.015	○			16	1.59		○	
1.8	0.020	○			17	1.80		○	
2.0	0.024	○			18	2.02		○	
2.3	0.032	○			19	2.25		○	
2.5	0.038	○			19.05	2.26		○	
2.6	0.042	○			20	2.49		○	5000 ○
3.0	0.056	○			22	3.01		○	
3.2	0.063	○			22.22	3.08		○	
3.5	0.076	○			23	3.29		○	
4.0	0.099	○	○		24	3.59		○	
4.5	0.126	○			25	3.89		○	5000 ○
5.0	0.156	○	○		25.4	4.02		○	
5.5	0.188	○			26	4.21		○	○
6.0	0.224	○	○		28	4.88		○	○
6.35	0.247	○			28.57	5.08		○	
6.5	0.263	○			30	5.60		○	○
7.0	0.305	○	○		32	6.38		○	○
8.0	0.399	○	○		34	7.20		○	
9.0	0.504	○	○		35	7.63		○	○
9.52	0.562	○	○		36	8.13		○	
10	0.623	○	○		38	8.99		○	
11	0.753		○		40	9.96		○	○
12	0.897		○		42	11.0		○	





## 各種みがき丸棒(1)

銅種 外径	SUS303	SUS309S	SUS310S	SUS316	SUS316L	SUS403	SUS430
2.0	2M			2M			2M
3.0	2M		2M	2M			2M
3.5	2M						2M
4.0	2M	4M	2M	2M	2M		2M
5.0	2M	4M	2M	2M	2M		2M
6.0	2M・4M	2M	2M・4M	2M・4M	2M・4M		2M・4M
7.0	2M	2M	4M	2M	2M		2M
8.0	2M・4M	2M	2M・4M	2M・4M	2M・4M		2M・4M
9.0	2M・4M	2M	2M・4M	2M・4M	2M・4M		4M
10.0	2M・4M	2M	2M	2M・4M	2M・4M	4M	2M・4M
11 ×4000	○			○			○
12	○			○	○	○	○
13	○			○		○	○
14	○			○			○
15	○			○	○		○
16	○			○	○	○	○
17	○			○			○
18	○			○	○	○	○
19	○			○	○	○	○
20	○			○	○	○	○
22	○			○	○	○	
24	○						
25	○			○	○	○	
26	○			○			
28	○			○			
30	○			○	○	○	
32	○			○			
35	○			○	○	○	
38	○			○			



# SUS304・303・316センターレス棒

径	銅種 長さ	SUS304	SUS303	SUS316	径	銅種 長さ	SUS304	SUS303	SUS316
		2000	2100	2000			2000	2100	2000
2.0		○	○	○	35.0		○	○	○
2.5		○	○	○	38.0		○	○	
3.0		○	○	○	40.0		○	○	
3.5		○	○	○	42.0		○		
4.0		○	○	○	45.0		○		
4.5		○	○	○	50.0		○		
5.0		○	○	○					
5.5		○	○	○					
6.0		○	○	○					
7.0		○	○	○					
8.0		○	○	○					
9.0		○	○	○					
10.0		○	○	○					
11.0		○	○	○					
12.0		○	○	○					
13.0		○	○	○					
14.0		○	○	○					
15.0		○	○	○					
16.0		○	○	○					
17.0		○	○	○					
18.0		○	○	○					
19.0		○	○	○					
20.0		○	○	○					
22.0		○	○						
25.0		○	○	○					
28.0		○	○						
30.0		○	○	○					
32.0		○	○						

# 各種六角棒

長さ⇒4000

鋼種		SUS 304	SUS 303	SUS 316	SUS 316L	鋼種		SUS 304	SUS 303	SUS 316	SUS 316L
径	径										
5	2m	○	○			55	○			○	
6	2m	○	○			58	○				
7	2m	○	○			60	○				
8		○	○	○		63	○				
9		○	○			65	○				
10		○	○	○	○	70	○				
11		○	○			75	○				
12		○	○	○		80	○				
13		○	○	○	○						
14		○	○	○	○						
17		○	○	○	○						
19		○	○	○	○						
21		○	○	○	○						
22		○	○	○	○						
23		○	○	○	○						
24		○	○	○	○						
26		○	○	○	○						
27		○	○	○	○						
29		○	○	○	○						
30		○	○	○	○						
32		○	○	○	○						
35		○	○	○	○						
36		○	○	○	○						
38		○	○	○	○						
41		○	○	○	○						
46		○	○	○	○						
50		○	○	○							
54		○	○	○							

# SUS304金網(1)

線径	MESH	開目	線径	MESH	開目
mm	メッシュ	mm	mm	メッシュ	mm
0.025	500	0.026	0.14	40	0.495
0.03	400	0.034	0.18	〃	0.455
0.03	350	0.043	0.22	〃	0.415
0.035	325	0.043	0.25	〃	0.385
0.04	300	0.045	0.29	〃	0.345
0.04	270	0.054	0.25	35	0.476
0.04	250	0.062	0.22	32	0.574
0.05	200	0.077	0.25	〃	0.544
0.05	180	0.091	0.29	〃	0.504
0.05	165	0.104	0.22	30	0.627
0.06	150	0.109	0.25	〃	0.597
0.08	130	0.115	0.26	〃	0.587
0.08	120	0.132	0.29	〃	0.557
0.10	100	0.154	0.34	〃	0.507
0.10	90	0.182	0.37	〃	0.477
0.12	80	0.198	0.29	28	0.617
0.14	〃	0.178	0.25	24	0.808
0.12	70	0.243	0.29	〃	0.768
0.14	〃	0.223	0.29	22	0.865
0.14	60	0.283	0.20	20	1.070
0.16	〃	0.263	0.25	〃	1.020
0.18	〃	0.243	0.29	〃	0.980
0.14	50	0.368	0.34	〃	0.930
0.18	〃	0.328	0.37	〃	0.900
0.20	〃	0.308	0.43	〃	0.840
0.22	〃	0.288	0.47	〃	0.800
0.20	45	0.364	0.29	18	1.121
0.26	42	0.344	0.37	〃	1.041

## SUS304金網(2)

線径	MESH	開目	線径	MESH	開目
mm	メッシュ	mm	mm	メッシュ	mm
0.43	18	0.981	0.57	8	2.605
0.20	16	1.388	0.60	〃	2.575
0.29	〃	1.298	0.65	〃	2.525
0.34	〃	1.248	0.75	〃	2.425
0.37	〃	1.218	0.95	〃	2.225
0.43	〃	1.158	1.10	〃	2.075
0.47	〃	1.118	0.57	7	3.059
0.57	〃	1.018	0.80	〃	2.829
0.34	14	1.474	0.65	6.5	3.258
0.37	〃	1.444	0.65	6	3.583
0.43	〃	1.384	0.75	〃	3.483
0.47	〃	1.344	0.95	〃	3.283
0.57	〃	1.244	1.10	〃	3.133
0.75	〃	1.064	0.75	5	4.330
0.43	12	1.687	0.83	〃	4.250
0.47	〃	1.647	0.95	〃	4.130
0.57	〃	1.547	1.10	〃	3.980
0.65	〃	1.477	0.83	4	5.520
0.75	〃	1.367	1.10	〃	5.250
0.47	10	2.070	1.50	〃	4.850
0.53	〃	2.010	1.10	3.5	6.157
0.57	〃	1.970	1.50	〃	5.757
0.65	〃	1.890	1.10	3.2	6.838
0.75	〃	1.790	1.10	3	7.367
0.95	〃	1.590	1.50	〃	6.967
1.10	〃	1.440	1.90	〃	6.567
0.80	9	2.022	1.10	2.5	9.060
0.53	8	2.645	1.50	〃	8.660

# SUS304金網(3)

線径	MESH	開目	
mm	メッシュ	mm	
1.90	2.5	8.260	
1.50	2	11.200	
1.90	〃	10.800	

