SUS304化粧管(HL,#400)(1)

 $H = H L \quad 4 = #400$

長さ				4M			
外径	0.8	1.0	1.2	1.5	2.0	3.0	4.0
5	4	4					
6	4	4					
7	4	4					
8	4	H · 4					
9	4	4					
10	4	H · 4					
12	4	H · 4					
13	4	H · 4	H · 4	H · 4			
13.8			H · 4	H · 4			
14	4	4					
15	4	4					
16	4	H · 4	H · 4	H · 4	H · 4		
17.3				H · 4	H · 4		
19	4	H · 4	H · 4	H · 4	H · 4		
21.7		4	H • 4	H · 4	H · 4	H · 4	
22	4	H • 4	H • 4	H · 4	H · 4		
25	4	H · 4	H · 4	H · 4	H · 4	H · 4	
25.4		4	H · 4	H · 4	H · 4		
27.2		H · 4	H · 4	H · 4	H · 4	H · 4	
30				4	4		
32		H · 4	H · 4	H · 4	H · 4	H · 4	
34		H · 4	H · 4	H · 4	H · 4	H · 4	
38		H · 4	H · 4	H · 4	H · 4	H · 4	
42.7			H · 4	H · 4	H · 4	H · 4	
45				H · 4	H · 4		
48.6			H · 4	H · 4	H · 4	H · 4	
50		4	H · 4	H · 4	H · 4	H · 4	
50.8				4			

SUS304化粧管(HL,#400)(2)

H = H L 4 = #400

接き 4 M 9 4 M 60.5 0.8 1.0 1.2 1.5 2.0 3.0 4. 60.5 H・4 H・	 						11 11	L 4-#400
外径 0.8 1.0 1.2 1.5 2.0 3.0 4. 60.5 H・4	\ \ \				4 M			
76.3 H·4 H·4 H·4 89.1 H·4 H·4 H·4 101.6 H·4 H·4 H·4 114.3 H·4 H·4 H·4 139.8 H·4 H·4 H·4 165.2 H·4 H·4 H·4	径	0.8	1.0	1.2	1.5	2.0	3.0	4.0
89.1 H·4 H·4 H·4 101.6 H·4 H·4 H·4 114.3 H·4 H·4 139.8 H·4 H·4 H·4 H·4 H·4	60.5				H · 4	H · 4	H · 4	
101.6 H·4 H·4 H·4 114.3 H·4 H·4 139.8 H·4 H·4 165.2 H·4	76.3				H · 4	H · 4	H · 4	
114.3	89.1				H • 4	H · 4	H · 4	
139.8 H·4 H·4 165.2 H·4	101.6				H • 4	H • 4	H • 4	
165.2 H·4	114.3					H · 4	H · 4	
	139.8					H · 4	H · 4	
216.3 H · 4	165.2						H · 4	
	216.3						H · 4	

SUS304化粧管(HL,#400)(3)

 $H = H L \quad 4 = #400$

長さ		5M			6	M	2 4 — # 400
外径	1.5	2.0	3.0	1.5	2.0	3.0	4.0
5							
6							
7							
8							
9							
10							
12							
13	H · 4			H · 4			
13.8	Н						
14							
15							
16	$H \cdot 4$			H • 4			
17.3	$H \cdot 4$	H · 4		H • 4	H · 4		
19	$H \cdot 4$	H · 4		H · 4	H · 4		
21.7	H · 4	H · 4	4	H · 4	H · 4	H · 4	
22	H · 4	H · 4		H · 4	H · 4		
25	H · 4	H · 4		H · 4	H · 4		
25.4							
27.2	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
32	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
34	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
38	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
42.7	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
45							
48.6	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
50	H • 4	H · 4	H · 4	H · 4	H · 4	H · 4	
60.5	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	
76.3	H · 4	H · 4	H · 4	H · 4	H · 4	H · 4	

SUS304化粧管(HL,#400)(4)

 $H = H L \quad 4 = #400$

長さ		5M			6.	M	L 4 = #400
外径 肉厚	1.5	2.0	3.0	1.5	2.0	3.0	4.0
89.1					H • 4	H · 4	
101.6					H • 4	H · 4	
114.3					H · 4	H · 4	
139.8					H · 4	H · 4	
165.2						H · 4	
216.3						H · 4	

SUS304角パイプ(HL,#400,未研磨)(1)

正方形

サイズ	肉厚 長さ	1.0	1.2	1.5	2.0	3.0
7 × 7	4,000	$H \cdot 4 \cdot 0$				
0 × 0	3,000	H • 4 • 0				
9 × 9	4,000	H • 4 • 0				
10 × 10	"	$H \cdot 4 \cdot 0$	H • 4 • 0			
12 × 12	"	$H \cdot 4 \cdot 0$	H • 4 • 0			
13 × 13	"	$H \cdot 4 \cdot 0$	H • 4 • 0			
14 × 14	4,000	H · 4 · 0	H · 4 · 0	H • 4 • 0		
16 × 16	5,000	H · 4 · 0	H · 4 · 0	H • 4 • 0		
16×16	6,000			H • 4 • 0		
10 × 10	5,000	$H \cdot 4 \cdot 0$	H • 4 • 0	H • 4 • 0	$H \cdot 4 \cdot 0$	
19 × 19	6,000			H • 4 • 0		
20 × 20	5,000		H • 4 • 0	H • 4 • 0		
20×20	6,000			H • 0		
21 × 21	5,000	$H \cdot 4 \cdot 0$	H • 4 • 0	H • 4 • 0		
22×22	"	$H \cdot 4 \cdot 0$	H • 4 • 0	H • 4 • 0		
24×24	"	$H \cdot 4 \cdot 0$	H • 4 • 0	H • 4 • 0		
25 × 25	"		H · 4 · 0	H • 4 • 0		
25 \ 25	6,000		H • 0	H • 4 • 0		
25.4×25.4	5,000		H • 4 • 0	H • 4 • 0		
28.6×28.6	"	$H \cdot 4 \cdot 0$	H • 4 • 0	H • 4 • 0		
30 × 30	"		$H \cdot 4 \cdot 0$	$H \cdot 4 \cdot 0$	$H \cdot 4 \cdot 0$	
30 \ 30	6,000		H • 0	H • 4 • 0		
32×32	5,000		H · 4 · 0	H • 4 • 0	$H \cdot 4 \cdot 0$	
34 ^ 34	6,000			H • 4 • 0		
35 × 35	5,000		H · 4 · 0	H · 4 · 0		
38.5×38.5	"		H • 4 • 0	H · 4 · 0	H • 4 • 0	
40 × 40	"			H · 4 · 0	H · 4 · 0	
40 ^ 40	6,000			H • 4 • 0	H • 4 • 0	

SUS304角パイプ(HL,#400,未研磨)(2)

正方形

正 万 形				11 - 1	1 L 4 — # 40	0 0 一 不 前 居
サイズ	肉厚 長さ	1.0	1.2	1.5	2.0	3.0
41 × 41	5,000		H · 4 · 0	H · 4 · 0	H · 4 · 0	
41 / 41	6,000			H · 4 · 0		
46 × 46	5,000			H · 4 · 0	H · 4 · 0	
F0 × F0	5,000			H · 4 · 0	H · 4 · 0	$H \cdot 4 \cdot 0$
50 × 50	6,000			H · 4 · 0	H · 4 · 0	$H \cdot 4 \cdot 0$
CO × CO	5,000			H · 4 · 0	H · 4 · 0	H · 4 · 0
60 × 60	6,000			H · 4 · 0	H · 4 · 0	
75 \ 75	5,000				H · 4 · 0	H · 4 · 0
75 × 75	6,000				H · 4 · 0	H • 0
100 \ 100	5,000				H · 4 · 0	$H \cdot 4 \cdot 0$
100 × 100	6,000				H · 4 · 0	

SUS304角パイプ(HL,#400,未研磨)(3)

長方形

サイズ	長さ	1.0	1.2	1.5	2.0	3.0
19 × 10	4,000	$H \cdot 4 \cdot 0$	H • 4 • 0			
22 × 12	5,000	H • 4 • 0	H • 4 • 0	H · 4 · 0		
24 × 14	5,000	H • 4 • 0	H • 4 • 0	H · 4 · 0	H • 4 • 0	
25 × 12	5,000		H • 4 • 0	H · 4 · 0		
20 × 20	5,000		H · 4 · 0	H · 4 · 0		
30×20	6,000			H · 4 · 0		
30 × 25	5,000		H · 4 · 0	H · 4 · 0		
20 × 16	5,000	H • 4 • 0	H · 4 · 0	H · 4 · 0		
32×16	6,000			H · 4 · 0		
40 × 18	5,000	H • 4 • 0	H · 4 · 0	H · 4 · 0		
40 × 20	5,000		H • 4 • 0	H · 4 · 0	H • 4 • 0	
40 ^ 20	6,000			H · 4 · 0		
40 × 25	5,000		H · 4 · 0	H · 4 · 0	H • 4 • 0	
40 × 25	6,000			H · 4 · 0		
50 × 20	5,000		H • 0	H · 4 · 0	H · 4 · 0	
50 \ 20	6,000			H • 0		
50 × 25	5,000			H · 4 · 0	H · 4 · 0	
50 × 25	6,000			$H \cdot 4 \cdot 0$		
50 × 30	5,000			$H \cdot 4 \cdot 0$	H • 4 • 0	
50 \ 50	6,000			$H \cdot 4 \cdot 0$		
51 × 26	5,000		$H \cdot 4 \cdot 0$	$H \cdot 4 \cdot 0$	H · 4 · 0	
51 × 20	6,000			$H \cdot 4 \cdot 0$		
60 × 25	5,000			H · 4 · 0	H · 4 · 0	
60 × 30	5,000			H · 4 · 0	H · 4 · 0	
00 ^ 30	6,000			H · 4 · 0	H · 4 · 0	
60 × 40	5,000			H • 4 • 0	H · 4 · 0	H · 4 · 0
61 × 22	5,000			H • 4 • 0	H · 4 · 0	
61 × 32	6,000			H • 4 • 0		

SUS304角パイプ(HL,#400,未研磨)(4)

長方形

区月份					1L 4-#40	0 0 /(1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1
サイズ	長さ	1.0	1.2	1.5	2.0	3.0
65 × 18	5,000		H • 4 • 0	H • 4 • 0		
70 × 25	5,000			H • 4 • 0	H • 4 • 0	
70 × 30	5,000			H • 4 • 0	H • 4 • 0	
75 \ 45	5,000			H • 4 • 0	H • 4 • 0	H · 4 · 0
75×45	6,000			H • 4 • 0	H • 4 • 0	
90 × 40	5,000			H • 4 • 0	H · 4 · 0	H · 4 · 0
80 × 40	6,000			H • 4 • 0	H • 4 • 0	
00 1/ 00	5,000			H • 4 • 0	H • 4 • 0	H • 4 • 0
90 × 30	6,000			H • 4 • 0		
90 × 50	5,000			H · 0	H · 4 · 0	H • 4 • 0
100 × 40	5,000				H · 4 · 0	H • 4 • 0
100 \/ 50	5,000				H • 4 • 0	H • 4 • 0
100 × 50	6,000				H • 4 • 0	H • 4 • 0
120 × 60	5,000				H · 4 · 0	H • 4 • 0
125 × 75	5,000				H · 4 · 0	H • 4 • 0
150 × 50	5,000				H · 4 · 0	H • 4 • 0
	1	<u> </u>			<u> </u>	

SUS304大型(肉厚)角パイプ(未研磨)

長さ⇔6000

正方形 長方形 ※=受注生産品

											/• \	74.	工生山
肉厚サイズ	3.0	4.0	5.0	6.0	9.0	12.0	肉厚サイズ	3.0	4.0	5.0	6.0	9.0	12.0
40 × 40	0	0					60 × 30	0	0				
50 × 50	0	0	0				75 × 45	0	0				
60 × 60	0	0	0				80 × 40	0	0				
75 × 75	0	0	0	0			90 × 50	0	0				
80 × 80	0	0	*				100 × 40	0	0				
90 × 90	0	0	*	*			100 × 50	\circ	0	0	0		
100 ×100	0	0	0	0	0		125×75	\circ	0	0	0		
110 ×110	0	0	*	*	*		150 × 75	\circ	0	0	0		
120 ×120	0	0	0	0	*		150 ×100	\circ	0	0	0	0	
125 ×125	0	0	0	0	0		200×75	\circ	0	0	0	*	
150 ×150	0	0	0	0	0	0<	200 ×100	\circ	0	0	0	0<	$\bigcirc \checkmark$
175 ×175	0	0	0	0	0	0<	200 ×150	\circ	0	0	0	0<	0<
200 ×200	0	0	0	0	0	0<	250 ×150	\circ	0	0	0	0<	0<
250 ×250		0	0	0	0	0~	300 ×200		0	0	0	0 <	0<
300 ×300		0	0	0	0	0<							
		1			<u> </u>					1			

SUS304 HLフラット角パイプ

長さ⇒4000

							長さ⇨4000
肉厚サイズ	1.0	1.2	1.5	肉厚サイズ	1.0	1.2	1.5
6 × 12	0	0					
25		0	0				
30		0	0				
40		0	0				
50		0	0				
65			0				
75			0				
100			0				
9 × 25			0				
30			0				
40			0				
50		0	0				
65		0	0				
75			0				
100			0				
10 × 40			0				
12 × 50		0	0				
65			0				
75			0				
100			0				

SUS304·316·316L 配管用溶接管(1)

	_	長さ		4000			6000			_	長さ		4000			6000	
外径×肉]厚	鋼種	304	316	316 L	304	316	316 L	外径×肉	 厚	鋼種	304	316	316 L	304	316	316 L
6	×	1.0	0							×	1.5	0					
6.3	5×	"	0							×	2.0	0					
7	×	"	0						16	×	1.0	0					
8	×	"	0							×	1.5	\circ					
	×	1.5	0							×	2.0	0					
9	×	1.0	0						17.3	×	1.2	0					
9.5	$3\times$	"	0							×	1.5	0	0		0		
10	×	"	0							×	2.0	0	0	0	0		
	×	1.5	0							×	2.5	0	0	0	0		
	×	2.0	0							×	3.0	0	0	0			
10.5	×	1.0	0						18	×	1.0	0					
	×	1.2	0						19	×	"	0					
	×	1.5	0							×	1.2	0					
	×	2.0	0	0						×	1.5	0					
12	×	1.0	0							×	2.0	0					
	×	1.5	0						20	×	1.0	0					
	×	2.0	0							×	1.5	0					
12.7	×	1.0	0							×	2.0	0					
	×	1.5	0						21.7	×	1.2	0					
	×	2.0	0							×	1.5	0	0				
13	×	1.0	0							×	2.0	0	0	0	0	0	0
13.8	×	1.2	0							×	2.5	0	0	0	0		
	×	1.5	0	0						×	3.0	0	0	0	0	0	0
	×	2.0	0	0	0				22	×	1.0	0					
	×	2.2	0						25	×	"	0					
	×	3.0	0	0						×	1.5	0					
14	×	1.0	0							×	2.0	0					
15	×	"	0						25.4	×	1.2	0					

SUS304·316·316L 配管用溶接管(2)

	_	長さ		4000		6000		長さ		さ				6000			
外径×	肉厚	· 鋼種	304	316	316 L	304	316	316 L	外径×肉厚	釧	種	304	316	316 L	304	316	316 L
25.4	×	1.5	0						42.7 ×	2.0		\bigcirc	0	0	0		
	×	2.0	0	0					×	3.0		\bigcirc	0	0	0	0	0
	×	3.0	0						×	3.5		0	0	0	0	0	
27.2	×	1.2	0						×	4.0		0	0	0	0		
	×	1.5	0	0	0				45 ×	2.0		\bigcirc					
	×	2.0	0	0	0	0	0		48.6 ×	1.2		\bigcirc					
	×	2.5	0	0	0	0			×	1.5		\bigcirc	0	0			
	×	3.0	0	0	0	0	0	0	×	2.0		\bigcirc	0	0	0		
30	×	1.5	0						×	3.0		\bigcirc	0	0	0	0	0
	×	2.0	0						×	3.5		0	0	0	0		
	×	3.0	0						×	4.0		0	0	0	0	0	0
32	×	1.2	0						×	5.1		0	0	0	0		
	×	1.5	0						50.8 ×	1.5	4	0					
	×	2.0	0						×	2.0		0	0				
	×	3.0	0						×	3.0		0	0				
34	×	1.2	0						60.5 ×	1.5		0	0	0			
	×	1.5	0	0		0			×	2.0	4	0	0	0	0		
	×	2.0	0	0	0	0	0	0	×	3.0		0	0	0	0	0	0
	×	2.5	0		0	0		0	×	3.5		0	0	0	0	0	
	×	3.0	0	0	0	0	0	0	×	4.0		0	0	0	0	0	0
	×	3.5	0	0	0	0	0		×	5.0		0					
	×	4.0	0	0	0	0			×	5.5		0	0	0	0		
38	×	1.5	0						63.5 ×	2.0	4	0					
	×	2.0	0						76.3 ×	2.0	4	0	0	0	0		
	×	3.0	0						×	3.0		0	0	0	0	0	0
40	×	2.0	0						×	3.5		0	0	0	0	0	
42.7	×	1.2	0						×	4.0		0	0	0	0		
	×	1.5	0			0			×	5.0		\bigcirc	0	0	0		

SUS304·316·316L 配管用溶接管(3)

	長さ		4000			6000			長さ		4000			6000	
外径×肉厚	鋼種	304	316	316 L	304	316	316 L	外径×肉厚	鋼種	304	316	316 L	304	316	316 L
76.3 ×	5.2	0	0	0	0			165.2 ×	3.5	0	0	0	0	0	
×	7.0	0	0	0	0			×	4.0	0	0	0	0		
89.1 ×	2.0	0	0	0	0			×	5.0	0	0	0	0	0	
×	3.0	0	0	0	0	0	0	×	7.1	0	0	0	0		
×	4.0	0	0	0	0	0	0	×	11	0	0	0	0		
×	5.0	0						190.7 ×	3.0	0					
×	5.5	0	0	0	0		0	×	4.0	0					
×	7.6	0	0	0	0		0	×	6.0	0					
101.6 ×	2.0	0	0	0	0			216.3 ×	3.0	0	0	0	0		
×	3.0	0	0	0	0			×	4.0	0	0	0	0	0	
×	4.0	0	0	0	0			×	5.0	0			0		
×	5.7	0	0		0			×	6.0	0					
×	8.1	0			0			×	6.5	0	0	0	0		
114.3 ×	2.0	0	0	0	0			×	8.2	0	0	0	0		
×	3.0	0	0	0	0	0	0	×	12.7	0	0	0	0		
×	4.0	0	0	0	0	0	0	267.4 ×	3.0	0	0	0	0		
×	5.0	0	0	0	0			×	3.5	0			0		
×	6.0	0	0	0	0	0		×	4.0	0	0	0	0		
×	8.6	0	0	0	0			×	5.0	0			0		
139.8 ×	2.0	0						×	6.5	0	0	0	0		
×	3.0	0	0	0	0	0		×	9.3	0	0	0	0		
×	3.5	0	0	0	0	0		×	15.1	0	0	0	0		
×	4.0	0	0	0	0			×	21.4				0		
139.8 ×	5.0	0	0	0	0	0		×	28.6				0		
×	6.6	0	0	0	0			318.5 ×	3.0	0	0	0	0		
×	9.5	0	0	0	0			×	4.0	0	0	0	0		
165.2 ×	2.0	0						×	4.5	0	0	0	0		
×	3.0	0	0	0	0	0		×	5.0	0					

SUS304·316·316L 配管用溶接管(4)

	_	長さ		4000			6000			長さ		4000			6000	
外径×肉	厚	鋼種	304	316	316 L	304	316	316 L	外径×肉厚	鋼種	304	316	316 L	304	316	316 L
318.5	×	6.5	0	0	0	0			558.8 ×	5.5	0	0		0		
	×	10.3	0	0	0	\circ			×	6.0			0			
	×	17.4	0	0		0			×	9.5	0					
355.6	×	4.0	0	0	0	0			609.6 ×	6.0	0	0	0	0		
	×	5.0	0	0	0	0			×	6.5	0					
	×	6.0	0	0					×	9.5	0			0		
	×	6.5	0						660.4 ×	5.5	0					
	×	8.0	0	0	0	0			×	8.0	0					
	×	11.1	0	0	0	0			711.2 ×	6.0	0					
	×	19	0			0			×	8.0	0					
406.4	×	4.0	0	0	0	0										
	×	4.5	0													
	×	5.0	0	0	0	0										
	×	6.0	0	0	0	0										
	×	6.5	0													
	×	8.0	0	0	0	0										
	×	12.7	0	0	0	0										
457.2	×	4.0	0	0	0	0										
	×	5.0	0	0	0	0										
	×	6.0	0			0										
	×	8.0	0	0	0	0										
	×	14.3	0		0	0										
508	×	4.0	0			0										
	×	5.0	0	0	0	0										
	×	5.5	0		0											
	×	6.0	0	0		0										
	×	9.5	0	0	0	0		0								
	×	15.1	0			0										

SUS304・316・316L シームレスパイプ(1)

外径	肉厚	長さ		材質		外径	肉厚	長さ		材質	
グト任	内厚	区で	304	316	316 L	グME	内厚	区で	304	316	316 L
2.0	0.5	2000	0			6.35	1.0	4000	0	0	0
2.5	"	2000	0				1.2	4000	0	0	
3.0	0.5	2000	0	0			1.5	4000	0	0	
	"	4000	0				1.65	4000		0	
	1.0	2000	0	0			2.0	4000	0		
	"	4000	0			7.0	0.5	2000	0	0	
3.5	0.5	2000	0				"	4000	0		
4.0	0.5	2000	0	0			0.8	4000	0		
	"	4000	0				1.0	2000	0		
	1.0	2000	0	0			"	4000	0	0	
	"	4000	0	0			1.5	4000	0	0	
5.0	0.5	2000	0	0			2.0	4000	0		
	"	4000	0	0		8.0	0.5	2000	0	0	
	1.0	2000	0	0	0		"	4000	0	0	0
	"	4000	0	0	0		0.8	4000	0	0	0
	1.5	2000	0				1.0	2000	0	0	
	"	4000	0				"	4000	0	0	0
6.0	0.5	2000	0	0			1.2	4000	0		
	"	4000	0	0	0		1.5	2000			0
	0.8	4000	0	0			"	4000	0	0	0
	1.0	2000	0	0			2.0	4000	0	0	0
	"	4000	0	0	0		2.5	4000	0		
	1.2	4000	0			9.0	0.5	2000	0	0	
	1.5	4000	0	0	0		"	4000	0		
	2.0	4000	0	0			0.8	4000	0		
6.35	0.5	2000	0	0			1.0	2000	0		
	"	4000	0	0			"	4000	0	0	0
	1.0	2000	0				1.2	4000	0		

SUS304・316・316L シームレスパイプ(2)

PI VA	4.6	E V		材質		PI VA	4.6	E V		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
9.0	1.5	4000	0	0		10.5	1.7	4000	0	0	0
	2.0	4000	0				"	5500	0	0	0
	2.5	4000	0				2.0	4000	0	0	0
	3.0	4000	0				2.4	2000		0	
9.53	0.5	2000	0				"	4000	0	0	0
	"	4000	0	0			"	5500	0	0	0
	1.0	2000	0			11.0	0.5	2000		0	
	"	4000	0	0	0		"	4000	0	0	
	1.2	4000	0	0			0.8	4000	0		
	1.5	4000	0	0			1.0	4000	0	0	
	1.65	4000		0			1.5	4000	0		
	2.0	4000	0	0	0		2.0	4000	0		
10.0	0.5	2000	0	0			3.0	4000	0		
	"	4000	0	0		12.0	0.5	2000	0	0	
	0.8	4000	0	0			"	4000	0	0	
	1.0	2000	0	0			0.8	4000	0	0	
	"	4000	0	0	0		1.0	2000	0	0	
	1.2	2000	0				"	4000	0	0	0
	"	4000	0	0			1.2	2000	0		
	1.5	2000	0				"	4000	0		
	"	4000		0	0		1.5	2000		0	
	2.0	4000	0	0	0		"	4000	0	0	0
	2.5	4000	0				2.0	2000	0		
	3.0	4000	0				"	4000	0	0	0
10.5	1.0	4000	0	0	0		2.5	4000	0		
	1.2	4000	0	0	0		3.0	4000	0	0	
	1.5	4000	0	0	0		4.0	4000	0		
	1.7	2000		0		12.7	0.5	2000	0		

SUS304・316・316L シームレスパイプ(3)

PI 소스	中国	لا ⊞		材質		かい	中国	لا ∺		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
12.7	0.5	4000	0			13.8	3.0	5500	0	0	0
	0.8	2000	0				3.5	4000	0		
	"	4000	0				4.0	4000	0		
	1.0	4000	0	0	0	14	0.5	4000	0		
	1.2	4000	0	0	0		0.8	4000	0		
	1.5	4000	0	0	0		1.0	4000	0	0	
	1.65	4000	0	0	0		1.5	4000	0	0	
	2.0	4000	0	0	0		2.0	4000	0	0	
	3.0	4000	0				2.5	4000	0		
13	0.5	2000	0	0			3.0	4000	0		
	"	4000	0			15	0.5	2000	0		
	0.8	4000	0				"	4000	0		
	1.0	4000	0	0	0		0.8	4000	0		
	1.2	4000	0				1.0	2000	0		
	1.5	4000	0	0			"	4000	0	0	0
	2.0	4000	0	0			1.2	4000	0		
	2.5	4000	0				1.5	4000	0	0	
	3.0	4000	0				2.0	4000	0	0	0
13.8	1.0	4000	0				2.5	4000	0	0	
	1.2	4000	0	0	0		3.0	4000	0		
	"	5500	0				4.0	4000	0		
	1.65	4000	0	0	0	15.9	0.89	4000	0		
	"	5500	0				1.0	4000	0		
	2.0	4000	0	0	0	16	0.5	2000	0	0	
	"	5500	0	0	0		"	4000	0	0	
	2.2	4000	0	0	0		0.8	4000	0		
	"	5500	0	0	0		1.0	4000	0	0	0
	3.0	4000	0	0	0		1.2	4000	0	0	

SUS304・316・316L シームレスパイプ(4)

別公	肉厚	巨々		材質		hl 公文	内间	巨幺		材質	
外径	内厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
16	1.5	4000	0	0	0	18	1.5	4000	0	0	
	1.6	4000	0				2.0	4000	0	0	
	2.0	4000	0	0	0		2.5	4000	0		
	2.5	4000	0	0			3.0	4000	0		
	3.0	4000	0	0			4.0	4000	0		
	3.5	4000	0			19	0.5	2000	0		
	4.0	4000	0				"	4000	0		
17	0.5	2000	0				0.8	4000	0		
	0.8	4000	0				1.0	4000	0	0	0
	1.0	4000	0				1.2	4000	0	0	
	1.5	4000	0				1.5	4000	0	0	0
17.3	1.0	4000	0				1.6	4000	0		
	1.2	4000	0	0	0		2.0	4000	0	0	
	"	5500	0				2.5	4000	0		
	1.65	4000	0	0	0		3.0	4000	0		
	"	5500	0	0	0		3.5	4000	0		
	2.0	4000	0	0	0		4.0	4000	0		
	"	5500	0	0	0	20	0.5	4000	0		
	2.3	4000	0	0	0		0.8	4000	0		
	"	5500	0	0	0		1.0	4000	0	0	0
	3.2	4000	0	0	0		1.5	4000	0	0	0
	"	5500	0	0	0		2.0	4000	0	0	
	"	6000	0				2.5	4000	0		
	4.0	4000	0				3.0	4000	0	0	
18	0.5	4000	0				4.0	4000	0		
	0.8	4000	0				5.0	4000	0		
	1.0	4000	0	0	0	21.7	1.2	4000	0	0	
	1.2	4000	0				1.65	4000	0	0	0

SUS304・316・316L シームレスパイプ(5)

PI 2Δ	中国	لا ⊞		材質		bl 4マ	中国	FF &		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
21.7	1.65	5500	0	0		23.0	1.5	4000	0		
	2.1	4000	0	0	0		2.0	4000	0		
	"	5500	0	0	0		3.0	4000	0		
	"	6000	0	0		24.0	1.0	4000	0		
	2.5	4000	0	0	\circ		2.0	4000	0		
	"	5500	0	0	0		4.0	4000	0		
	"	6000	0			25.0	0.5	2000	0		
	2.8	4000	0	0	0		1.0	4000	0	0	
	"	5500	0	0	\circ		1.2	4000	0		
	"	6000	0	0	\circ		1.5	4000	0	0	
	3.7	4000	0	0	0		2.0	4000	0	0	
	"	5500	0	0	0		"	6000	0		
	"	6000	0	0			2.5	4000	0		
	4.7	4000	0	0	0		3.0	4000	0	0	
	"	5500	0	0	0		3.5	4000	0		
	"	6000	0	0			4.0	4000	0	0	
	7.5	4000	0				5.0	4000	0	0	
	"	5500	0				5.5	4000	0		
22.0	0.5	2000	0				6.0	4000	0		
	0.8	4000	0			25.4	1.0	4000	0		
	1.0	4000	0	0	0		1.2	4000	0	0	
	1.5	4000	0	0	0		1.5	4000	0	0	
	2.0	4000	0				1.6	4000	0		
	2.5	4000	0				2.0	4000	0	0	0
	3.0	4000	0				2.5	4000	0		
	4.0	4000	0				3.0	4000	0	0	
	4.5	4000	0				3.5	4000	0		
23	1.0	4000	0				4.0	4000	0	0	

SUS304・316・316L シームレスパイプ(6)

外径	肉厚	長さ		材質		外径	肉厚	長さ		材質	
グ州主	内字	XC	304	316	316 L	グM王	内序	KC	304	316	316 L
25.4	4.5	4000	0			28	3.0	4000	0		
	5.0	4000	0				4.0	4000	0		
	6.0	4000	0				5.0	4000	0		
26	3.0	4000	0				6.5	4000	0		
27.2	1.2	4000	0	0			7.5	4000	0		
	1.65	4000	0	0	0	29	1.0	4000	0		
	"	5500	0			30	1.0	4000	0		0
	2.1	4000	0	0	0		1.5	4000	0		
	"	5500	0	0	0		2.0	4000	0	0	
	"	6000	0	0	0		2.5	4000	0		
	2.5	4000	0	0	0		3.0	4000	0	0	0
	"	5500	0	0	0		3.5	4000	0		
	"	6000	0				4.0	4000	0		
	2.9	4000	0	0	0		5.0	4000	0	0	
	"	5500	0	0	0		6.0	4000	0	0	
	"	6000	0	0			8.0	4000	0		
	3.9	4000	0	0	0	32	1.0	4000	0		
	"	5500	0	0	0		1.2	4000	0		
	"	6000	0				1.5	4000	0	0	
	4.5	4000	0				2.0	4000	0	0	
	5.5	4000	0	0	0		3.0	4000	0	0	
	"	5500	0	0	0		3.5	4000	0		
	"	6000	0				4.0	4000	0	0	
	7.8	4000	0				5.0	4000	0		
	"	5500	0				6.0	e	0	0	
28	1.0	4000	0				7.0	4000	0		
	1.5	4000	0				8.0	e	0	0	
	2.0	4000	0			34	1.0	4000	0		

SUS304・316・316L シームレスパイプ(7)

b) 公	肉厚	E ×		材質		hì 公文	肉厚	巨々		材質	
外径	内厚	長さ	304	316	316 L	外径	内厚	長さ	304	316	316 L
34	1.2	4000	0			35	5.0	4000	0		
	1.65	4000	0	0	0	36	3.0	4000	0		
	"	5500	0		0		"	6000	0		
	2.0	4000	0	0	0		4.0	4000	0		
	"	5500	0				5.5	4000	0		
	2.5	4000	0				6.5	4000	0		
	"	6000	0				8.0	4000	0	0	
	2.8	4000	0	0	0		9.0	4000	0		
	"	5500	0	0	0		10.0	ℓ	0		
	"	6000	0		0	38	1.0	4000	0		
	3.0	4000	0	0	\bigcirc		1.2	4000	0		
	"	5500	0	0	\circ		1.5	4000	0	0	
	"	6000	0	0	\circ		2.0	4000	0	0	
	3.4	4000	0	0	0		3.0	4000	0	0	
	"	5500	0	0	0		3.5	4000	0		
	"	6000	0	0	0		4.0	4000	0	0	
	4.0	4000	0				4.5	4000	0		
	4.5	4000	0	0	0		5.0	4000	0	0	
	"	5500	0	0	0		5.5	4000	0		
	"	6000	0	0	0		6.0	4000	0	0	
	5.0	4000	0				7.0	4000	0		
	"	6000	0				8.0	4000	0	0	
	6.4	4000	0	0	0		9.0	4000	0		
	"	5500	0	0	0	40	1.0	4000	0		
	"	6000	0	0	0		1.5	4000	0		
	9.1	4000	0	0	0		2.0	4000	0		
	"	5500	0	0	0		3.0	4000	0		
	"	6000	0	0			3.5	4000	0		

SUS304・316・316L シームレスパイプ(8)

₩₩	中国	لا ∺		材質		bi ムマ	中国	ע דּו		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
40	4.0	4000	0			42.7	6.4	5500	0	0	0
	5.0	4000	0	0			"	6000	0		0
	6.0	4000	0				7.0	l	0	0	
	7.0	4000	0				8.0	l	0		
	7.5	4000	0				9.1	4000	0		
	8.0	4000	0				"	5500	0		
	9.0	4000	0				"	6000	0		
	10.0	4000	0	0			9.5	4000	0	0	
42	10.0	4000	0			44	5.0	l	0		
42.7	1.65	4000	0	0	0	45	2.0	4000	0		
	"	5500	0	0			3.0	4000	0	0	
	2.0	4000	0				4.0	4000	0		
	2.8	4000	0	0	0		5.0	4000	0	0	
	"	5500	0	0	0		5.5	l	0		
	"	6000	0				6.5	l	0	0	
	3.0	4000	0	0	0		7.0	4000	0		
	"	5500	0	0	0		8.0	ℓ	0	0	
	"	6000	0	0			8.5	4000	0		
	3.6	4000	0	0	0		10.0	4000	0	0	
	"	5500	0	0	0		"	6000	0		
	"	6000	0		0		11.5	l	0		
	4.0	l	0				12.5	6000	0		
	4.5	l	0			48.6	1.65	4000	0	0	0
	4.9	4000	0	0	0		"	5500	0		0
	"	5500	0	0	0		2.0	4000	0	0	
	"	6000	0				2.8	4000	0	0	0
	6.0	l	0				"	5500	0	0	0
	6.4	4000	0	0	0		"	6000	0		

SUS304・316・316L シームレスパイプ(9)

PI VA	内层	E 2		材質		カレムマ	中国	Fiy		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
48.6	3.0	4000	0	0	0	50.8	6.0	4000	0		
	"	5500	0	0	0		6.5	4000	0		
	"	6000	0	0			7.0	4000	0		
	3.5	4000	0				7.5	4000	0		
	3.7	4000	0	0	0		8.0	ℓ	0		
	"	5500	0	0	0		10.0	ℓ	0	0	
	"	6000	0	0	0		10.5	4000	0		
	4.0	4000	0				12.5	4000	0		
	5.1	4000	0	0	0		13.5	4000	0		
	"	5500	0	0	0	52	3.5	4000	0		
	"	6000	0	0	0		6.0	4000	0		
	6.0	4000	0				7.5	4000	0	0	
	7.1	4000	0	0	0		10.0	4000	0	0	
	"	5500	0	0	0		14.0	4000	0	0	
	"	6000	0	0		54	2.0	4000	0		
	8.0	ℓ	0				3.0	4000	0		
	10.2	4000	0				3.5	4000	0	0	
	"	5500	0	0	0		4.0	4000	0		
50	7.0	ℓ	0				5.0	4000	0		
	9.0	l	0				6.0	4000	0		
	12.5	l	0	0			9.0	6000	0		
	14.0	ℓ	0				12.5	6000	0		
50.8	1.5	4000	0	0			15.0	5000	0		
	2.0	4000	0	0		55	2.0	4000	0		
	3.0	4000	0	0			5.0	4000	0		
	4.0	4000	0	0			5.5	4000	0		
	5.0	4000	0				8.0	4000	0		
	5.5	l	0			56	3.0	4000	0		

SUS304・316・316L シームレスパイプ(10)

別公	内匠	E &		材質		かるマ	内匠	E >		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
56	6.0	4000	0			60.5	3.5	6000	0		0
	8.0	4000	0	0			3.9	4000	0	0	0
	10.0	4000	0	0			"	5500	0	0	0
	14.0	6000	0	0			"	6000	0	0	0
	17.0	4000	0				4.9	4000	0	0	
57	2.0	4000	0				"	6000	0		
	3.0	4000	0				5.5	4000	0	0	0
	4.0	ℓ	0				"	5500	0	0	0
	6.0	ℓ	0				"	6000	0	0	0
	7.5	ℓ	0				6.0	4000	0		
58	10.0	4000	0				"	6000	0		
60	7.0	ℓ	0				"	ℓ	0	0	
	12.5	l	0	0			8.7	4000	0	0	0
	14.0	l		0			"	5500	0	0	0
	15.0	ℓ	0				"	6000	0		0
	17.5	4000	0				10.0	6000	0		
60.5	1.65	4000	0	0	0		11.1	4000	0	0	
	"	5500	0				"	5500	0	0	
	"	6000	0				"	6000	0		
	2.0	4000	0	0			13.0	6000	0		
	2.8	4000	0	0	0		15.0	6000	0	0	
	"	5500	0	0	0		18.0	4000	0		
	"	6000	0	0	0	62	7.0	4000	0		
	3.0	4000	0	0	0	63	8.0	ℓ	0	0	
	"	5500	0	0			11.5	ℓ	0		
	"	6000	0				15.5	ℓ	0		
	3.5	4000	0	0	0		17.5	l	0		
	"	5500	0	0	0	63.5	2.0	4000	0		

SUS304・316・316L シームレスパイプ(11)

PI 7A	内匠	E Y		材質		かるマ	内匠	E >		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
63.5	3.0	4000	0			68	8.0	ℓ	0		
	4.0	4000	0			70	2.0	4000	0		
	5.0	6000	0				3.0	4000	0		
	6.0	6000	0				4.0	4000	0		
	6.5	6000	0	0	0		5.0	4000	0	0	
	7.0	4000	0				"	6000	0		
	10.0	4000	0	0			6.5	ℓ	0	0	
	12.0	4000	0				7.0	6000	0		
	13.5	4000	0				8.0	4000	0		
	16.0	ℓ	0				"	6000	0		
65	2.0	4000	0				10.0	4000	0		
	3.0	4000	0				"	5000	0	0	
	3.5	l	0				12.5	4000	0		
	4.0	ℓ	0				"	5500	0	0	
	5.0	ℓ	0	0			15.0	e	0	0	
	6.0	4000	0				18.0	4000	0		
	7.0	4000	0				20.0	6000	0		
	8.5	ℓ	0			71	4.0	4000	0		
	10.0	4000	0	0			5.5	5000		0	
	12.0	6000	0	0			"	6000		0	
	13.5	6000	0				7.5	4000	0		
	15.0	6000	0	0			"	6000	0		
	18.0	6000	0				10.5	6000			0
	20.0	6000	0				13.0	ℓ	0	0	
67	7.0	6000	0				15.0	l	0		
	8.0	6000	0				17.5	4000	0	0	
	10.0	4000	0			73	3.5	6000	0		
68	6.0	l	0				5.0	4000	0		

SUS304・316・316L シームレスパイプ(12)

別公	肉厚	E ×		材質		b) 公文	内间	巨々		材質	
外径	内厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
73	5.0	5500	0			76.3	8.0	ℓ	0		
	7.0	4000	0				9.5	4000	0	0	0
	"	6000	0	0			"	5500	0	0	0
	10.0	4000	0				"	6000	0		0
	12.5	6000	0				10.0	ℓ	0	0	
	15.0	4000	0				12.5	4000	0		
75	10.0	4000	0				"	6000	0		
	12.5	ℓ	0				13.5	ℓ	0	0	
	15.0	4000	0				14.0	4000		0	
	17.5	ℓ	0				15.0	4000	0		0
76.3	2.1	4000	0	0	0		"	6000	0	0	
	"	5500	0				18.0	ℓ	0	0	
	3.0	4000	0	0	0		20.0	ℓ	0		
	"	5500	0	0	0		23.0	ℓ	0		
	"	6000	0	0	0	80	2.0	4000	0		
	3.5	4000	0	0	0		3.0	4000	0		
	"	5500	0	0			4.0	4000	0		
	"	6000	0				5.0	ℓ	0		
	4.0	4000	0				6.0	ℓ	0		
	"	5500	0				8.5	ℓ	0		
	5.2	4000	0	0	0		10.0	6000	0	0	
	"	5500	0	0	0		12.5	4000	0		
	"	6000	0		0		15.0	4000	0	0	0
	6.0	4000	0				16.0	ℓ	0		
	"	l	0	0			17.5	ℓ	0		
	7.0	4000	0	0	0		20.0	ℓ	0	0	
	"	5500	0	0	0		25.0	4000	0		
	"	6000	0		0	81	6.0	ℓ	0		

SUS304・316・316L シームレスパイプ(13)

hl 公	内间	E ×		材質		hì 公文	内匠	巨々		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
82	13.0	6000	0			89.1	5.5	6000	0		0
82.6	3.0	4000	0				6.6	4000	0		
	5.0	ℓ	0				"	ℓ	0	0	
83	8.5	ℓ	0				7.6	4000	0	0	
	10.0	l	0				"	5500	0	0	0
85	8.0	6000	0				"	6000	0	0	0
	8.5	ℓ	0				11.1	4000	0	0	0
	10.0	6000	0	0			"	5500	0	0	0
	12.5	4000		0			"	6000	0		0
	"	6000	0	0			15.2	4000	0		
	15.0	4000	0	0			"	6000	0	0	
	20.0	4000	0			90	10.0	l	0	0	
	"	6000	0	0			13.0	4000	0		
	22.5	l	0				13.5	l	0	0	
	25.0	4000	0				15.0	5000		0	
	"	6000	0				16.0	6000	0		
	27.5	l	0				17.5	6000	0		
89.1	2.1	4000	0	0	0		20.0	5000	0	0	
	"	5500	0				22.5	5000	0		
	3.0	4000	0	0	0		25.0	6000	0		
	"	5500	0	0	0	92	11.0	ℓ	0		
	"	6000	0	0	0		15.0	5000		0	
	4.0	4000	0	0	0	95	5.0	6000	0		
	"	5500	0	0	0		7.5	6000	0	0	
	"	6000	0				10.0	6000	0	0	
	5.0	4000	0				12.5	6000	0	0	
	5.5	4000	0	0	0		14.5	6000	0		
	"	5500	0	0	0		15.0	4000	0		

SUS304・316・316L シームレスパイプ(14)

PI 소스	中国	لا ⊞		材質		かい	中国	لا ∺		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
95	16.0	6000	0	0		101.6	12.7	4000	0	0	0
	17.5	6000	0				"	5500	0	0	
	20.0	5000	0				"	6000	0		0
	22.5	4000	0	0			15.0	4000	0	0	
	25.0	4000	0	0			20.0	6000	0		
100	10.0	6000	0	0			25.0	l	0		
	14.5	5000	0	0			26.0	l	0	0	
	15.0	4000	0			103	10.5	4000	0		
	17.5	5000	0			105	5.0	6000	0		
	18.5	l	0				9.0	ℓ	0		
	20.0	6000	0				10.0	5000	0	0	
	22.0	l	0	0		106	"	ℓ	0		
101.6	2.1	4000	0		\circ		13.0	4000	0	0	
	"	5500	0				17.5	6000	0	0	
	"	6000	0				20.0	ℓ	0		
	3.0	4000	0	0	0		25.0	ℓ	0	0	
	"	5500	0	0	0		27.5	ℓ	0		
	"	6000	0			108	13.0	4000	0		
	4.0	4000	0	0	0	110	10.0	4000	0	0	
	"	5500	0	0			13.0	5000	0		
	"	6000	0				15.0	6000	0		
	5.7	4000	0	0	0		20.0	4000	0	0	
	"	5500	0	0	0	112	16.0	4000	0	0	
	"	6000	0		0		21.0	l	0		
	7.0	l	0				24.5	4000	0		
	8.1	4000	0	0	0	114.3	2.1	4000	0	0	0
	"	5500	0		0		"	5500	0		0
	"	6000	0	0	0		"	6000	0		

SUS304・316・316L シームレスパイプ(15)

PI 73	内匠	E Y		材質		からマ	内匠	Eν		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
114.3	3.0	4000	0	0	0	120	4.0	ℓ	0		
	"	5500	0	0	0		5.0	6000	0		
	"	6000	0	0	0		8.0	l	0		
	4.0	4000	0	0	0		10.0	6000	0	0	
	"	5500	0	0	0		13.0	6000	0		
	"	6000	0				15.0	6000	0		
	5.0	4000	0				20.0	4000	0	0	
	6.0	4000	0	0	0		25.0	ℓ	0		
	"	5500	0	0	0		26.0	ℓ		0	
	"	6000	0	0	0		27.0	4000	0		
	7.1	ℓ	0	0			30.0	5000	0		
	8.6	4000	0	0	0	125	5.0	ℓ	0		
	"	5500	0	0	0		10.0	5000	0	0	
	"	6000	0	0	0		12.5	6000	0	0	
	11.1	4000	0	0	0		15.0	ℓ	0		
	"	5500	0	0	0		17.5	ℓ	0	0	
	"	6000	0		0		20.0	ℓ	0		
	13.5	4000	0	0	0		22.5	ℓ	0		
	"	5500	0	0	0		25.0	ℓ	0		
	"	6000	0		0		27.0	ℓ	0		
	16.0	4000	0			127	5.0	5000	0		
	17.1	4000	0				6.0	ℓ	0		
	"	6000	0		0		7.0	6000	0		
	20.0	6000	0				8.0	6000	0	0	
	25.0	l	0				10.0	6000	0		
117	13.5	l	0				20.0	l	0		
118	14.0	l	0				27.0	ℓ	0		
	23.5	l	0			130	5.0	6000	0		

SUS304・316・316L シームレスパイプ(16)

PI 2스	力區	ע דּו		材質		bl 4マ	中国	ע דּו		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
130	7.0	6000	0			139.8	6.6	5500	0	0	0
	10.0	l	0				"	6000	0		0
	12.5	4000	0				9.5	4000	0	0	0
	14.0	ℓ	0				"	5500	0	0	0
	15.0	l	0				"	6000	0	0	0
	16.0	l					12.7	4000	0	0	
	20.0	l	0				"	5500	0	0	0
132	6.0	l	0				"	6000	0	0	
	10.0	5000	0				15.9	4000	0	0	0
	13.0	l	0	0			"	5500	0	0	0
	16.0	l	0				"	6000	0		0
	21.0	l	0	0			20.0	5500	0		
	23.5	l	0				"	6000	0		
	26.0	l	0				21.0	6000	0		
	27.5	l	0				25.0	l	0	0	
	30.5	ℓ	0			140	14.0	4000	0		
	31.0	ℓ	0				20.0	l	0	0	
135	10.0	ℓ	0				25.0	l	0	0	
	15.0	l	0				30.0	l	0		
	20.0	l	0				35.0	l	0		
139.8	2.8	4000	0			145	10.0	6000	0		
	3.4	4000	0	0	0		12.5	6000	0		
	"	5500		0	0		13.0	4000	0	0	0
	"	6000	0	0	0		15.0	l	0		
	5.0	4000	0	0	0		20.0	l	0	0	
	"	5500	0	0	0		25.0	l	0		
	"	6000	0	0	0		30.0	l	0		
	6.6	4000	0	0	0	150	10.0	6000	0	0	

SUS304・316・316L シームレスパイプ(17)

PI 72	内匠	Eν		材質		かる	内回	EX		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
150	12.5	ℓ	0			165.2	5.0	4000	0	0	0
	15.0	6000	0				"	5500	0	0	0
	17.5	ℓ	0				"	6000	0	0	0
	20.0	ℓ	0				7.1	4000	0	0	0
	22.0	ℓ	0	0			"	5500	0	0	0
	25.0	ℓ	0				"	6000	0	0	0
	30.0	ℓ	0				9.3	4000	0		
	35.0	ℓ	0				11.0	4000	0	0	
152	22.0	ℓ	0				"	5500	0	0	0
152.4	10.0	4000	0				"	6000	0		0
154	"	ℓ	0				14.3	4000	0	0	0
155	"	4000	0				"	5500	0	0	0
	15.0	ℓ	0	0			"	6000	0	0	
	20.0	ℓ	0	0			18.2	4000	0	0	0
	26.0	ℓ	0				"	5500	0		0
160	5.0	6000	0				"	6000	0	0	0
	10.0	6000	0				21.9	ℓ	0		
	12.5	6000	0				24.0	ℓ	0		
	15.0	ℓ	0	0			25.0	ℓ	0		
	20.0	ℓ	0	0			27.0	ℓ	0		
	24.0	ℓ	0				30.0	ℓ	0		
	29.0	ℓ	0			170	10.0	ℓ	0		
	30.0	ℓ	0				15.0	ℓ	0	0	
	35.0	ℓ	0				20.0	ℓ	0		
165.2	2.8	4000	0				25.0	ℓ	0		
	3.4	4000	0	0	0		26.0	ℓ	0		
	"	5500	0	0	0		32.0	ℓ	0		
	"	6000	0	0		175	10.0	ℓ	0		

SUS304・316・316L シームレスパイプ(18)

b) 公	内间	長さ		材質		hì公	肉厚	巨々		材質	
外径	肉厚	KC	304	316	316 L	外径	内学	長さ	304	316	316 L
175	15.0	l	0			200	25.0	l	0		
180	10.0	l	0				28.0	ℓ	0		
	12.5	ℓ	0				30.0	ℓ	0		
	15.0	l	0	0			40.0	ℓ	0		
	18.0	ℓ	0			206.0	20.0	l	0		
	20.0	ℓ	0	0		212	21.0	ℓ	0	0	
	25.0	ℓ	0				27.0	ℓ	0		
	27.5	ℓ	0				41.0	l	0		
	30.0	l	0			216.3	2.8	4000	0		
	35.0	l	0				4.0	4000	0	0	0
185	10.0	ℓ	0				"	6000	0		
	15.0	ℓ	0				6.5	4000	0	0	
	20.0	ℓ	0				"	5500	0	0	
190	10.0	ℓ	0				"	6000	0	0	0
	12.5	ℓ	0				8.2	4000	0	0	0
	15.0	ℓ	0				"	5500	0	0	
	17.5	ℓ	0				"	6000	0	0	0
	20.0	ℓ	0	0			10.3	ℓ	0		
	22.5	ℓ	0				12.7	4000	0	0	
	25.0	ℓ	0				"	5500	0	0	
	28.0	ℓ	0				"	6000	0	0	0
	30.0	ℓ	0				18.2	4000	0		
190.7	7.0	6000	0				"	5500	0		
	10.0	ℓ	0				"	6000	0	0	0
	11.0	4000			0		23.0	4000	0	0	0
200	10.0	l	0				"	6000	0		0
	15.0	l	0				27.0	4000	0		
	20.0	ℓ	0	0			30.0	ℓ	0		

SUS304・316・316L シームレスパイプ(19)

PI 72	内匠	Eν		材質		かるマ	内匠	E V		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
216.3	33.0	l	0			267.4	28.6	6000	0		0
220	25	l	0			318.5	4.5	4000	0		
224	15.0	ℓ	0				6.5	4000	0		
	22.0	ℓ	0				"	6000	0		
	32.0	ℓ	0				10.3	5500			0
	42.0	l	0				"	6000	0	0	0
232	9.0	6000	0				17.4	5500	0		0
	16.0	l	0	0			"	6000	0	0	0
	21.0	l	0	0			21.4	l	0		
236	16.0	l	0				25.4	6000	0		
	23.0	l	0				33.3	6000	0		0
	30.0	l	0			355.6	11.1	6000	0	0	0
	43.0	l	0				19.0	6000	0	0	0
250	15.0	l	0			406.4	12.7	6000	0		0
	20.0	ℓ	0				21.4	6000	0		0
	25.0	ℓ	0	0							
	30.0	ℓ	0								
	35.0	ℓ	0								
255	24.0	ℓ	0								
267.4	4.0	4000	0								
	6.5	4000	0								
	"	5500	0	0							
	"	6000	0								
	9.3	5500	0	0							
	"	6000	0	0	0						
	15.1	6000	0	0	0						
	18.2	6000	0	0							
	21.4	6000	0								

SUS304・316・316L BAパイプ(1)

₩₩	中国	Eν		材質		₩₩	中區	F 2		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
1.58	0.4	2000		0		6.35	1.65	4000		0	
2	0.5	2000		0		7	0.5	2000	0		
3	0.5	2000	0	0		"	"	4000	0		
"	1.0	2000	0	0		8	0.5	2000	0		
3.18	0.5	2000	0	0		"	"	4000	0		
"	0.72	2000	0	0	0	"	0.8	4000	0		
"	1.0	2000	0	0		"	1.0	2000	0	0	0
4	0.5	2000	0	0		"	"	4000	0	0	
"	1.0	2000	0	0		"	1.5	4000		0	
4.76	0.8	2000		0		9	0.5	2000	0		
5	0.5	2000	0			"	"	4000	0		
"	0.8	2000	0			9.53	0.89	2000		0	
"	"	4000	0			"	"	4000	0	0	
"	1.0	2000	0	0		"	1.0	2000	0	0	0
6	0.5	2000	0			"	"	4000	0	0	0
"	"	4000	0			"	1.24	4000	0	0	0
"	0.8	4000	0			"	1.65	4000		0	
"	1.0	2000	0	0		10	0.5	2000	0		
"	"	4000	0	0	0	"	"	4000	0		
"	1.2	4000		0		"	0.8	4000	0		
"	1.5	4000		0		"	1.0	2000	0	0	0
6.35	0.5	2000	0			"	"	4000	0	0	
"	"	4000	0			"	1.5	4000	0	0	
"	0.89	2000	0	0	0	11	0.5	2000	0		
"	"	4000	0	0	0	"	"	4000	0		
"	1.0	2000	0	0	0	12	0.5	2000	0		
"	"	4000	0	0	0	"	"	4000	0		
"	1.24	4000		0		"	1.0	2000	0	0	0

SUS304・316・316L BAパイプ(2)

hl 4₹	内匠	Eν		材質		원 2호	内匠	EV		材質	
外径	肉厚	長さ	304	316	316 L	外径	肉厚	長さ	304	316	316 L
12	1.0	4000	0								
"	1.2	4000		0							
"	1.5	4000	0	0							
12.7	1.0	2000	0	0	0						
"	"	4000	0	0	0						
"	1.24	2000	0	0	0						
"	"	4000	0	0	0						
"	1.65	4000		0							
"	2.11	4000		0							
13.8	1.2	4000	0								
14	1.0	4000	0								
15	1.0	4000	0								
15.88	1.0	4000	0	0	0						
"	1.24	4000		0							
"	1.65	4000		0							
17	1.0	4000	0								
17.3	1.2	4000	0								
18	1.0	4000	0								
19	1.5	4000	0								
19.05	1.24	4000	0	0	0						
"	1.65	4000	0	0	0						
20	1.0	4000	0								
21.7	1.65	4000	0		0						
25.4	1.65	4000			0						
27.2	1.65	4000	0		0						
34	1.65	4000	0		0						
48.6	1.65	4000			0						
60.5	1.65	4000			0						

SUS304極細パイプ(セミシームレス)

長さ⇨1000

規格サイズ	外 径	内 径	肉厚
7 G	4.57	4.01	0.28
8 G	4.20	3.64	0.28
9 G	3.75	3.19	0.28
10 G	3.40	2.84	0.28
11 G	3.06	2.64	0.21
12 G	2.76	2.40	0.18
13 G	2.41	1.99	0.21
14 G	2.11	1.69	0.21
15 G	1.81	1.45	0.18
16 G	1.61	1.25	0.18
17 G	1.48	1.12	0.18
18 G	1.26	0.90	0.18
19 G	1.06	0.70	0.18
20 G	0.88	0.58	0.15
21 G	0.81	0.51	0.15
22 G	0.71	0.41	0.15
23 G	0.63	0.33	0.15
24 G	0.55	0.30	0.125
25 G	0.51	0.26	0.125
26 G	0.45	0.23	0.11
27 G	0.41	0.19	0.11
28 G	0.35	0.17	0.09
29 G	0.33	0.15	0.09
30 G	0.31	0.13	0.09
29 G	0.33	0.15	0.09

SUS304 ロール用パイプ

外径	肉厚	長さ	外径	肉厚	長さ
60	2.0	2000	100	2.0	1650
75	"	1650		"	1800
	"	1800		"	2000
	"	2000		"	2200
	"	2200		"	2300
	"	2300		"	2400
	"	2400		"	2500
	"	2500		"	2600
	"	2600		"	2800
	"	2800	100	3.0	1650
	"	3000		"	1800
75	3.0	1650		"	2000
	"	1800		"	2200
	"	2000		"	2300
	"	2200		"	2400
	"	2300		"	2500
	"	2500		"	2600
	"	2600		"	2800
	"	2800		"	3000
	"	3000		"	3300
			125	"	2000