

SUS304・316・316Lフラットバー・四角棒(1)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
				304			304	316 316L	304					304	316 316L					
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延	
2×6	2000	0.19		○						3×15	4000	1.43		○	○	○	○	○		
	8	〃	0.254		○						16	〃	1.52		○	○			○	
9	〃	0.286		○						19	〃	1.81		○	○			○	○	
10	3000	0.477		○					○	20	〃	1.90	1.92	○	○	○	○	○	○	○
	4000	0.636		○	○				○		22	〃	2.09		○	○			○	
12	〃	0.76		○						25	〃	2.38	2.39	○	○	○	○	○	○	○
15	〃	0.952		○	○				○	30	〃	2.86	2.87	○	○	○	○	○	○	○
20	〃	1.27		○	○				○	32	〃	3.04	3.06	○	○	○	○	○	○	○
25	〃	1.58		○	○				○	35	〃	3.33		○	○			○	○	
30	〃	1.90		○	○				○	38	〃	3.62	3.64	○	○	○	○	○	○	○
32	〃	2.03		○	○				○	40	〃	3.81	3.83	○	○	○	○	○	○	○
35	〃	2.22							○	42	〃	4.00		○	○					
38	〃	2.41		○					○	45	〃	4.28		○	○			○	○	
40	〃	2.54		○	○				○	48	〃	4.56		○	○					
45	〃	2.86		○	○				○	50	〃	4.76	4.80	○	○	○	○	○	○	○
50	〃	3.17		○	○				○	60	〃	5.72		○	○	○	○	○	○	
										65	〃	6.20		○	○			○	○	
3×3	2000	0.142		○						75	〃	7.12		○	○	○		○		
	5	3000	0.357		○					90	〃	8.56		○						
6	〃	〃	0.429		○					100	〃	9.52		○	○	○		○		
	4000	0.572		○						110	〃	10.5		○						
7	〃	0.668		○						120	〃	11.4		○						
8	〃	0.76		○						125	〃	11.9		○						
9	〃	0.856		○						130	〃	12.4		○						
10	〃	0.952		○	○				○	140	〃	13.3		○						
12	〃	1.14		○	○				○	150	〃	14.3		○						
13	〃	1.24		○	○				○											

SUS304・316・316Lフラットバー・四角棒(2)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	H L	#400	圧延	HOT	圧延			304	316 316L	コールド	H L	#400	圧延	HOT	圧延
4× 4	4000	0.508		○						5× 8	4000	1.27		○					
	9	1.14		○							9	1.43		○					
	10	1.27		○	○						10	1.58		○	○				
	11	1.40		○	○				○		12	1.90		○	○				
	12	1.52		○							13	2.06		○	○				
	13	1.65		○	○				○		15	2.38		○	○	○	○	○	
	15	1.90		○	○	○	○	○			16	2.54		○	○				
	16	2.03		○	○			○	○		19	3.01		○	○			○	○
	17	2.16		○							20	3.17	3.19	○	○	○	○	○	○
	19	2.41		○	○			○	○		22	3.49		○	○			○	○
	20	2.54		○	○	○	○	○			25	3.96	3.99	○	○	○	○	○	○
	22	2.79		○	○			○	○		30	4.76	4.80	○	○	○	○	○	○
	25	3.17	3.19	○	○	○	○	○	○		32	5.08	5.12	○	○	○	○	○	○
	30	3.81	3.83	○	○	○	○	○	○		34	5.40		○	○				
	32	4.08		○	○	○	○	○			35	5.56		○	○			○	○
	35	4.44		○	○			○	○		38	6.04	6.08	○	○	○	○	○	○
	38	4.84		○	○	○	○	○			40	6.36	6.40	○	○	○	○	○	○
	40	5.08	5.12	○	○	○	○	○	○		45	7.12						○	○
	45	5.72		○	○			○	○		50	7.92	8.00	○	○	○	○	○	○
	50	6.36	6.40	○	○	○	○	○	○		60	9.52		○	○	○	○	○	
	60	7.60		○	○	○	○	○			65	10.3		○	○	○	○	○	
	65	8.24		○	○			○	○		75	11.9		○	○	○	○	○	
	75	9.52		○	○	○	○	○			90	14.3		○	○			○	○
	90	11.4		○	○						100	15.8		○	○	○	○	○	
	100	12.7		○	○	○			○		130	20.6		○					
											150	23.8		○	○				
5× 5	4000	0.792		○	○														

SUS304・316・316Lフラットバー・四角棒(3)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延
6× 6	4000	1.14		○	○					6× 42	4000	8.00		○	○				
	9	1.71		○							45	〃	8.56		○	○	○	○	○
	10	1.90		○	○						48	〃	9.12		○	○		○	○
	12	2.28		○	○					50	〃	9.52	9.56	○	○	○	○	○	○
	13	2.48		○	○						5000	11.9					○		
	15	2.86		○	○	○	○	○			6000	14.3			○	○		○	○
	16	3.04		○	○					60	4000	11.4		○	○	○	○	○	
	18	3.42		○	○					65	〃	12.4	12.40	○	○	○	○	○	○
	19	3.62		○	○		○	○			5000	15.4					○		
	20	3.81	3.83	○	○	○	○	○	○		6000	18.5			○	○		○	○
	22	4.20		○	○		○	○		70	4000	13.3		○	○		○	○	
25	〃	4.76	4.80	○	○	○	○	○	○	75	〃	14.3	14.40	○	○	○	○	○	○
	5000	5.95					○				5000	17.8					○		
	6000	7.14					○				6000	21.4			○	○		○	○
30	4000	5.72	5.76	○	○	○	○	○	○	90	4000	17.1		○	○		○	○	
	5000	7.15					○			100	〃	19.0	19.20	○	○	○	○	○	○
	6000	8.58			○		○				5000	23.8					○		
32	4000	6.08	6.12	○	○	○	○	○	○	110	6000	28.6		○	○		○	○	
	5000	7.60					○				4000	20.9			○	○			○
	6000	9.12					○				120	〃	22.8		○	○			○
35	4000	6.68		○	○		○	○		125	〃	23.8		○	○			○	
38	〃	7.24	7.28	○	○	○	○	○	○	130	〃	24.8		○	○			○	
	5000	9.05					○			140	〃	26.6		○	○			○	
	6000	10.90			○		○	○	○	150	〃	28.6		○	○			○	
40	4000	7.60	7.68	○	○	○	○	○	○	7× 7	4000	1.56		○	○				
	5000	9.50					○				20	〃	4.44					○	
	6000	11.4			○		○	○											

SUS304・316・316Lフラットバー・四角棒(4)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット				
				304			304	316 316L	304					304	316 316L						
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延		
8× 8	4000	2.03		○	○	○				9× 32	5000	11.4					○				
	10	ノ	2.54		○	○					6000	13.7			○	○		○			
	16	ノ	4.08		○	○		○			35	4000	10.0			○	○		○		
	25	ノ	6.36					○			38	ノ	10.8	10.9	○	○	○	○		○	○
	30	ノ	7.60					○				5000	13.6						○		
	32	ノ	8.12		○	○	○	○			6000	16.3			○	○		○			
	35	ノ	8.88					○			40	4000	11.4			○	○	○	○		
	38	ノ	9.64		○	○		○				5000	14.2						○		
	40	ノ	10.2					○				6000	17.1			○	○		○		
	45	ノ	11.4					○				45	4000	12.8			○			○	
50	ノ	12.7		○	○		○		50	ノ	14.3	14.4	○	○	○	○		○	○		
	65	ノ	16.5				○			5000	17.8						○				
	75	ノ	19.0				○			6000	21.4			○	○		○				
	100	ノ	25.4					○			55	4000	15.7					○			
											60	ノ	17.1			○	○	○	○		
	9× 9	4000	2.57		○	○	○				90	ノ	18.6	18.7	○	○	○	○		○	○
13		ノ	3.71		○	○		○		65		5000	23.2					○			
15		ノ	4.28		○	○	○	○		6000		27.8			○	○		○			
16		ノ	4.56		○	○		○		75		4000	21.4	21.6	○	○	○	○		○	○
19		ノ	5.44		○	○		○				5000	26.8						○		
20		ノ	5.72		○	○	○	○				6000	32.1			○	○		○		
22		ノ	6.28		○	○		○				4000	25.7	25.8	○	○		○		○	○
25		ノ	7.12	7.20	○	○	○	○		○		5000	32.1						○		
		6000	10.7		○	○						6000	38.5						○		
30		4000	8.56	8.60	○	○	○	○		○		100	4000	28.6	28.7	○	○	○	○		○
	6000	12.8		○	○					5000	35.7							○			
32	4000	9.12	9.20	○	○	○	○		○	6000	42.8				○	○		○			

SUS304・316・316Lフラットバー・四角棒(5)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
		304		316 316L		304			304			316 316L		304			304		316 316L	
		コールド	H L	#400	圧延	HOT	圧延	コールド	H L			#400	圧延	HOT	圧延					
9×125	4000	35.7		○	○		○			75	4000	23.8		○	○	○	○			
	5000	44.6					○				6000	35.7		○						
	6000	53.5					○				4000	31.7	31.9	○	○	○	○		○	
150	4000	42.8		○	○		○			100	5000	39.6					○			
	5000	53.5					○				6000	47.6		○			○			
	6000	64.2					○				125	4000	39.6		○	○		○		
200	4000	57.2		○	○		○			150	〃	47.6		○	○		○			
250	〃	71.2		○	○		○			200	〃	63.6		○	○		○			
300	〃	85.6		○			○			250	〃	79.2		○	○		○			
										300	〃	95.2		○			○			
10×10	4000	3.17		○	○	○	○													
	15	〃	4.76		○	○	○	○		12×12	4000	4.56		○	○	○	○			
	19	〃	6.04		○	○		○		14	〃	5.32		○						
	20	〃	6.36		○	○	○	○		15	〃	5.72					○			
	25	〃	7.92		○	○	○	○		16	〃	6.08		○	○					
	30	〃	9.52		○	○	○	○		19	〃	7.24		○	○		○			
	32	〃	10.2		○	○	○	○		20	〃	7.60		○	○	○	○			
	35	〃	11.1					○		25	〃	9.52	9.56	○	○	○	○			
	38	〃	12.0		○	○	○	○			6000	14.3		○						
	40	〃	12.7		○	○	○	○		28	4000	10.6					○			
	45	〃	14.3					○		30	4000	11.4		○	○	○	○			
	〃	15.8	16.0	○	○	○	○		〃		6000	17.1		○						
50	5000	19.8						○		32	4000	12.2	12.2	○	○	○	○			
	6000	23.8		○				○			6000	18.3		○	○					
60	4000	19.0						○		35	4000	13.3		○	○		○			
65	〃	20.6		○	○	○	○			38	〃	14.5	14.6	○	○	○	○			
	6000	30.9		○							5000	18.1					○			

SUS304・316・316Lフラットバー・四角棒(6)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット					
				304			304	316 316L	304					304	316 316L							
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延			
38	6000	21.7		○	○		○			13×13	4000	5.36		○	○	○	○					
40	4000	15.2		○	○	○	○			14×14	4000	6.20		○	○	○	○					
	6000	22.9		○	○																	
45	4000	17.1					○															
50	4000	19.0	19.2	○	○	○	○		○○	15×15	4000	7.12		○	○	○	○					
	5000	23.8					○															
	6000	28.6		○	○		○			16×16	4000	8.12		○	○	○	○					
65	4000	24.8	24.9	○	○	○	○		○○	19	〃	9.64		○	○							
	5000	31.0					○			20	〃	10.2		○	○	○	○					
	6000	37.1		○	○		○			25	〃	12.7	12.8	○	○	○	○		○○			
70	4000	26.6				○			30	〃	15.2					○						
75	〃	28.6	28.7	○	○	○	○		○○	32	〃	16.2	16.4	○	○	○	○		○○			
	5000	35.7					○			35	〃	17.8					○					
	6000	42.8		○	○		○			38	〃	19.3	19.4	○	○	○	○		○○			
90	4000	34.2				○			40	〃	20.3		○	○	○	○						
100	〃	38.1	38.3	○	○	○	○		○○	45	〃	22.8					○					
	5000	47.6					○			50	5000	31.7					○					
	6000	57.1		○	○		○															
125	4000	47.6		○	○		○			65	4000	33.0	33.2	○	○		○		○○			
	5000	59.5					○							5000	41.2					○		
	6000	71.4					○										6000	49.5		○		
150	4000	57.2		○	○		○			75	4000	38.1	38.3	○	○		○		○○			
	5000	71.5					○							5000	47.6					○		
	6000	85.8					○										6000	57.1		○		
200	4000	76.0		○	○		○		90	4000	45.6					○						
250	〃	95.2		○	○		○		100	〃	50.8	51.2	○	○		○			○○			

SUS304・316・316Lフラットバー・四角棒(7)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	H L	#400	圧延	HOT	圧延			304	316 316L	コールド	H L	#400	圧延	HOT	圧延
16×100	5000	63.5					○			75	4000	45.2	45.6	○	○		○		○
	6000	76.2		○			○			90	♪	54.4					○		
125	4000	63.6		○	○		○			100	♪	60.4	60.8	○	○		○		○
	5000	79.5					○				5000	75.5						○	
150	6000	95.4					○			6000	90.6						○		
	4000	76.0		○	○		○			125	4000	75.2		○	○		○		
200	5000	95.0					○			150	♪	90.4		○	○		○		
	6000	114					○			200	♪	120		○	○		○		
250	4000	102		○	○		○			250	♪	151		○	○		○		
300	♪	127		○	○		○			300	♪	181		○			○		
300	♪	152		○			○												
										20×20	4000	12.7	12.8	○	○	○	○		○
19×19	4000	11.4	11.5	○	○	○	○		○○	70	♪	44.4					○		
25	♪	15.1		○	○	○	○												
30	♪	18.1					○			22×22	4000	15.4	15.4	○	○		○		○○
32	4000	19.3		○	○	○	○			25	♪	17.4					○		
35	♪	21.1					○			30	♪	20.9					○		
38	♪	22.9		○	○	○	○			32	♪	22.3		○			○		
40	♪	24.1					○			35	♪	24.4					○		
45	♪	27.1					○			38	♪	26.5		○			○		
50	♪	30.1	30.3	○	○	○	○		○○	40	♪	27.9					○		
	5000	37.6					○			45	♪	31.4					○		
55	6000	45.2					○			50	♪	34.9		○			○		
	4000	33.1					○			65	♪	45.2		○			○		
65	♪	39.2	39.4	○	○		○		○○	75	♪	52.4		○			○		
	5000	48.9					○			90	♪	62.8					○		
	6000	58.7					○			100	4000	69.6		○			○		

SUS304・316・316Lフラットバー・四角棒(8)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット			
				304			304	316 316L	304					304	316 316L					
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延	
22×125	ㄥ	87.2					○			30×50	ㄥ	47.6			○			○		
150	ㄥ	105					○			55	ㄥ	52.4			○			○		
200	ㄥ	140					○			65	ㄥ	62.0			○			○		
250	ㄥ	174					○			75	ㄥ	71.2			○			○		
300	ㄥ	209					○			100	ㄥ	95.2			○			○		
										125	ㄥ	119						○		
25×25	4000	19.8	20.0	○	○	○	○		○○	150	ㄥ	143						○		
32	ㄥ	25.4		○			○			200	ㄥ	190						○		
38	ㄥ	30.1		○			○			250	ㄥ	238						○		
40	ㄥ	31.7					○			300	ㄥ	286						○		
45	ㄥ	35.7					○													
50	ㄥ	39.6		○			○			32×32	4000	32.5	32.7	○	○			○		○○
60	ㄥ	47.6					○													
65	ㄥ	51.6		○			○			35×50	4000	55.6			○			○		
75	ㄥ	59.6		○			○			×55	ㄥ	61.2						○		
100	ㄥ	79.2		○			○			×65	ㄥ	72.0			○			○		
125	ㄥ	99.2		○			○			×75	ㄥ	83.2			○			○		
150	ㄥ	119		○			○			×100	ㄥ	111			○			○		
200	ㄥ	158		○			○			×125	ㄥ	139						○		
250	ㄥ	198		○			○			×150	ㄥ	166						○		
300	ㄥ	238		○			○													
										36×36	4000	41.2	41.4	○				○		○○
26×26	4000	21.4		○																
										38×38	4000	46.0	46.0	○	○			○		○○
28×28	4000	24.9		○	○		○													
										40×40	4000	50.8	51.2	○				○		○○
30×30	4000	28.6	28.7	○	○		○		○○	50	ㄥ	63.6						○		

SUS304・316・316Lフラットバー・四角棒(9)

厚さ×幅	長さ	kg/P		コールド			ホット			厚さ×幅	長さ	kg/P		コールド			ホット		
				304			304	316 316L	304					304	316 316L				
		304	316 316L	コールド	HL	#400	圧延	HOT	圧延			304	316 316L	コールド	HL	#400	圧延	HOT	圧延
40× 65	〃	82.4					○			65×100	〃	206					○		
75	〃	95.2					○												
100	〃	127					○			70× 70	4000	156					○		
125	〃	158					○			100	〃	222					○		
150	〃	190					○			125	〃	278					○		
										150	〃	333					○		
42× 42	4000	56.0	56.4				○	○○											
										75× 75	4000	178					○		
45× 45	4000	64.4	64.8	○			○	○○											
										80×100	4000	254					○		
50× 50	4000	79.2	79.8	○			○	○○		125	〃	317					○		
65	〃	103					○			150	〃	381					○		
75	〃	119					○												
100	〃	158					○			90× 90	4000	257					○		
125	〃	198					○			100	〃	286					○		
150	〃	238					○			125	〃	357					○		
										150	〃	428					○		
55× 55	4000	96.0		○			○												
										100×100	4000	317					○		
60× 60	4000	114		○			○			×125	〃	396					○		
75	〃	143					○			×150	〃	476					○		
100	〃	190					○												
125	〃	238					○												
150	〃	286					○												
65× 65	4000	134		○			○												
75	〃	155					○												

SUS303 ホットフラットバー・四角棒(1)

長さ⇒4000

厚さ×幅	kg/P	厚さ×幅	kg/P	厚さ×幅	kg/P
6×25	4.76	16×50	25.4	75	59.6
30	5.72	65	33.0	100	79.2
40	7.60	75	38.1	150	119.0
50	9.52	100	50.8	200	158.0
65	12.4	150	76.0		
75	14.3	200	102.0	30×50	47.6
100	19.0			75	71.2
		19×25	15.1	100	95.2
9×25	7.12	30	18.1	150	143.0
30	8.56	40	24.1	200	190.0
40	11.4	50	30.1		
50	14.3	65	39.2	35×50	55.6
65	18.6	75	45.2	75	83.2
75	21.4	100	60.4		
100	28.6	150	90.4	35×100	111.0
		200	120.0		
12×25	9.52			40×50	63.6
30	11.4	22×25	17.4	75	95.2
40	15.2	30	20.9	100	127.0
50	19.0	40	27.9		
65	24.8	50	34.9	50×75	119.0
75	28.6	65	45.2	100	158.0
100	38.1	75	52.4		
150	57.2	100	69.6	四角棒	
200	76.0	150	105.0	16×16	8.12
		200	140.0	19×19	11.4
16×25	12.7			22×22	15.4
30	15.2	25×50	39.6	25×25	19.8
40	20.3	65	51.6	30×30	28.6

SUS303 ホットフラットバー・四角棒(2)

長さ⇨4000

厚さ×幅	kg/P	厚さ×幅	kg/P	厚さ×幅	kg/P
32×32	32.5				
35×35	38.9				
36×36	41.2				
40×40	50.8				
45×45	64.4				
50×50	79.2				
60×60	114.0				
65×65	134.0				
75×75	178.0				
90×90	257.0				
100×100	317.0				

SUS304・316・316L・430 アングル(1)

0 = 酸洗仕上品 H = 全面 HL 研磨品 4 = 外 2 面 # 400 研磨品

厚さ×幅	304						316・316L				430	
	4000		5000		6000		4000		6000		4000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨
2× 30											3.62	0・4
40											4.88	0・4
3× 20	3.58	0・H・4					3.60	0			3.47	0・4
25	4.52	0・H・4					4.56	0			4.40	0・4
30	5.48	0・H・4	6.85	0	8.22	0・H・4			8.28	0	5.32	0・4
35					9.66	0						
40	7.40	0・H・4	9.25	0	11.1	0・H・4			11.2	0	7.20	0・4
45					12.8	0						
50	9.48	0・H			14.2	0・H						
4× 30					10.6	0						
35	8.4	0			12.6	0						
40	9.64	0・H・4			14.5	0・H・4						
45					16.6	0						
50	12.4	0・H	15.4	0	18.5	0・H・4			18.7	0		
55					20.4	0						
5× 30					13.1	0						
35					15.5	0						
40	11.9	0・H	14.9	0	17.9	0・H・4			18.0	0		
45					20.5	0						
50	15.2	0・H	19.0	0	22.9	0・H・4			23.0	0		
60					27.6	0						
65					30.3	0						
70					32.7	0						
75					35.0	0						
6× 30					15.2	0						
35					18.2	0						
40	14.0	0			21.0	0・H						

SUS304・316・316L・430 アングル(2)

0 = 酸洗仕上品 H = 全面 HL 研磨品 4 = 外 2 面 # 400 研磨品

厚さ×幅	304						316・316L				430	
	4000		5000		6000		4000		6000		4000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨
6× 45					24.1	0						
50	17.9	0・H	22.4	0	26.9	0・H・4			27.0	0		
55					29.8	0						
60					32.6	0・H・4						
65	23.9	0・H	29.8	0	35.8	0・H・4			36.1	0		
70					38.6	0						
75	27.7	0・H	34.6	0	41.5	0・H・4			41.8	0		
80					44.4	0						
90					50.2	0						
100	37.3	0	46.6	0	55.9	0・H・4						
7× 70					44.5	0						
8× 50					34.7	0						
60					42.3	0						
65					46.4	0						
70					50.2	0						
75					54.1	0						
80					57.8	0・H						
90					66.0	0						
100	48.8	0			73.2	0・H						
9× 50	25.8	0			38.6	0・H						
60					47.2	0						
65					51.8	0						
70					56.1	0						
75	40.4	0・H			60.6	0・H・4			60.6	0		
80					64.8	0						
90	49.2	0			73.8	0・H						
100					82.2	0						

SUS304・316・316L・430 アングル(3)

0 = 酸洗仕上品 H=全面 HL 研磨品 4 = 外2面#400研磨品

厚さ×幅	304						316・316L				430	
	4000		5000		6000		4000		6000		4000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨	kg/P	研磨
9× 125					103.0	0						
150					125.0	0						
10× 50					42.5	0						
60					52.1	0						
65					57.1	0						
75					66.6	0						
80					70.8	0						
90					81.0	0						
100	60.4	0・H			90.6	0・H・4			91.2	0		
12× 75					78.6	0						
80					84.0	0						
90					96.0	0						
100					107.0	0						
12× 125					136.0	0						
130					142.0	0						
150					165.0	0						
15× 125					168.0	0						
150					203.0	0						

SUS304不等辺アングル SUS304 コールド(ピン角)アングル

0 = 酸洗仕上品

0 = 未研磨

厚さ×辺×辺	6,000	
	kg/P	研磨
● 4× 45×30	13.6	0
● 6× 50×30	21.4	0
● 65×50	31.7	0
75×50	34.4	0
● 75×65	38.8	0
100×75	48.8	0
125×75	55.9	0
7× 75×50	39.5	0
● 100×75	56.7	0
● 9× 75×50	50.0	0
● 90×75	67.2	0
100×75	71.4	0
125×75	82.2	0
150×90	99.0	0
12×150×90	130.0	0

厚さ×辺	4,000		6,000	
	kg/P	研磨	kg/P	研磨
3×20	3.54	0		
25	4.48	0		
30	5.44	0	8.16	0
40	7.36	0	11.0	0
50	9.24	0	13.9	0
4×30			10.7	0
40			14.5	0
50			18.3	0
5×30			13.1	0
40	11.9	0	17.9	0
50			22.6	0
6×30			15.5	0
40			21.2	0
50			26.9	0
60			32.6	0
65			35.5	0
75			41.2	0
9×50			39.0	0
75			60.6	0

● = 片辺切断品

※表面肌 = 熱間圧延品の引抜肌

SUS304・430 フォーミングアングル

C = C G 肌 H = 酸洗肌 2 = 2 B 4 = 外 2 面 # 400 研磨品


鋼種 長さ 厚さ×幅	304				430	
	4,000		6,000		4,000	
	kg/P	研磨	kg/P	研磨	kg/P	研磨
2× 20	2.37	C・2			2.30	C・2
25	3.01	C・2			2.92	C・2
30	3.64	C・2・4			3.54	C・2・4
40	4.92	C・H・2・4			4.76	C・2・4
3× 15	2.48	C・2				
20	3.44	C・H・2・4			3.24	C・4
25	4.40	C・2・4			4.24	C・4
30	5.32	C・H・2・4	7.98	C・H・2	5.20	C・4
40	7.24	C・H・2・4	10.9	C・H・2	7.04	C・4
50			13.6	C・H・2		
4× 50			17.8	C		
5× 40			17.1	C		
50			21.8	C・H		
65			29.0	H		
75			33.7	C・H		
6× 50			25.7	C・H		
60			31.4	C・H		
65			34.3	C・H		
70			37.1	H		
75			40.0	C・H		
80			42.8	H		

SUS304スモールアングル

厚さ×辺	4.000
	kg/P
1.0 × 9	0.568
10	0.632
12	0.760
13	0.824
16	1.01
19	1.20
25	1.53
1.2 × 19	1.39
25	1.90
30	2.17
32	2.32
1.5 × 30	2.85
32	3.04
外面HL SPV	


SUS304フォーミングC形鋼

厚さ×縦×横×A	6,000
	kg/P
2 × 40×20× 8	8.28
50×25×10	10.7
52×20× 8	9.48
60×20× 8	10.2
60×30×10	12.5
60×30×15	13.1
70×20× 8	11.2
75×40×15	16.4
75×45×15	17.8
80×40×14.5	17.2
100×50×19.5	22.0
100×50×20	21.6
120×60×19.5	25.8
125×50×20	24.0
2 B 外面HL SPV	



SUS304フォーミングチャンネル


厚さ×縦×横	6,000
	kg/P
3 × 40 × 10	8.1
40 × 20	11.0
50 × 12.5	10.3
50 × 25	13.8
60 × 15	12.4
60 × 30	16.7
75 × 35	20.3
80 × 20	16.7
80 × 40	22.4
100 × 25	21.0
100 × 50	28.1
120 × 60	33.8
150 × 50	34.5
4 × 100 × 50	36.3
5 × 80 × 40	36.9
100 × 50	46.4
150 × 50	58.7
6 × 60 × 30	32.5
80 × 40	44.0
100 × 50	55.4
125 × 65	71.1
CG・外面HL SPV	



SUS304・316・316L チャンネル

鋼種 長さ 重量 厚さ×縦×横	304			316		316L	
	4,000	5,000	6,000	4,000	6,000	4,000	6,000
	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P
3×40×20			10.8				
50×25			13.7				
4×100×50	24.8		37.2		37.4		37.4
5×80×40	23.9	29.9	35.9		36.1		36.1
100×50	30.6	38.2	45.9		46.2		46.2
6×100×50	36.0	45.0	54.1		54.4		54.4
● 120×60			65.4				
130×65	48.0	60.0	72.0		72.6		72.6
150×75	55.6	69.5	83.4		84.0		84.0
※ 200×100	74.8		112.0				
※ 8×200×100	98.4		148.0				
9×150×75	81.2		122.0		122.0		122.0
● 10×200×100	121.2		182.0		183.0		183.0

※溶接品
●圧延品と溶接品



SUS304ワイドチャンネル

長さ 重量 厚さ×縦×横	6,000	長さ 重量 厚さ×縦×横	6,000
	kg/P		kg/P
6 × 220 × 65	96.6	9 × 300 × 90	198.0
230 × 65	99.6	300 × 100	206.0
250 × 75	111.0	10 × 250 × 100	205.0
9 × 250 × 75	164.0	300 × 90	219.0
250 × 90	176.0	300 × 100	229.0

※全て溶接品です
※304L・316・316Lも製作できます

SUS304 H形鋼

圧延品

高さ×幅×ウェブ×フランジ	6,000
	kg/P
100 × 100 × 6 × 8	103.0
125 × 125 × 6.5 × 9	143.0
148 × 100 × 6 × 9	125.0
150 × 150 × 7 × 10	188.0
200 × 100 × 5.5 × 8	127.0
200 × 200 × 8 × 12	302.0
250 × 250 × 9 × 14	435.0

※表面肌は酸洗仕上品

溶接品

高さ×幅×ウェブ×フランジ	6,000
	kg/P
75 × 75 × 5 × 8	71.40
100 × 100 × 6 × 8	100.0
125 × 125 × 7 × 9	143.0
148 × 100 × 6 × 9	123.0
150 × 150 × 8 × 10	192.0
200 × 100 × 6 × 8	128.0
200 × 200 × 8 × 12	295.0
250 × 125 × 6 × 9	173.0
250 × 9 × 14	428.0
300 × 300 × 10 × 16	584.0

※表面肌は酸洗仕上品

